

IM30 V2


FORMIDABLE Smart Unattended (Outdoor)



Transportation



Self-Service



Powered by
Android 10



PCI 6.x
SRED



5" HD
Display




















2MP
Front




















IP65
IK08

SPECIFICATIONS

	Operating System	PayDroid Powered by Android 10
	Processor	Quad-core ARM Cortex-A53 1.6GHz
	Memory	8GB Flash + 1GB LPDDR4 RAM Optional: 2GB LPDDR4 RAM
	Card Readers	Chip & PIN Contactless Magnetic Stripe
	Cameras	2MP Front-Facing
	QR Scanner	2MP Reads 1D & 2D Codes
	Display	5" TFT 720 x 1280, IPS
	Comms Configurations	4G + Ethernet + WiFi (dual band) + Bluetooth 5.0 Ethernet + WiFi (dual band) + Bluetooth 5.0 Ethernet-Only
	Power	7V - 48V DC via MDB slave or RS232 or Digital I/O 24V DC via JVMA
	SIM / SAM	2 SAM (optional 4)
	Keys / Buttons	1 Reset Key 1 Service Key
	Audio	1 Speaker
	Ports	2 RS232 1 USB Host 1 USB OTG 1 LAN 1 MDB Slave 1 HDMI 1 Digital I/Os 1 Mic & Speaker 1 MDB Master 1 SMA (optional) 1 SIM Slot (optional) GPS (optional)
	Physical	External Dimension: W x H x D: 105 x 146 x 47mm Installation Cutout: W x H: 82 x 107mm
	Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Accessories	Mounting Fixture External Antenna (optional)
	Certifications	PCI PTS 6.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs UL IC FCC UKCC Felica VCCI ATEX IP65 IK08



SPECIFICATIONS

	Operating System	PayDroid Powered by Android 7.1
	Processor	Quad-core ARM Cortex-A53 1.6GHz
	Memory	8GB Flash + 1GB LPDDR4 RAM Optional: 2GB LPDDR3 RAM
	Card Readers	Chip & PIN Contactless Magnetic Stripe
	Cameras	2MP Front-Facing
	QR Scanner	0.3MP Reads 1D & 2D Codes
	Display	5" TFT 720 x 1280, IPS
	Comms Configurations	4G + Ethernet + WiFi (dual band) + Bluetooth 5.0 Ethernet + WiFi (dual band) + Bluetooth 5.0 Ethernet-Only
	Power	12V - 48V DC via MDB Slave 12V - 48V DC via RS232 19V - 30V AC via Executive
	SIM / SAM	2 SAM (optional 4)
	Keys / Buttons	1 Reset Key 1 Service Key
	Audio	1 Speaker
	Ports	2 RS232 1 USB Host 1 USB OTG 1 LAN 1 MDB Slave 1 HDMI 1 Digital I/Os 1 Mic & Speaker 1 MDB Master 1 SMA (optional) 1 SIM Slot (optional)
	Physical	External Dimension: W x H x D: 105 x 146 x 47mm Installation Cutout: W x H: 82 x 107mm
	Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Accessories	Mounting Fixture External Antenna (optional)
	Certifications	PCI PTS 5.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs UL IC FCC UKCC Felica VCCI ATEX IP55 IK08

