

## **EPOS Litchi Pro**

## L1610/L1611/L1612



Food & Beverage



Fashion & Retail



Supermarket





Powered by Android 14



Octa-Core



15.6" IPS Main Display



Wi-Fi® 6



Bluetooth® 5.0





## **SPECIFICATIONS**

| <b>(2)</b> | Operating System          | Android 14, GMS Certified, Supporting UNIPHIZ UI   |
|------------|---------------------------|--|
|            | Processor                 | Octa-Core Cortex A72 2.2GHz   NPU: 6TOPS   |
|            | Memory                    | LPDDR4X 4GB + eMMC 64GB Optional: LPDDR4X 6GB + eMMC 128GB External: microSD Card Slot Up to 256GB   |
| <u></u>    | Cameras                   | Optional: Main Screen Camera: 5MP Auto Focus<br>Optional: Secondary Screen Camera: 5MP Auto Focus  |
|            | Displays                  | Main Display: 15.6" 1920 × 1080 px IPS Touch Screen Secondary Display: L1610: N/A L1611: 10.1" 1280 × 800 Pixels IPS Screen, Optional Touch L1612: 15.6" 1920 × 1080 Pixels IPS Screen, Optional Touch |
| ((†))      | Comms<br>Configurations   | Wi-Fi® 6   Bluetooth® 5.0  |
| -1  1      | Audio                     | Speaker: 3W Microphone   |
|            | Card Readers              | Optional: NFC on the Secondary Screen (Card Reader, Card Emulation)  |
|            | SAM                       | Optional: 1 Mini SAM   |
| ھے         | Buttons                   | Power Button   |
|            | Battery                   | Lithium-ion Polymer Battery, 3.8V / 7000mAh  |
| 0          | Ports                     | 1 Type-A 3.0   3 Type-A   1 Type-C 3.0   1 LAN (1000M)  1 DK (RJ11, 24V / 12V)<br>1 RS232(RJ45)   DC IN   Audio Jack   Optional: 6 PIN POGO PIN  |
| <b>Ģ</b> = | Power                     | Input: 100-240V AC, 1.0A   Output: 24V DC, 1.5A  |
| Ð          | Power Indicator           | White LED  |
|            | Physical                  | 364.6 × 220.0 × 322.4mm<br>L1610: 5kg   L1611: 6kg   L1612: 7kg  |
| <b>∫</b> ≡ | Environmental             | Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F)<br>Storage Temperature: -20°C ~ 60°C (-4°F ~ 140°F)<br>Relative Humidity: 10% ~ 93%, Non-Condensing   |
|            | Accessories<br>(Optional) | MSR Reader   MSR + Chip + NFC Reader   3D Camera   |







