


Version	SWB LS	LWB HS
<b>General Information</b>		
Classification	L7e-CU	NA
Body structure	Load-bearing	Load-bearing
Dimensions (L × W × H)	2815 × 1250 × 1890 mm	3100 × 1250 × 1890 mm
Width (Front/Rear)	1550 <sup>(Mirror opened)</sup> / 1235 mm	1550 <sup>(Mirror opened)</sup> / 1235 mm
Wheelbase	1900 mm	2125 mm
Seats / Doors	1 / 2	1 / 2
Ramp angles (Front/Rear)	90° / 22°	90° / 22°
Track Width (Front/Rear)	966 / 1043 mm	966 / 1043 mm
Min. turning radius	5000 mm	5000 mm
Min. ground clearance	140 mm	140 mm
GVW (Gross)	1200 kg	1200 kg
Curb weight (Net)	611 kg	692 kg
<b>Cargo Box</b>		
Box Volume	1.6 m <sup>3</sup>	1.95 m <sup>3</sup>
Cargo Outside (L × W × H)	1242 × 1194 × 1277 mm	1510 × 1194 × 1277 mm
Cargo Inside (L × W × H)	1143 × 1158 × 1207 mm	1397 × 1158 × 1207 mm
Cargo Payload <sup>2</sup>	439 kg	358 kg
Load Height	705 mm	705 mm
<b>Electric Motor</b>		
Motor Type / Drive Mode	PMSM / RWD	PMSM / RWD
Transmission	Fixed ratio	Fixed ratio
Top Speed	45 km/h	70 km/h
Peak Power (Rated)	7.5 kW (3.7 kW)	15 kW (7.5 kW)
Peak Torque (Rated)	55 N.m (27.5 N.m)	85 N.m (42.5 N.m)
Driving Range (WMTC)	90 km	130 km
Real-world Driving Range <sup>1</sup>	72+ km	104+ km
Energy Consumption	≈ 107 Wh/km	≈ 111 Wh/km
Energy Efficiency	≈ 9 km/Wh	≈ 9 km/Wh
CO2 emission	0 g/km	0 g/km
<b>Battery Pack</b>		
Battery Type	LiFePO4 (Air-cooled)	LiFePO4 (Air-cooled)
Battery Pack Capacity <sup>3</sup>	7.68 kWh	11.52 kWh
Battery Pack Nominal Voltage	76.8V	76.8V
Battery Pack Rated Capacity	100Ah	150Ah
<b>Charging</b>		
Charging Mode	AC Slow Charging	AC slow charging
On-board Charger (OBC)	1.8 kW	3.3 kW
Charging Time (20-80%) <sup>4</sup>	≈ 3.2 h	≈ 2.6 h
Charging Time (0-100%) <sup>4</sup>	≈ 5.3 h	≈ 4.4 h
Charging Distance in 1 hour (est.)	≈ 11 km	≈ 30 km
<b>Tires &amp; Suspensions</b>		
Brake (Front / Rear)	Disc / Drum	Disc / Drum
Wheels	Aluminium Alloy	Aluminium Alloy
Tire	145/70R12 (LT)	145/70R12 (LT)
Front suspension	McPherson	McPherson
Rear suspension	Leaf Spring	Leaf Spring



Version	SWB LS	LWB HS
<b>Lights</b>		
Front combination light	Halogen	Halogen
Daytime running light	Halogen	Halogen
Turn Signal Lights	Halogen	Halogen
Combination Tail light	LED	LED
Rear fog & Reversing light	LED	LED
Interior lighting	LED	LED
<b>Standard Accessories</b>		
CBS Combined Braking System	Power Windows	Bluetooth connectivity
Intermittent Windshield Wiper	Analogue Instrument Cluster	OBD Connection
Imitation Leather Seat Covers	Heating	Rear-view Camera
2-way Manual Seats	Rearview Mirrors <sup>(manual)</sup>	Key-in Ignition
1 × USB Port	9" LCD Infotainment Display	EU Type2 Charging Plug
Reversing Warning Alarm	Key FOB / Keyless Entry	Portable Charger (220V)
2 × Cup Holders	3-point Safety Belt <sup>(retractable)</sup>	Warning Triangle & Safety Vest
Central Door Lock	4 × Loudspeaker	Drive Mode Dialer (R N D)
Adjustable Air Vents		
<b>Powertrain Upgrade</b>		
Battery Pack Upgrade <sup>3</sup>	11.5 kWh (150Ah / 76V)	23 kWh (300Ah / 76V)
• Driving Range (RW range)	130 km (100+ km)	260 km (200+ km)
• Peak Motor Power	15 kW	15 kW
• Peak Torque Power	85 N.m	85 N.m
• Horse Power 20 hp	20 hp	27 hp
• On-board Charger (OBC)	3.3 kW	3.3 kW
• Curb Weight	690 kg	720 kg
• Payload	350 kg	330 kg
<b>Options</b>		
3.3 kW On-board Charger (OBC)	•	○
6.6 kW On-board Charger (OBC)	•	•
Alloy Wheel	•	•
Rooftop Solar Panel	•	•
Air Condition	•	•
Driver: LHD	•	•
Roof Rack Platform	•	•
<b>Warranty</b>		
Battery Pack	4 years or 200,000 km <sup>(whichever comes first)</sup>	4 years or 200,000 km <sup>(whichever comes first)</sup>
Vehicle	3 years or 40,000 km <sup>(whichever comes first)</sup>	3 years or 40,000 km <sup>(whichever comes first)</sup>

<sup>1</sup> The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain accessories and weather conditions.

<sup>2</sup> Payload excludes the driver (75 kg) and includes cargo options. The total permissible cargo weight must not be exceeded.

<sup>3</sup> Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.

<sup>4</sup> Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included in the calculation.

Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures within a similar weight class. Please check with your dealer for any local specifications.



## CONTACT US

Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com

Sophie +86 183 6122 7440 | sophieyu@jonwayev.com

[www.jonwayev.com](http://www.jonwayev.com)