




















Lens

QR Reader



SPECIFICATIONS

| | | |
|---|--------------------------------|--|
| | Model Name | T3350 |
|  | Operating System | RunthOS |
|  | Processor | Windows / Android / Linux / Mac OS |
|  | Supporting System | 32 bit Security Processor |
|  | Reading Precision | 1D ≥ 5mil, 2D ≥ 10mil |
|  | Reading Sensitivity | Picth ± 50° Yaw ± 50° Roll ± 360° |
|  | Drop Height | 0.8m |
|  | Power | Input: 5.0V DC, 500mA |
|  | Physical | 87.2 x 87.2 x 77.7mm, 204g |
|  | Buttons | 1 Left Button 1 Menu Button 1 Right Button |
|  | Ports | 2.0 Type-A male connector, 1.5m |
|  | Indicators | Optional: LED indicator, Buzzer, Audio Speaker |
|  | Comms Configurations | USB 2.0 Optional: Bluetooth® 4.2 |
|  | Displays | 0.96" 80 x 160 Pixel, TFT LCD |
|  | Typical Depth of Field | Code128: 10 ~ 160mm (15mil), QR Code: 0 ~ 300mm (40mil) |
|  | Symbologies | Mobile 1D : Code128, 2D : QR Code and etc |
|  | Cameras | CMOS Image Sensor, 0.3MP |
|  | Minimum Symbol Contrast | ≥ 30% |
|  | Memory | 8M Flash + 1M SRAM |
|  | Environmental | Operating Temperature: -10°C ~ 50°C (14°F ~ 122°F) Storage Temperature: -20°C ~ 70°C (-4°F ~ 158°F) Relative Humidity: 10% ~ 93%, non-condensing |

