

## SSM-T02

### 拧入型温度传感器/Screw-in type temperature sensor

- 测温范围/Measuring range : -50~350°C (pt100) 0~600°C (K、J)
- 热电阻、热电偶可选/Thermal resistance, thermocouple optional
- 多种安装接口可选/Multiple Process connection optional
- 良好的热传导性/High thermal conductivity



### 技术规格/Technique parameter

#### 产品性能/Product Performance

|                          |   |
|--------------------------|---|
| 长期漂移/Long-Term Stability | ±0.05%FS、0.1°C每年/year (取较大者/The bigger one) |
| 精度/Accuracy              | A级 (pt100)                                  |
|                          | I 级热电偶/Thermocouple ±0.4%t                  |
|                          | II级热电偶/Thermocouple ±0.75%t                 |
| 响应时间/Response Time       | t 0.9=10sec                                 |

#### 物理特征/Physical Characteristics

|                         |                                     |
|-------------------------|-------------------------------------|
| 安装接口/Process connection | 参见订购指南/See Ordering Guide           |
| 保护管/Protection tube     |                                     |
| 材质/Material             | SS304、SS316L                        |
| 直径/Diameter             | 6mm、8mm、10mm等/etc.                  |
| 连接电缆/Connecting cable   |                                     |
| 硅胶/Silica gel           | 环境温度/Ambient temperature -50~180°C  |
| 聚四氟乙烯/PTEF Teflon       | 环境温度/Ambient temperature -190~260°C |
| 金属网/Metal mesh          | 环境温度/Ambient temperature -50~350°C  |
| 重量/Weight               | 根据实际产品/According to physical object |

#### 环境数据/Environmental Data

|                   |         |
|-------------------|---------|
| 认证/Authentication | CE、RoHS |
|-------------------|---------|

### 特有技术规格/Specific technical specifications


#### 电阻输出/Resistance Output

|                          |                        |
|--------------------------|------------------------|
| 输出 (3线) /Output (3-wire) | pt100 (3线)             |
| 输出 (4线) /Output (4-wire) | pt100 (4线)、pt1000 (4线) |

#### 热电势输出/Thermopower Output

|                          |                 |
|--------------------------|-----------------|
| 输出 (2线) /Output (2-wire) | mv (2线) /2-wire |
|--------------------------|-----------------|

## 外型尺寸/External dimensions



### 拧入型温度传感器 (SSM-T02)

型号表示: SSM-T02-①-②-③/④-⑤⑥⑦

| 系列号<br>Series | ①分度号<br>Graduation | ②安装接口<br>Process connection   | ③探杆直径<br>Probe diameter | ④探杆长度<br>Probe length | ⑤电缆长度<br>Cable length | ⑥电缆材质<br>Cable Material | ⑦末端方式<br>Terminal mode | 参数描述<br>Parameter description |
|---------------|--------------------|-------------------------------|-------------------------|-----------------------|-----------------------|-------------------------|------------------------|-------------------------------|
| SSM-T02       | RTD                | 2G<br>4G<br>1GM<br>4N<br>XX * | 6<br>8                  | 25<br>50<br>XX *      | 1M<br>XX *            | 2J<br>4F                | U<br>XX *              | pt100三线制/3-wire               |
|               | RTD2               |                               |                         |                       |                       |                         |                        | pt100双支/Double-Branch         |
|               | J                  |                               |                         |                       |                       |                         |                        | J型热电偶/J-type                  |
|               | K                  |                               |                         |                       |                       |                         |                        | K型热电偶/K-type                  |
|               |                    |                               |                         |                       |                       |                         |                        | G1/4                          |
|               |                    |                               |                         |                       |                       |                         |                        | G1/2                          |
|               |                    |                               |                         |                       |                       |                         |                        | G1/8活动螺纹/Movable thread       |
|               |                    |                               |                         |                       |                       |                         |                        | 1/2NPT                        |
|               |                    |                               |                         |                       |                       |                         |                        | 其他规格/Other *                  |
|               |                    |                               |                         |                       |                       |                         |                        |                               |
|               |                    |                               |                         |                       |                       |                         |                        | Φ8mm                          |
|               |                    |                               |                         |                       |                       |                         |                        | 25mm                          |
|               |                    |                               |                         |                       |                       |                         |                        | 50mm                          |
|               |                    |                               |                         |                       |                       |                         |                        | 其他规格/Other *                  |
|               |                    |                               |                         |                       |                       |                         |                        | 1000mm                        |
|               |                    |                               |                         |                       |                       |                         |                        | 其他规格/Other *                  |
|               |                    |                               |                         |                       |                       |                         |                        | 标准/Standard                   |
|               |                    |                               |                         |                       |                       |                         |                        | 硅胶/Silica gel                 |
|               |                    |                               |                         |                       |                       |                         |                        | 聚四氟乙烯/PTEF Teflon             |
|               |                    |                               |                         |                       |                       |                         |                        | 标准/Standard                   |
|               |                    |                               |                         |                       |                       |                         |                        | U型插片/U-shaped insert          |
|               |                    |                               |                         |                       |                       |                         |                        | 其他规格/Other *                  |

#### 注意事项/Attention:

1、带 "\*" 号请联系技术人员

With "\*", please contact the technician