








Cylinder Cell Equipment

| Item Number & Name | Photo | Description | Price | Die Price |
|---|---|--|--------------|-----------|
| MRX-DH650 Spot Welding Machine |  | Max output power: 10KVA Welding current: 00 - 99A Power: AC220V±10% 50 - 60Hz Input air pressure: 0.3 - 0.7MPa Application: welding materials 0.03mm - 0.25mm Whole equipment weight: 45Kg Dimension: L 400 x W 560 x H 400mm | \$ 2,700.00 | N/A |
| MRX-DH1000 Ultrasonic Metal Welding Machine |  | Power: 1000W Working volt: AC220V / 50Hz Working compressed air source: 0.5 -0.7Mpa Working frequency: 40KHz Input power: 0 - 1000VA Welding time: 0-1s Controller dimension: L 360 x W 480 x H 200mm Welder dimesion: L 300 x W 460 x H 270mm | \$ 13,600.00 | N/A |
| MRX-FT300 Electrode Slitting Machine |  | Cutting width: 20 - 300mm Electrode thickness: 80 - 300um Burrs ≤ 25um Dia of cutting blade: 85mm Cutting speed: Max 4m/min adjustable Dimension: L 850 x W 920 x H 400mm Weight: 100kg | \$ 11,500.00 | N/A |
| MRX-GC650 Cylinder Cell Grooving Machine |  | Standard machine equipped with a set of 18650 cylindrical battery grooving dies (Other cylindrical battery dies are available). Component material: high-strengthen chrome steel, surface is treated with electroplating and painting to prevent corrosion. Adjustable range of grooving depth: 1.2-2mm Grooving speed: 300r/S (adjustable) Grooving width: 1.1 - 1.5mm (depends on the thickness of grooving cutter) Accuracy: ±0.1mm Output: 6 - 8/min Power supply: 220v/50HZ 140W Compressed air: 0.5 - 0.7MPa | \$ 5,600.00 | N/A |

Prices are for reference only, please inquire for a quote.

Cylinder Cell Equipment

| Item Number & Name | Photo | Description | Price | Die Price |
|--|---|---|-------------|-----------|
| MRX-JR90 Manual Winding Machine |  | Power supply: 220V/50Hz Power: 40W Rotating speed: 0 - 170r/min, adjustable Applicable cylindrical battery core: dia <math>< \Phi 30</math> Dimension: 360mm x 310mm x 280mm Weight: 25Kg | \$ 2,200.00 | N/A |
| MRX-JZ300 Electrolyte Diffusion Chamber |  | The chamber is made of anti-corrosion aluminum. Diffusion time can be regulated from 0 to 9999s. Vacuum can reach -90KPa (vacuum pump not included). Power supply: 220V/50Hz Power: 50W Compressed air source: 0.5 - 0.7Mpa Working temperature: -20 - 40 ^{°C} Dimension inside the chamber: L 355mm x W 256mm x H 325mm Weight: about 40KG | \$ 4,700.00 | N/A |
| MRX-SF650 Cylindrical Cell Crimping Machine |  | Standard machine equipped with a set of 18650 cylindrical battery crimping dies (Other cylindrical battery dies are available). Sealing pressure: pressure gauge at 55-800kg/cm ² Service life of mold is more than 300,000 uses. Component material: high-strength chrome steel with electroplating and painting to prevent corrosion. Dimension: 235mm x 190mm x 360mm Weight: 40kg | \$ 3,700.00 | N/A |

Prices are for reference only, please inquire for a quote.