

Hydraulic breaker in illustrations.

Load and stability diagram available on request.

BHB 105

PERFORMANCE

Slewing speed	6,5 s/245°
Transport speed, max.	2,7 km/h; 1.7 mph
Climbing inclination, max.	30°

HYDRAULIC SYSTEM

Hydraulic system capacity	27 l; 7.1 US gal
Pump type	Variable load-sensing
System pressure	18 MPa; 2 610 psi
Pump flow max. 50Hz and 60Hz	27 l/min; 7 US gal/min

POWER SYSTEM

Power technology	SmartPower™
Electric motor type	ABB
Power*	9,8 kW
Recommended fuse size*	16 A
Starting device	Direct start

CONTROL SYSTEM

Control type	SmartRemote, portable
Signal code	
Digital	
Transfer	Professional radio/Cable
Range, radio	Up to 300 m

WEIGHT

Machine weight**	560 kg; 1 235 lb
Recommended attachment weight	105 kg; 231 lb

NOISE LEVEL

Sound power level LWA***	90 dB(A)
Width min.	597 mm; 23.5 in
Height min.	880 mm; 34.6 in
Vertical reach (incl. breaker)	3200 mm; 126 in
Horizontal reach (incl. breaker)	2700 mm; 106.3 in

*Valid for 400V/50Hz and 440V/60Hz

**Excluding attachment and extra equipment

***Measured according to directive 2000/14/EC







