# NEW Arrival



Multimeter Function Comparision								
Model	NF-531	NF-532	NF-5310B	NF-5320A	NF-5320D	NF-5330A	NF-5330C	
DC Voltage	200mV~600V ±0.5%+3	60mV~600V ±0.5%+3	1000V ± (0.5%+4)	6V~1000V ± (0.5%+4)	6V-1000V ± (0.5%+4)	0.1V~1000V ± (0.5%+3)	0.1V~1000V ± (0.5%+3)	
AC Voltage	200mV~600V ±I%+3	60mV~600V ±1%+3	700V ± (0.5%+4)	6V-750V ± (0.8%+3)	6V-750V ± (0.8%+3)	0.1V~750V ± (0.5%+3)	0.1V~750V ± (0.5%+3)	
DC Current	200mA~10A ±1.2%+3	600uA~10A ±1.2%+3		600µA~10A ± (0.8%+8)	6A-10A ± (0.8%+8)			
AC Current		600uA~10A ±1.5%+3		600µA~10A ± (1.0%+8)	6A-10A ± (1.0%+8)			
Resistance	200Ω~200kΩ(±1.0%+3) 2MΩ~20MΩ(±1.5%+3)	600Ω~600kΩ(±1.0%+3) 6MΩ~60MΩ(±L5%+3)	60MΩ ± (0.8%+5)	600Ω~40MΩ ± (1.0%+8)	$600Ω \sim 60MΩ$ ± (1.0%+8)	0.1Ω~60MΩ ± (0.8%+3)	0.1Ω~60MΩ ± (0.8%+3)	
Capacitance		10nF-1000uF(±4.0%+5) 10mF/100mF(±5.0%+5)	60mF ± (3. 5%+20)	60nF~6mF±(5.0%+10) 30mF±(5.0%+10)	60nF~6mF ± (2.5%+60) 30mF ± (5.0%+10)	10pF~60mF ± (3.5%+20)	10pF~60mF ± (3.5%+20)	
Frequency		10Hz-1000kHz(±1.0%+3) 10MHz(±3.0%+3)	√	10Hz~10MHz ± (0.01%+5)			0.01Hz~8MHz ± (0.01%+3)	
Duty Cycle		1%-99%	1%-99%±(1.0%+2)	0.1%-99%				
Display counts	2000 counts	6000 counts	6000 counts	6000 counts	6000 counts	6000 counts	6000 counts	
Auto/Manual range			Auto	Manual	Manual	Auto	Auto	
LED Display			$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	√/touch button	√/touch buttor	
Live Test		√	$\checkmark$	√		√	√	
NCV		√	$\sqrt{}$	√	$\sqrt{}$	$\sqrt{}$	√	
Diode test			$\sqrt{}$	√	<b>√</b>	$\sqrt{}$	√	
Continuity	√	√	√	√	√	$\sqrt{}$	√	
MAXMINhold		MAX	MAX	MAX	MAX	MAX	MAX	
Data Hold			√	√	$\sqrt{}$	$\sqrt{}$	√	
True RMS		√	$\sqrt{}$	√	√	√	√	
Battery test( 1.5 V/9 V )	√	√	√		√	√	√	
Low battery indication		,	√	√	√	√	√ √	
AUTO power off	√	√	√	√	√	√	√	
Double color backlight			√	$\sqrt{}$	√	√	√	
Flashlight			$\sqrt{}$	√	$\checkmark$	√	√	
Power	2*1.5VAA	2*1.5VAA	1*1.5VAA	2*1.5VAA	2*1.5VAA	2*1.5VAA	2*1.5VAA	



# **JMS-11**

#### **Air Condition Tester**

- 1.Formaldehyde test based on the principle of semiconductor gas sensor.
- 2.LED light of sound light alarm system, red, yellow and green represent bad, normal and excellent respectively, and buzzer alarms when air quality is bad.
- 3.Low battery reminder.



# JMS-12

#### **Air Quality Tester**

- 1. It can test the temperature and humidity of formaldehyde TVOC
- 2. Sound & Light alert: Display realtime air condition from bad to good, sound alert auto-on when in bad air condition.
- 3. High definition display with clear handwriting.
- 4. Low power reminder function.



# NF-518

#### Multifunctional **Wall Detector**

- 1.Wall Detecting Function: Metal Detection/ Wooden Detection/AC Power Detection.
- 2. Depth measurement: Wood: 3.8cm/Live (AC) wire: 5cm/Non-magnetic metal: 10cm/Magnetic metal: 12cm.
- 3. Equipped with automatic shutdown function.
- 4. Equipped with a 2.4-inch high-definition color screen, the test results are clearly displayed



# NF-514

#### **Building Electronic Thermometer**

- 1.Cement concrete
- professional thermometer 2.High Definition LCD
- 3.LED lighting function
- 4.It is suitable for all kinds of construction site temperature measurement



# NF-518S

## Wall Detector + Laser Rangefinder

- 1. 2-In-1 Laser rangefinder &
- Wall Scanner Detector.

  2. Laser rangefinder, 60M/Distance/ Area/Volume/Pythagorean measurement.
- 3. Wall scanner detector, used for wooden batten, metal detect and AC detect.
- 4. Large Capacity Lithium battery without worrying about replacing the battery.



# NF-522

#### Thermal Imager

- 1.Multimode object detection: wood studs,metal objects,or live wiring.
- 2.Informative graphic display when find the material.
- 3.Quickly locate the metal wood AC
- 4. Automatic calibration.

# CABLE CONTINUITY TESTERS



#### NF-8601S

# **TDR Cable Length**

- .Measures cable length and display the distance to fault, graphical wire mapping.
- 2.Identify PoE presence and detect
- 3.Test network performance.data packet, min & max time.
- 4. Tone trace cable with complete AC Interference Rejection.
- 5.Port flash directly locate target cable connected to switch/hub/router
- 6.To import and export data from comupter (160 sets, txt format).



#### NF-8601/8601W

#### **Cable Length Tester**

- 1.Measure length of network telephone and coaxil cable.
- 2.Identify which pins are providing power and detect how much voltage 3. To test network performance, data
- packet, min & max time. 4. Tone trace cable with complete AC Interference Rejection.
- 5.Port flash directly locate target cable connected to switch/hub/router 6.To import and export data from
- comupter (160 sets, txt format).
- 7.8 remote identifiers help to test 8 cables at one time (Only for NF-



## **NF-868**

#### LCD Cable Length **Tester**

- 1.Test open, short, cross connection, reverse, pairing connection and broken wire positioning. 2.Capable to measure length of
- RJ45/RJ11/BNC/USB cable at length of 1500m. 3.Cable tracing on exchanger or Router with power-on.
- 4. To quickly find the target wire or cable among kinds of wires.



#### NF-8108A/8108M

#### **Network Cable Tester**

- 1.Measures cable length and determine the distance of open circuit and short
- 2.Permits you to check wiring error in 5E/6E twisted cord network and telephone line.
- 3.8 remote identifiers help to test 8 cables at one time (Only for NF-





NF-308/388

#### **Wire Fault Locator**

- 1.Trace RJ45 RJ11 BNC USB and other cables 2.Port flash directly locate target
- cable connected to switch. 3.Check wiring error in RJ45/BNC cable, such as open, short, cross 4.Measure RJ45 and BNC cable
- length and broken point. 5. Testing polarity and voltage.
- 6.8 remote identifiers help to test 8 cables at one time (Only for NF-



#### NF-300

#### **Network Coaxil Cable** Tester

- 1.Trace RJ45 BNC USB and other cables without AC current noise.
- 2.Port flash directly locate target
- 3.Check wiring error in RJ45/BNC cable, such as open, short, cross.
- 4 Measure RJ45 and BNC cable length and broken point.



# NF-468



# NF-468/468B **Cable Tester**

- 1.Test RJ45 and RJ11 cable (NF-
- 2.Test RJ45 & RJ11 and BNC Cable (NF-468B)
- 3.Test corresponding double -twisted cable 1, 2, 3, 4, 5, 6, 7, 8, and G.
- 4. Checks for cable continutiy, open circuit, short circuit and crossed wire pairs.



## **NF-468V**

#### **Cable Tester**

- 1. Visible LED status display. 2. Check physical status of RJ45 & RJ11 cable
- 3. Automatically runs all tests and checks for continutiy, open,
- shorted and crossed wire pairs.
- 4. Slow and fast test switch.
- 5. Power supply: 9V battary or power adaptor.



# NF-8200

#### **Network Telephone Cable Tester**

- 1.Trace and locate RJ45 (STP / 4core), RJ11 cables.
- 2.Anti-jamming, capable of working on the exchanger and PC startup. 3.Measure cable length for RJ45,RJ11
- 4.Check open, short, cross, crosstalk for RJ11, RJ45 cable
- 5.Locate short and breakage point accurately.
- 6.Earphone permits use in noisy



# NF-858C

#### Wire Traker

- 1.Trace and Measure lan cable and coaxil cable length
- 2.CAT5 CAT6 and Coaxial cable continuity test.
- 3.Port flash directly locate target cable connected to switch.
- 4.Build in a VFL to check the fiber
- 5.Detect the voltage on POE switch. 6.Built-in rechargeable Lithium battery save energy.



#### **NF-3468**

#### 4-in-1 Network Cable **Tester**

- 1.Tests 4 types of cables: RJ45/RJ11/2.0 USB/BNC.
- 2.LEDs indicate connections and
- 3. Simple one-button test.
- 4.Detachable module for testing remote points.
- 5.Test distance: 1500Ft.





#### NF-468PF/NF-468S

#### **Cable PoE Tester**

- 1. Check continuity of RJ11& RJ45 Cable & Crystal head (NF-468S).
- 2. Detect Ethernet network for Power over Ethernet existence
- 3. Identify that the standard of the PoE switch is 802.3at or 802.3af (NF-468S)



# UNDEBGROUND WIBE LOCATOB



#### **NF-488**

#### **PoE Checker**

- 1.Test the information of the standard PoE device.
- 2.Identify the supply voltage, power supply polarity and mode of PoE
- 3.Check physical status of RJ45
- 4. Test the current, voltage and power consumed by DC appliances.
- 5. The loop-back test function of the



#### NF-8209

#### Wire Tracker

- 1.Three scan modes selectable: Digital/Analog/PoF mode.
- 2.Measure cat5, cat6 cable length, the range is 200m. 3.Port flash function directly find
- target cables connected with
- 4.Test physical status for STP, UTP
- 5. Detect AC voltage & PoE.



# NF-816/NF-816L

#### **Underground Wire** Locator

- 1.Helpful-locating & tracking buried and hidden wires
- 2. Easily locate pet fence wires, metals pipes, electrical wires, etc.
- 3. Wire tracer range-up to 2 feet deep and 1000 feet in length.
- 4.Power:9V Alkaline battery (NF-5.Power:Rechargeable Lithium battery



NF-168S

NF-168V

# NF-168S/168V

#### Wire Tracker

- 1. Check wiremap of Lan cable.
- 2.Tracing RJ45/RJ11/BNC cable connected to the switch or router (NF-168N).
- 3. Tracing RJ45/RJ11 cable connected to the switch or router (NF-168N).
- 4. Visual fault locator: 5mW (NF-



NF-801B



# NF-801B/NF-806R

#### Wire Tracker

- 1. Tracking RJ11, RJ45, cables or other metal wire.
- Check wiremap of Lan cables. 3. Track the cables, and diagnose the breakage.
- 4. Visible indication: pin-to-pin cable map for individual cable (not by
- 5. Low Voltage alarm function

(NF-801B and NF-806R is just difference of colour and the alligator



#### NF-802

#### **Wire Tracker**

- 1.Check cable condition, good or fault. Such as open,cross,short etc
- 2.Trace and locate RJ45 and RJ11
- 3.Port flash function directly find
- target cables connected with switch Telephone Line Test: judging TIP or PING line and judging whether the telephone line is idle, ringing or off-hook.
- 5.QC for crimping crystal head. 6.Detect AC voltage presence (40V-
- 7 Low battery prompt function 8.TYPE-C USB power supply charging for Emitter and Receiver



# NF-820

#### **High & Low Voltage** Wire Tracker

- 1.Track with complete AC Interference
- 2.Tone trace live cable (□220V with socket avoiding burnout).
- 3 Detect invisible cable, the range
- 4. Signal sensitivity for transmitter and receiver is adjustable



# NF-822

#### Flexible Probe Wire Tracker

- 1.Detect cable location in underground or other invisible cable.
- 2.Detection range is 0~0.3 m deep and cable length 1000m for SCAN.
- 3. Signal sensitivity for transmitter
- 4. Polarity judgment and Low battery



# NF-811

#### Wire Tracker

- 1.Tracking RJ11, RJ45, cables or other metal wire
- 2. Check wiremap of Lan cable
- 3.Telephone Line Test : Judging TIP



# NF-813C

#### **Wire Tracke**

- 1.Quickly finding the required line pairs among numerous ones.
- 2.Trace cable with continuous and clear tone, AC Current rejection.
- 3.Teste physical connection status of network cable
- 4. Telephone Line Test: Judging TIP or PING line.
- 5.Port flash function directly find target cables connected with



# NF-826

#### **Underground Wire** Locator

- 1. Finds for open or shorts cable in the wall or earth.
- 2. Tracks for cable in the wall or earth.
- 3. Finds for fuse and safeguard.
- 4. Finds for socket or junction box is envelop
- 5. Finds for open or shorts conduit under the floor.



# NF-5120/5130/5140

#### **Pipe Blockage Detector**

- 1.Locate hidden blockage, clogging inside the pipe.
- 2.Waterproof probe, IP54 and sensitivity adjustment
- 3. Rechargeable lithium battery.
- 4. Optional from 20/30/40M.

# LASER DISTANCE METER



# NF-900C

#### **Optical Power Meter**

- 1.Measurement of the power of optical sender(dbm and w).
- 2. Insertion loss test of optical devices.
- 3.Wavelength:850/1300/1310/1490



#### NF-907C

#### 2-in-1 Power Meter + VFL

- 1.Measurement of the power of optical sender(dbm and w).
- 2.Insertion loss test of optical devices. 3. Check fiber breakage, winding, etc.
- 4.Wavelength:850/1300/1310/1490 /1550/1625nm(power meter).
- 5.Wavelength:650Nm (visual fault



# NF-2030/2050

#### **Laser Distance Meter**

- 1.Length, area and volume modes
- 2.Switch the reference position according to requirement.
- 3.Max range: 30/50m for option.
- 4.Battery type: 1.5V 2\*AAA.



2000

2.000 ...

NF-271

# NF-271 **Laser Distance Meter**

- 1.Length,area, volume and Pythagorean
- 2. Switch the reference position according to requirement.
- 3. Store up to 50 sets of data and retrieve
- 4.Max range: 50/70m for option
- 5.Battery type: 1.5V 2\*AAA.



# NF-909C

#### 2-in-1 Power Meter+ **Light Source**

- 1.Measurement of the power of optical sender(dbm and w).
- Insertion loss test of optical devices.
- 3.Light source function 4.wavelength: 850/1300/1310/1490/1550/
- 5.wavelength:1310/1550nm(light source).



# NF-911C

#### 3-in-1 Optical Multimeter

- 1.Light source supports 1310 and 1550 nm.
- 2.Power meter supports 850, 1300, 1310, 1490, 1550 and 1625 nm.
- 3. Visual fault locator: 20mW









# NF-272L

#### **Laser Distance Meter**

- 1.Length,area, volume and Pythagorean
- 2.Broadcast voice and electronic angle.
- 3. Switch the reference position according to requirement
- 4. Store up to 99 sets of data and retrieve historical data.
- 5.Max range: 50/70/100m for option.
- 6.Battery type: rechargeable Lithium









+ ## 11


U CLEAR □



(\*)

4






NF-273L

**Laser Distance Meter** 

.Length,area, volume and Pythagorean



6.Max range: 60/80/120m for option. 7.Battery type: rechargeable Lithium battery.



# NF-908

**MINI Optical Power Meter** 

- 1. Powerful red light;
- 4. Network test, applicable to







**(** 











# NF-274L

# **Laser Distance Meter**

- 1. Green Beam for outdoors measure 2. Length, area, volume and Pythagorean
- 3. Broadcast voice and electronic angle.
- 4. Bluetooth for transferring measurements into desired software
- 5. Switch the reference position according to requirement.
- 6. Store up to 100 sets of data and retrieve
- 7. Max range: 60/80/120m for option. 8. Battery type: rechargeable Lithium





## 1.Green Beam for outdoors measure

- 2.Length,area, volume and Pythagorean
- 3. Broadcast voice and electronic angle 4. Switch the reference position according
- to requirement 5.Store up to 99 sets of data and retrieve
- 7.Battery type: rechargeable Lithium








# **Visual Fault Locator**

- 1.Detect and locate fiber breaks, poor connections, bending or
- 2.The 2.5mm universal connector of the detector is compatibly designed for ST, SC, FC.
- 3. Optional from 5/10/20/30mW.






















# LASEB DISTANCE METEB





# NF-2240

## Laser Tape Measurer

- 1.Tape & Laser measurement.
- 2.Length, area and volume modes.
- 3.Max range:40m.
- 4.Battery type:1.5V 2\*AAA.





# NF-2260L

#### Laser Tape Measurer

- 1.Tape & Laser measurement.
- 2.Length, area and volume modes.
- 3.Max range: 60m.
- 4.Battery type: rechargeable Lithium battery.









NF-112G

NF-15T

Function comparision ( Laser level )							
Model	NF-112G	NF-15T					
Laser Beam	Green	Green					
Specifications	4V4H4D( 3D12 lines)	4V1H1D(5 lines)					
Laser Diode Wave Length	635nm	635nm					
Working Range	25m	30~50m					
Automatic Leveling Range	±3°	±3°					
Power Supply	Lithium battary	Lithium battary					
Accurcy	±2mm/5m	±1mm/3m					
Operating Temp	-10 °C~45°C	-10 °C~50°C					
Laser Level Weight	1.85kg	1.4kg					

# LASEB DISTANCE METEB



Function comparision (Laser distance meter)									
Model	NF-2030	NF-2050	NF-271	NF-272L	NF-273L	NF-274L	NF-275L	NF-2240	NF-2260L
Laser Beam	Red	Red	Red	Red	Red	Green	Green	Red	Red
Test Range	30m	50m	50/70m	60/80/100m	60/80/120m	60/80/100m	60/100m	40m	60m
Accuracy	±1.5mm								
Screen	1.2 inch High-definition screen 2.0 inch High-definition screen FSTN with blacklight 1.2 inch High-definition scr							-definition screen	
Battary Type	2*AAA 3*AAA			8	850mAh Li-battary 750mAhLi-battary 2*AAA 500m/				
Single & Continious Measurement									
Min & Max Measurement	√								
Area & Volume Measurement	√								
Laser-off&power-offAutomatically	√								
Unit Switch	0	0	√	√	√	√	√	√	√
Benchmark Switch	0	0	√	√	√	√	√	√	√
Hint Tone	0	0	√	√	√	√	√	√	√
Voice Broadcast	0	0	0	√	√	√	√	0	√
Addition And Subtraction	0	0	√	√	√	√	√	0	0
Automatic Level	0	0	√	√	√	√	√	0	0
Vertical Horizontal	0	0	0	√	√	√	√	0	0
Angle ±90°	0	0	0	√	√	√	√	0	0
Electronic Bubble	0	0	0	0	√	√	0	0	0
Bluetooth 4.x	0	0	0	0	√	√	0	0	0
Triangle Area	0	0	0	0	√	√	0	0	0
Trapezoidal Area	0	0	0	0	√	√	0	0	0
Point-point Measurement	0	0	0	0	√	√	0	0	0
Countdown Measurement	0	0	0	0	√	√	0	0	0
Data Storage	0	0	50 sets	99 sets	100 sets	100 sets	99 sets	0	0

# NETWORK TOOL KITS



#### NF-706

#### **CCTV Tester**

- 1.CVBS & Analog signal testing. 2.PTZ control and audio testing.
- 3. Color bar and Video generate display.
- 4. Supply power for Cameras.
- 5.Multimeter function included.
- 6. Measure cable length and wiremap.
- 7. Trace Lan coax cables quickly.





#### NF-715

# **CCTV Tester**

- 1.H.265 decoding, 4K camera test with mainstream;
- 2.Screen+ IP discovery; 3.For Non-ONVIF camera;
- 4.HDMI Input & Output;
- 5.Cable test & Tracy;
- POE & Power Info: CVBS Loop test.



# NF-511

# **Metal Scanner**

- 1.Detect small hidden metal objects.
- 2.Choose between sound or vibration
- 3.Detection sensitivity: 2.5mm steel
- 4.Battery Required: rechargeable Lithium battery.



# NF-609C

#### Voltage detector

- 1.Detect AC range is 50~1000V.
- 2. Test live wire and with flash indicate. 3. Sensitivity adjustable and Signal strength indicate.
- 4.Low battery warning.





#### NF-716

#### **CCTV Tester**

1.H.265 decoding, 4K camera test with mainstream; 2.Screen+ IP discovery; 3.For Non-ONVIF camera; 4.HDMI Input & Output; 5.Cable test & Tracy; POE & Power Info: CVBS Loop test.



# NF-521

## Thermal Imager

- 1. High-precision infrared camera capable of real-time image transmission.
- 2.Center temperature measurement and high temperature tracking.
- 3. Wide Application Range, such as schools, factories, office buildings.

# **Network tool kits**

NF-1206

NF-1304

NF-1501









# NF-188/198

#### **GPS Land Meter**

- 1.Measure area and length of any shape. 2. Vehicle-carrier & Equal-width area
- 3. Display measuring value, figure track
- 4. Applicable google map shows real graphics trajectory(Only for NF-198).



# NF-912

#### **PON Optical Power meter**

- 1. Data storage
- 2. SC/FC port
  3. Auto OFF function

# YOUR MEASUREING INSTRUMENT EXPERT



