


☐

I'm not robot


reCAPTCHA

Continue

Delonghi pinguino portable air conditioner error codes

Error codes de Delonghi AC Self-test: Error code what should I do low temperature LE (frost prevention). The equipment is equipped with a frost protection device to prevent excessive ice formation. When the defrosting process is complete, the equipment starts automatically again. High-level HL (full internal tray). the Empty internal safety tray following the instructions in the End-of-Season Operation section. If you are in cooling mode, contact your local authorized service. In warm-up mode: The empty inner tray. CF Replace the filter. When this message is displayed, the water filter needs to be replaced as described in the section: Replacing the limestone filter. PF probe failure (damaged sensor). If displayed, contact your local authorized service center. F1 1 failed. This message may appear if the water filter is specially filled. See section: Replace the nipple filter. If the filter has been changed recently, contact your local authorized service center. Low temperature - the ambient temperature is very low. H1 High Temperature - The ambient temperature is very high. Probe Failure E1 (damaged sensor). The device has a self-diagnostic system to identify multiple defects. Error messages are displayed on the instrument display. Problem of troubleshooting: The air conditioner does not come in reason: 1. There is no current 2. It is not connected to the main 3. Internal protection device is triggered Solution: 1. wait 2. Turn on main 3. Call the service center Problem: The air conditioner only works for a short time: 1. The air exhaust pipe has 2 snares or snares. Preventing any air from being discharged Solution: 1. Keep the air duct properly, keep it as low and free as possible to avoid hiccups. 2. Check and remove any obstruction that obstructs air discharge Problem: A/C works, but does not cool the room motif: 1. Open windows, doors and/or curtains 2. There are heat sources in the room (oven, hair dryer, etc.). 3. The air exhaust duct is separated from the equipment 4. Clogged dust filter solution: 1. Doors, windows and curtains above, keeping in mind the right usage tips above. 2. Elimination of heat sources 3. Place the air exhaust hose in the box behind the equipment 4. Clean or replace the filter as described above Problem: During operation, there is an unpleasant smell in the room Reason: Dust filter and (when present) clogged electrostatic filter Solution: Clean the filter as described above Problem: The air conditioner does not work for about three minutes after starting again Cause: The internal compressor safety device prevents the appliance from returning to until it is turned off for the last time. This delay is part of normal work. Problem: The symbol and one of the following messages appears on the device LT/HL/CF/PF/FI: Reason: The device has a self-diagnostic self-diagnosis to identify multiple defects. Solution: See the SELF-DIAGNOSIS chapter. CF is displayed when the limestone filter needs to be replaced. The effectiveness of the filter depends on the hardness of the water. However, it should be replaced every five years. If the remote control unit is replaced or abandoned, the batteries must be removed and disposed of in accordance with current law as they are harmful to the environment. Do not mix old and new batteries. Do not mix alkaline, standard (carbon-zinc) or rechargeable (nickel-cadmium) batteries. Do not dispose of the battery on fire. Batteries may explode or leak. Delonghi A/C Manual PDF Delonghi 4 AC Manual PDF LG Tower AC Error Codes Carrier Air Conditioner Error Codes Delonghi AC Error Codes Self test: Error code what should I do le low temperature (frost prevention). The equipment is equipped with a frost protection device to prevent excessive ice formation. When the defrosting process is complete, the equipment starts automatically again. High-level HL (full internal tray). the Empty internal safety tray following the instructions in the End-of-Season Operation section. If you are in cooling mode, contact your local authorized service. In warm-up mode: The empty inner tray. CF Replace the filter. When this message is displayed, the water filter needs to be replaced as described in the section: Replacing the limestone filter. PF probe failure (damaged sensor). If displayed, contact your local authorized service center. F1 1 failed. This message may appear if the water filter is specially filled. See section: Replace the nipple filter. If the filter has been changed recently, contact your local authorized service center. Low temperature - the ambient temperature is very low. H1 High Temperature - The ambient temperature is very high. Probe Failure E1 (damaged sensor). The device has a self-diagnostic system to identify multiple defects. Error messages are displayed on the instrument display. Problem of troubleshooting: The air conditioner does not come in reason: 1. There is no current 2. It is not connected to the main 3. Internal protection device is triggered Solution: 1. wait 2. Turn on main 3. Call the service center Problem: The air conditioner only works for a short time: 1. The air exhaust pipe has 2 snares or snares. Preventing any air from being discharged Solution: 1. Keep the air duct properly, keep it as low and free as possible to avoid hiccups. 2. Check and remove any obstruction that obstructs air discharge Problem: A/C works, but does not cool the room motif: 1. Open windows, doors and/or curtains 2. There are heat sources in the room (oven, hair, etc.) 3. The air exhaust duct is separated from the equipment 4. Clogged dust filter solution: 1. Doors, windows and curtains above, keeping in mind the right usage tips above. Above. Eliminating heat sources 3. Place the air exhaust hose in the box behind the equipment 4. Clean or replace the filter as described above Problem: During operation, there is an unpleasant smell in the room Reason: Dust filter and (when present) clogged electrostatic filter Solution: Clean the filter as described above Problem: The air conditioner does not work for about three minutes after starting again Cause: The internal compressor safety device prevents the appliance from working again until it is turned off for the last time. This delay is part of normal work. Problem: The symbol and one of the following messages appears on the device display LT/HL/ CF/ PF/ FI: Reason: The device has a self-diagnostic system to identify multiple defects. Solution: See the SELF-DIAGNOSIS chapter. CF is displayed when the limestone filter needs to be replaced. The effectiveness of the filter depends on the hardness of the water. However, it should be replaced every five years. If the remote control unit is replaced or abandoned, the batteries must be removed and disposed of in accordance with current law as they are harmful to the environment. Do not mix old and new batteries. Do not mix alkaline, standard (carbon-zinc) or rechargeable (nickel-cadmium) batteries. Do not dispose of the battery on fire. Batteries may explode or leak. You can also read the operator's air conditioning error code | eSO-split air conditioner error codes (OL 1 Time)EEPROM indoor unit parameter error. E1-(OL 2 Time)Communication error of internal/external units. E3-(OL 4 Time)The internal fan speed was ... Read More Mana Ke hm yaar Nahi Delonghi Portable air conditioner fault codes Error codes error codes what should I do low temperature LE (frost prevention). The equipment is equipped with a frost protection device to prevent excessive ice formation. When the defrosting process is complete, the equipment starts automatically when the defrosting process is complete. High-level HL (full internal tray). Empty the internal safety tray by following the instructions in the End-of-Season Operation section. If it occurs again in cooling mode, contact authorized local customer services. In heating mode: Empty the internal tray. CF Replace the filter. When this message is displayed, the water filter needs to be replaced as described in the section: Replacing the limestone filter. PF probe failure (damaged sensor). If displayed, contact your local authorized service center. F1 1 failed. This message may appear if the water filter is particularly full. See section: Replacing limestone filters. If the filter has been changed recently, contact your local authorized service center. Low temperature - the ambient temperature is very low. H1 High Temperature - The ambient temperature is very high. Probe Failure E1 (damaged sensor). The device has a self-diagnostic system to identify multiple defects. Error messages are displayed on the instrument display. Delonghi Portable Air Conditioner Error code of portable delongi delongi air conditioner – Le HL CF PF F1 Troubleshooting problem: Air conditioner does not come in reason: No current Is not connected to the main internal protection device is tripped Solution: Wait for Main Call Service Center Main Problem: Air Conditioning only works for a short reason: The air exhaust pipe has bumps or bends preventing any air from being discharged Solution: Keep the air duct properly, keep it as low and free as possible to avoid bottlenecks. Check and remove any obstruction obstructing the air discharge Problem: The air conditioner works, but does not cool the room motif: Open windows, doors and/or curtains There are heat sources in the room (oven, hair dryer, etc.). The air exhaust pipe is separated from the Clogged Dust Filter Solution: windows and curtains above, in view of the correct usage suggestions above. eliminate heat sources Place the air exhaust hose in the housing behind the equipment Clean or replace the filter as described above Problem: During operation, there are Unpleasant smell in the room Reason: Dust filter and (when present) clogged electrostatic filter Solution: Clean the filter as described above Problem: The air conditioner does not work for about three minutes after starting again Cause: The internal compressor safety device prevents the appliance from working again until it is turned off for the last time. Solution: Wait. This delay is part of the normal operation. Problem: The symbol and one of the following messages appears on the device display LT/HL/ CF/ PF/ FI: Reason: The device has a self-diagnostic system to identify multiple defects. Solution: See the SELF-DIAGNOSIS chapter. Delonghi Portable Air Conditioner Fault Codes Delonghi Portable Air Conditioner Failure Codes Portable Error Code of CF Air Conditioner is displayed when the limestone filter needs to be replaced. The effectiveness of the filter depends on the hardness of the water. However, it should be replaced every five years. Delonghi Delonghi Portable Air Conditioner Fault Codes Portable Air Conditioner Failure Codes If the remote control unit is replaced or abandoned, batteries should be removed and disposed of in accordance with current law as they are harmful to the environment. Do not mix old and new batteries. Do not mix alkaline, standard (carbon-zinc) or rechargeable (nickel-cadmium) batteries. Do not dispose of the battery on fire. Batteries may explode or leak. Netflix DNS Codes updated 2020 2020