

# FRAGMENT

S A F E T Y



**YOU WORK**  
**WE CARE**

GENERAL  
CATALOGUE



## SUMMARY

- 3 SAFETY SHOES  
100% NITRILE
- 4 SAFETY SHOES  
PU/NITRILE
- 5 SAFETY SHOES  
PU/PU POLYETHER
- 7 BOOTS
- 10 RAIN PROTECTIVE &  
HIGH VISIBILITY CLOTHES
- 11 100% COTTON GARMENTS
- 12 DISPOSABLE MASKS
- 13 DISPOSABLE COVERALLS
- 14 SAFETY SHOES STANDARDS
- 15 DISPOSABLE MASKS &  
COVERALLS STANDARDS
- CONTACT



« Our knowledge of the field and our proximity with our customers are our main assets to meet all your Personal Protective Equipment needs.

Safety is priceless, but it has a cost. Therefore, we are committed to design robust PPE with increased lifespan and the best value for money.

Our mission is to provide the highest level of protection to every PPE user without compromising on comfort of use »

## OUR BUSINESS SECTORS



INDUSTRY  
& MANUFACTURE



OIL  
& GAS



MINING  
INDUSTRY



CONSTRUCTION  
BUILDING



SECOND WORK  
& ARTISANS



AGRICULTURE  
& GARDEN



MEDICAL  
& HYGIENE



LOGISTIC  
& SERVICES

## PRODUCTS' ADVANTAGES



ROBUSTNESS



STANDARDS



PRICE



COMFORT



DESIGN



With more than 10 years of experience in the PPE Business, our team of experts constantly adapt to the constraints and needs of every environment



Our PPE experts and multilingual team is committed to answer your request in English, French & Spanish



Proximity and relationship are very important to us. You can reach us 24/7 for any question

**YOU WORK**  
**WE CARE**



# SAFETY SHOES

## 100% NITRILE

HYDROLYSIS RESISTANCE

COST

COMFORT

WEIGHT

### NITRILE BENEFITS :

Nitrile is a derivative of rubber, known to be an extremely robust material

Our 100% Nitrile sole is particularly versatile due to its resistance to a multitude of risks : heat resistance, cut, abrasion, hydrocarbons and other chemicals

Regardless of the work environment, our 100% Nitrile soles provide optimal protection and excellent durability

Nitrile is a material that is not affected by the hydrolysis effect\*

\*Hydrolysis : chemical reaction caused by heat and humidity which causes premature degradation of the sole

100% HYDROLYSIS RESISTANT



HRO



ROBUSTNESS & DURABILITY



### SALONGA S3 HRO SRC (100% NITRILE)



 Sizes : 36-48

 720g



- ◆ Upper : Water resistant full-grain leather + high resistant nylon + leather front bumper
- ◆ Lining : Breathable mesh
- ◆ Toe cap : Steel
- ◆ Puncture resistant sole : Steel
- ◆ Insole : Premolded EVA
- ◆ Outsole : Welded 100% Nitrile - Sole resistant to tropical weather & hydrolysis
- ◆ HRO : Heat resistant outsole (300°C - 60 seconds)
- ◆ Extra : PU free, antistatic, energy absorbing heel, reinforced laces + 1 quick release, oil resistant sole, side reflective stripes



Certification : EN ISO 20345:2011 S3 HRO SRC



### KATAVI S3 HRO SRC (100% NITRILE)



 Sizes : 36-48

 670g



- ◆ Upper : Water resistant full-grain leather + high resistant nylon
- ◆ Lining : Breathable mesh
- ◆ Toe cap : Steel
- ◆ Puncture resistant sole : Steel
- ◆ Insole : Premolded EVA
- ◆ Outsole : Welded 100% Nitrile - Sole resistant to tropical weather and hydrolysis
- ◆ HRO : Heat resistant outsole (300°C - 60 seconds)
- ◆ Extra : PU free, antistatic, energy absorbing heel, oil resistant sole



Certification : EN ISO 20345:2011 S3 HRO SRC

**FRAGMENT**  
SAFETY



# SAFETY SHOES PU/NITRILE

HYDROLYSIS RESISTANCE

COST

COMFORT

WEIGHT

## PU/NITRILE BENEFITS :

Our PU/Nitrile sole is made up of two parts : the midsole with polyether PU and the contact sole with nitrile

This combination results in obtaining the best performance of each material :

- The flexibility and lightness of PU for better comfort
- The robustness of Nitrile for increased durability and heat resistance (HRO)

The combination of the two materials also results in obtaining a sole that is highly resistant to the hydrolysis effect\*

\*Hydrolysis : chemical reaction caused by heat and humidity which causes premature degradation of the sole



## MASAI S3 HRO SRC (PU/NITRILE)



 Sizes : 36-48

 730g



- Upper : Water resistant full-grain leather
- Lining : Breathable mesh
- Toe cap : Steel
- Puncture resistant sole : Steel
- Insole : Premolded EVA – Extra confort
- Outsole : Injected - PU/Nitrile - Resistant to tropical weather and hydrolysis
- HRO : Heat resistant outsole (300°C- 60 seconds)
- Extra : Antistatic, energy absorbing heel, oil resistant sole

 Certification : EN ISO 20345:2011 S3 HRO SRC



## MASAI LOW S3 HRO SRC (PU/NITRILE)



 Sizes : 36-48

 665g



- Upper : Water resistant full-grain leather
- Lining : Breathable mesh
- Toe cap : Steel
- Puncture resistant sole : Steel
- Insole : Premolded EVA – Extra confort
- Outsole : Injected - PU/Nitrile - Resistant to tropical weather and hydrolysis
- HRO : Heat resistant outsole (300°C- 60 seconds)
- Extra : Antistatic, energy absorbing heel, oil resistant sole

 Certification : EN ISO 20345:2011 S3 HRO SRC

**FRAGMENT**  
SAFETY




Criteria	Material A	Material B	Material C	Material D	Material E	Material F	Material G	Material H
Hydrolysis Resistance	High	High	High	High	High	Medium	Medium	Low
Cost	Low	Low	Medium	Medium	Medium	High	High	High
Comfort	High	High	High	High	High	High	Medium	Low
Weight	High	High	High	High	Medium	Medium	Low	Low

**KRUGER S3 SRC (PU/PU)**

 Sizes : 36-48

 645g

- Upper : Water resistant full-grain leather
  - Lining : Breathable mesh
  - Toe cap : Steel
  - Puncture resistant sole : Steel
  - Insole : Premolded EVA – Extra comfort
  - Outsole : Injected – dual density polyether PU/PU
  - Extra : Antistatic, energy absorbing heel, oil resistant outsole
-  **Certification : EN ISO 20345:2011 S3 SRC**

**KRUGER LOW S3 SRC (PU/PU)**

 Sizes : 36-48

 605g

- ♥ Upper : Water resistant full-grain leather
  - ♥ Lining : Breathable mesh
  - ♥ Toe cap : Steel
  - ♥ Puncture resistant sole : Steel
  - ♥ Insole : Premolded EVA – Extra comfort
  - ♥ Outsole : Injected – dual density polyether PU/PU
  - ♥ Extra : Antistatic, energy absorbing heel, oil resistant outsole
- ♥ **Certification : EN ISO 20345:2011 S3 SRC**







**RADOM (RUBBER)**



📏 Sizes : 36-48

🛒 520g

🎨 Colors



- 🛡️ Design Rangers - Mid Cut Allround Tactical Boot - Outsole 100% Rubber
- 💎 Upper : Leather + High resistant nylon + 19 cm high
- 💎 Lining : Breathable Mesh with extra padding
- 💎 Insole : Removable premolded - EVA
- 💎 Outsole : Welded 100% Rubber (light and robust)
- 💎 Extra : Lateral closing zip for an easy layoff, extra rear tendon protection, breathable upper, extreme lightweight (520 g), Excellent foot support: ankles protection against strains and sprains



**LAGOS S3 HRO SRC (NITRILE)**



📏 Sizes : 36-48

🛒 755g

🎨 Colors



- 🛡️ Design Rangers - Mid Cut Safety Tactical Boot - Outsole 100% Nitrile
- 💎 Upper : Leather + high resistant nylon - 19 cm high
- 💎 Lining : Breathable mesh with extra padding
- 💎 Insole : Removable premolded - EVA
- 💎 Outsole : Welded 100% Nitrile - Hydrolyse resistant
- 💎 Protection parts : Composite non-metallic
- 💎 Extra : lateral closing zip for an easy layoff, extra rear tendon protection, breathable upper
- 🛡️ Certification : EN ISO 20345:2011 S3 HRO SRC



**CAMEIA S3 HRO WR SRC (NITRILE)**



📏 Sizes : 36-48

🛒 795g

🎨 Colors



- 🛡️ Rigger Boot S3 HRO WR SRC - Outsole 100% Nitrile
- 💎 Upper : Water resistant full-grain leather + front bumper - 23 cm high
- 💎 Lining : Waterproof membrane
- 💎 Insole : Removable premolded ultra-thick - EVA
- 💎 Outsole : Welded 100% Nitrile - Hydrolysis resistant
- 💎 Protection parts : Composite non-metallic
- 💎 Extra : 2x side pull strap for easy layoff, rear tendon reinforcement, extra comfort sole

🛡️ Certification : EN ISO 20345:2011 S3 HRO WR SRC





VICTORIA S5 SRA (NITRILE)



📏 Sizes : 36-46

🛒 1100g

🎨 Colors  
● ● ● ●



- ♥ Upper : PVC (38 cm)
- ♥ Toe cap : Steel
- ♥ Puncture resistant sole : Steel
- ♥ Outsole : PVC/Nitrile
- ♥ Extra : 100% waterproof, antistatic, energy absorbing heel, oil resistant outsole, wide studs, reinforced upper for malleollus and metatarsus, front bumper, rear grip for easy take off

🛡 Certification : EN ISO 20345:2011 S5 SRA



KASAI O4 SRA (PVC)



📏 Sizes : 36-48

🛒 850g

🎨 Colors  
● ● ● ●



- ♥ Upper : PVC (38 cm)
- ♥ Outsole : PVC
- ♥ Extra : 100% waterproof, antistatic, energy absorbing heel, oil resistant outsole, wide studs for increased stability and better slip resistance, front bumper, rear grip for easy take off

🛡 Certification : EN ISO 20347 O4 SRA



**FRAGMENT**  
S A F E T Y



**FRAGMENT**  
S A F E T Y

NAMIB S3 SRC





## RAINY



△ Sizes : S to 3XL

✱ Colors



- ✱ Rain set : Jacket + Trousers
- ✱ Fabric : Polyester PVC coated
- ✱ Seams : Waterproof
- ✱ Jacket : Fixed hood with drawstring, drawstring at the bottom of the jacket, indirect ventilation at the back, zipper under front press-stud flap, elasticated sleeves, 2 lower pockets with flap
- ✱ Trousers : Elasticated waist, zipper stud fly, adjustable bottom of legs with press-studs, 2 hand slits



## RAINY HV



△ Sizes : S à 3XL

✱ Colors



- ✱ Rain set : Jacket + Trousers
- ✱ Fabric : Polyester PVC coated
- ✱ Reflective bands : Parallel belt assembly - Silver color - 5,5cm
- ✱ Seams : Waterproof
- ✱ Jacket : Fixed hood with drawstring, drawstring at the bottom of the jacket, indirect ventilation at the back, zipper under front press-stud flap, elasticated sleeves, 2 lower pockets with flap
- ✱ Trousers : Elasticated waist, zipper stud fly, adjustable bottom of legs with press-studs, 2 hand slits



## COATY



△ Sizes : S à 3XL

✱ Colors



- ✱ Rain coat
- ✱ Fabric : Polyester PVC coated
- ✱ Seams : Waterproof
- ✱ Extra : Fixed hood with drawstring, zipper under front press-stud flap, elasticated sleeves, 2 lower pockets with flap



## COATY HV



△ Sizes : S à 3XL

✱ Colors



- ✱ Rain coat with reflective bands
- ✱ Fabric : Polyester PVC coated
- ✱ Reflective bands : Shoulder-belt assembly - Silver color - 5,5cm
- ✱ Seams : Waterproof
- ✱ Extra : Fixed hood with drawstring, zipper under front press-stud flap, elasticated sleeves, 2 lower pockets with flap



## VESTY HV



△ Sizes : S à 3XL

✱ Colors



- ✱ High visibility jacket
- ✱ Fabric : 120 g/m2 100% Polyester
- ✱ Reflective bands : Shoulder-belt assembly and harness - Silver color - 5,5cm
- ✱ Extra : 2 velcro bands



## VESTY HV PLUS



△ Sizes : S à 3XL

✱ Colors



- ✱ High visibility Premium jacket
- ✱ Fabric : 120 g/m2 100% Polyester
- ✱ Reflective bands : Shoulder-belt assembly and harness - Silver color - 5,5cm
- ✱ Extra : Heavy duty vertical zipper, 2x large pockets with velcro closure, a badge holder, a phone pocket, a pen pocket and a D-ring for keys or badges



## MINING SHIRT (100% COTTON)



Vented back + Shoulder with Mesh



Vented armpits with Mesh



Lined seams with tie-offs



- Working shirt
- Fabric : 145 g/m2 100% Cotton Twill
- Reflective bands : Parallel belt assembly - Silver color - 5 cm
- Seams : Lined with tie-off on the stress points
- Ventilation : Back, shoulder and armpit ventilation with Mesh
- Extra : 2 chest pockets with button closure, pen holder on the left pocket flap, 1 pocket on the left sleeve, vertical button closure, buttoned sleeve adjustment, collar with protective flap



Sizes : S à 3XL



Colors



## MINING TROUSERS (100% COTTON)



Sizes : S à 3XL



Colors



- Working trousers with reflective bands
- Fabric : 240 g/m2 100% Cotton Twill
- Extra : 2 front pockets, 1 back pocket (right hand side), 1 cargo pockets with flap (left hand side), 1 tool slot pocket (right hand side), zipper fly, belt pass, elasticated waist



## MINING OVERALL (100% COTTON)



Sizes : S à 3XL



Colors



- Working overall with reflective bands
- Fabric : 240 g/m2 100% Cotton Twill
- Reflective bands : Parallel assembly - silver color - 5 cm
- Fastening : Double slider vertical zip
- Extra : 1 chest pocket with button flap, 2 front pockets, 1 back pocket, double slider zipper (top/bottom) under snap flap, elasticated back for waist size adjustment, elasticated sleeves for wrist adjustment





## MASK2 - FFP2 MOLDED (WITHOUT VALVE)



- 20 masks / box
- 8 hours (maximum usage time)
- One size fits all
- Biological protection
- Protection against moderately toxic particles and aerosols



- Box of 20 FFP2 disposable masks
- Mask : Non woven synthetic fiber
- Fastening : 2 elastic bands (around the head)
- Format : Molded shell
- Nose clip : Adjustable with foam edge

Certification : EN ISO 149:2001+A1:2009 Filtering half-masks against particles



## MASK2V - FFP2 MOLDED (WITH VALVE)



- 10 masks / box
- 8 hours (maximum usage time)
- One size fits all
- Biological protection
- Protection against moderately toxic particles and aerosols




- Box of 10 FFP2 disposable masks with valve
- Mask : Non woven synthetic fiber
- Fastening : 2 elastic bands (around the head)
- Format : Molded shell
- Valve : Plastic (high performance exhalation valve)
- Nose clip : Adjustable with foam edge

Certification : EN ISO 149:2001+A1:2009 Filtering half-masks against particles



## MASK2V-2F - FFP2 (FOLDED WITH VALVE)



- 10 masks / box
- 8 hours (maximum usage time)
- One size fits all
- Biological protection
- Protection against moderately toxic particles and aerosols



- Box of 10 FFP2 disposable folded masks with valve
- Mask : Non woven synthetic fiber
- Fastening : 2 elastic bands (around the head)
- Format : Soft with vertical folding
- Valve : Plastic (high performance exhalation valve)
- Nose clip : Adjustable with foam edge

Certification : EN ISO 149:2001+A1:2009 Filtering half-masks against particles



## MASK3V - FFP3 MOLDED (WITH VALVE)



- 10 masks / box
- 8 hours (maximum usage time)
- One size fits all
- Biological protection
- Protection against moderately toxic particles and aerosols



- Box of 10 FFP3 disposable masks with valve
- Mask : Non woven synthetic fiber
- Fastening : 2 elastic bands (around the head)
- Format : Molded shell
- Valve : Plastic (high performance exhalation valve)
- Nose clip : Adjustable with foam edge

Certification : EN ISO 149:2001+A1:2009 Filtering half-masks against particles



## MASK3VP - FFP3 MOLDED (WITH VALVE & STRAPS)



- 5 masks / box
- 8 hours (maximum usage time)
- One size fits all
- Biological protection
- Protection against moderately toxic particles and aerosols



- Box of 5 FFP3 disposable masks with valve and adjustable straps
- Mask : Non woven synthetic fiber
- Fastening : 2 elastic bands
- Straps : Wide adjustable elastic straps
- Format : Molded shell
- Valve : Plastic (high performance exhalation valve)
- Nose clip : Adjustable with integral foam edge

Certification : EN ISO 149:2001+A1:2009 Filtering half-masks against particles



## COVER56 (TYPE 5/6)



**Sizes : S to 3XL**

- Protection against chemical risks
- TYPE 5 : Protection against solid particulates (dust-asbestos)
- TYPE 6 : Protection against liquid chemicals (splashes)
- Antistatic : Protective to dissipate static electricity

EN ISO 13982-1  
TYPE 5

EN ISO 1149-5

EN ISO 13034  
TYPE 6



- Disposable coverall Type 5/6
- Material : Non woven microporous laminate - 55g
- Seams : Serged seams
- Hood : Fix elasticated hood - 2 parts
- Closing : Front zip covered by self adhesive flap
- Extra : Elastics at cuffs, ankles and waist, antistatic



## COVER56B (TYPE 5B/6B)



**Sizes : S to 3XL**

- Protection against chemical risks
- TYPE 5-B : Protection against solid particulates (dust-asbestos)
- TYPE 6-B : Protection against liquid chemicals (splashes)
- Antistatic : Protective to dissipate static electricity
- Biological Protection against infective agents
- Protection against radioactive contamination

EN ISO 13982-1  
TYPE 5-B

EN ISO 1149-5

EN ISO 13034  
TYPE 6-B

EN ISO 14126



EN ISO 1073-2  
CLASS 1

- Disposable coverall Type 5B/6B
- Material : Non woven microporous laminate - 65g
- Seams : Serged seams
- Hood : Fix elasticated hood - 2 parts
- Closing : Front zip covered by self adhesive flap
- Extra : Elastics at cuffs, ankles and waist, antistatic



## COVER3B (TYPE 3B)



**Sizes : S à 3XL**

- Protection against chemical risks
- TYPE 3-B : Protection against liquid chemicals (sprays)
- TYPE 4-B : Protection against liquid chemicals (mists)
- TYPE 5 : Protection against solid particulates (dust - asbestos)
- TYPE 6 : Protection against liquid chemicals (splashes)
- Antistatic : Protective to dissipate static electricity
- Protection against radioactive contamination
- Biological Protection against infective agents

EN ISO 14605  
TYPE 3-B  
TYPE 4-B

EN ISO 1149-5

EN ISO 13982-1  
TYPE 5-B

EN ISO 14126

EN ISO 13034  
TYPE 6-B

EN ISO 1073-2  
CLASS 1



- Disposable coverall Type 3B
- Material : Polypropylene + Laminated film - 82 g
- Seams : Heat sealed taped seams
- Hood : Fix elasticated hood - 3 parts
- Closing : Front zip covered by double self-adhesive flap
- Extra : Elastics at cuffs, ankles and waist, thumb loops, antistatic



# SAFETY SHOES STANDARDS

## SIZE CORRESPONDENCE

EUROPE	35	36	37	38	39	40	41	42	43	44	45	46	47	48
UK	2	3	4	5	6	6,5	7	8	9	10	10,5	11	12	13
US	3	4	5	6	7	7,5	8	9	10	11	11,5	12	13	14
Cm	23,1	23,7	24,4	25,1	25,7	26,4	27,1	27,8	28,4	29,1	29,7	30,3	31	31,6

**FRAGMENT**  
S A F E T Y

## ISO STANDARDS

### EN ISO 20344 : Test methods for safety shoes

Standards summarizing all the tests and test methods performed on safety shoes before they are placed on the market

This Standard is used in conjunction with EN ISO 20345 and EN ISO 20347 which define the basic and additional requirements for safety footwear

### EN ISO 20345 : Specification of safety shoes for professional use

This international standard specifies the basic and additional (optional) requirements for general purpose safety footwear. The safety shoe is equipped with a safety toe resistant to impacts equivalent to 200 joules and crushing of 15 KN

### EN ISO 20347 : Specifications for work footwear for professional use

This footwear is different from safety footwear by the fact that these do not have toe caps against injury from falling objects or crushing impacts

## GENERAL REQUIREMENTS

	STANDARD EN ISO 20345	BASIC PROPERTIES (PROTECTIVE TOE)	CLOSED BACK	ANTI STATIC	OIL RESISTANT OUTSOLE	ENERGY ABSORBING HEEL	WATER REPELANT COATING	PUNCTURE RESISTANT OUTSOLE	STUDDED SOLE
CLASS 1 Leather Shoes and other materials	SB	X							
	S1	X	X	X	X	X			
	S1P	X	X	X	X	X		X	
	S2	X	X	X	X	X	X		
	S3	X	X	X	X	X	X	X	X
CLASS 2 All rubber shoes	S4	X	X	X	X	X	X		
	S5	X	X	X	X	X	X	X	X

	STANDARD EN ISO 20347	BASIC PROPERTIES	CLOSED BACK	ANTI STATIC	OIL RESISTANT OUTSOLE	ENERGY ABSORBING HEEL	WATER REPELANT COATING	PUNCTURE RESISTANT OUTSOLE	STUDDED SOLE
CLASS 1 Leather Shoes and other materials	OB	X							
	O1	X	X	X	X	X			
	O2	X	X	X	X	X	X		
	O3	X	X	X	X	X	X	X	X
CLASS 2 All rubber shoes	O4	X	X	X	X	X	X		
	O5	X	X	X	X	X	X	X	X

## SLIP RESISTANCE

### SYMBOL TYPES OF FLOORS

<b>SRA</b>	Hard industrial indoor floors (tile type)
<b>SRB</b>	Hard industrial indoor or outdoor floors (paint or resin type)
<b>SRC</b>	SRA + SRB = SRC indoor or outdoor floors (polyvalent type)

## RECOMMENDED STORAGE CONDITIONS

We recommend storing the products as follows :

- Do not compress or bend
- Do not store near steam pipes, radiators or other sources of artificial heat or expose directly sunlight, artificial light or other sources of ozone
- Storage ambient temperature must be between 10° C and 21° C. Storage temperature should not exceed 35° C

## ADDITIONAL SPECIFICATIONS

Added to this are additional markings for special specifications :

<b>AN</b>	Protection of the malleolus
<b>C</b>	Conductive because electrical resistance does not exceed 100k
<b>CI</b>	Cold insulation
<b>CR</b>	Upper cut resistant
<b>ESD</b>	Dissipative shoe
<b>HI</b>	Heat insulation
<b>HRO</b>	Heat resistant outsole up to 300°C (for 60 seconds)
<b>M</b>	Metatarsus protection against choc impacts
<b>WR</b>	Water resistant (waterproof)

**FRAGMENT**  
S A F E T Y

## DISPOSABLE MASKS - RESPIRATORY PROTECTION

**FFP1** C€ EN149 **8H00**  
(maximum usage time)

**Nominal Protection Factor\*\* X4**

**Particles without specific toxicity and water-based aerosols**

Ex : cotton, graphite, sodium hydroxide, calcium carbonate, cement, cellulose...

**FFP2** C€ EN149 **8H00**  
(maximum usage time)

**Nominal Protection Factor\*\* X12**

**Solid and / or liquid aerosols indicated as dangerous or irritant**

Ex : softwoods, metals, resin, fiberglass, mineral fiber, charcoal...

**FFP3** C€ EN149 **8H00**  
(maximum usage time)

**Nominal Protection Factor\*\* X50**

**Toxic solid and / or liquid aerosols**  
Ex : hardwoods, ceramic, rock wool, cadmium, chromium, powdered pesticide...

 **EN ISO 149 :**

This standard specifies the minimum characteristics to be required of filtering half-masks used as respiratory protection devices against particles. It defines three classes of filtration efficiency, namely FFP1, FFP2 and FFP3

PRODUCTS	STANDARDS	LEAKING OF THE AMBIANT ATMOSPHERE* (%)	NOMINAL PROTECTION FACTOR**
FFP1	EN149	22	4
FFP2	EN149	8	12
FFP3	EN149	2	50

\* TIL : Leaking of the ambient atmosphere into the respiratory interface measured in laboratory

\*\* FPN : Nominal Protection Factor corresponds to the level of protection tested in the laboratory.  
The level of APF, Assigned Protection Factor, might be different according local regulations

## DISPOSABLE COVERALLS - CHEMICAL PROTECTION

 **TYPE 6 :**  
Against splashes (limited)




 **TYPE 5 :**  
Dry particulate-tight





 **TYPE 4 :**  
Spray tight





 **TYPE 3 :**  
Liquid-jets tight


 • Protective clothing against liquid chemicals (splashes)  
EN ISO 13034

 • Protective clothing for use against solid particules (dust-asbestos)  
EN ISO 13982-1

 • Protective clothing for use against liquid chemicals (sprays-fogs)  
EN ISO 14605

 • Protective clothing to dissipate static electricity  
EN ISO 1149-5

 • Protective clothing against infective agents  
EN ISO 14126

 • Protective clothing against radioactive contamination  
EN ISO 1073-2



# FRAGMENT

## S A F E T Y

### WE WORK ALL OVER AFRICA !

Dakar - Nairobi - Cape Town - Kigali - Lagos - Abidjan - Conakry - Lomé - Marrakech - Casablanca - Bamako - Ouagadougou - Accra  
Libreville - Luanda - Yaoundé - Maputo - Johannesburg - Durban - Harare - Dar Es Salaam - Douala - Port Harcourt - Port Gentil  
Antananarivo - Port Louis - Kinshasa - Cotonou - Pointe Noire - Brazzaville - Kampala - Lubumbashi - Mombasa - Addis Adeba - Djibouti  
Windhoek - Walvis Bay - Gaborone - Pretoria - Beira - Pemba - Toamasina - Mtwara - Mwanza - Arusha - Bujumbura - Lusaka - Bulawayo  
Lilongwe - Lamu - Port-Soudan - Asmara - Khartoum - Le Caire - Tripoli - Tunis - Alger - Nouakchott - Banjul - Bissau - Freetown  
Monrovia - Porto-Novo - Abuja - Malabo - Bangui - N'Djamena - Niamey - Djouba - Victoria - Malé - Kumasi - Ibadan - Kano - Blantyre



Email :  
[contact@fragmentsafety.com](mailto:contact@fragmentsafety.com)



Contact & Whatsapp :  
+33 6 32 80 75 10



Rue de la République  
13002 Marseille - FRANCE

## YOU WORK WE CARE