


VEHICLE TYPE: PICKUP		CLASSIFICATION: L7e-CU		BATTERY PACK: 23.04 kWh		DRIVER: LHD <small>(RHD available)</small>	
MAIN SPECIFICATIONS							
Dimensions (L × W × H) unladen	3700 × 1440 (1735 Mirror) × 1800 mm			Top speed	75 km/h		
Body structure	Load-bearing structure			Gradeability	25% (14°)		
No. of Doors/Seats	2 / 2 (Driver and Passenger)			Minimum turning radius	5500 mm		
Wheelbase	2495 mm			Driving range (WVTA)*	260 km		
Track Width (Front/Rear)	1145 / 1195 mm			Real-world range	200+ km		
Ground Clearance (Curb Weight)	160 mm			Energy consumption*	≈115.9 Wh/km		
Ramp angles (Front/Rear)	48° / 30°			Energy efficiency*	≈8.6 km/kWh		
Gross Vehicle Weight	1450 kg			Battery warranty	4 years or 200,000 km	whichever comes first	
Actual vehicle mass	850 kg			Vehicle warranty	3 years or 50,000 km	whichever comes first	
CHARGING							
Charging speed	AC slow charging			Charger type	EU Type 2		
On-board charger (OBC)	3.3 kW			Charging time (20-80%)****	≈5 hours		
Charging distance in 1 hour (est.)****	≈23 km			Charging time (0-100%)****	≈9 hours		
ELECTRIC MOTOR							
Motor type	PMSM (Air cooled)			Peak power	20 kW (27 hp)		
Drive System	Rear-wheel drive			Max. torque	112 N.m		
Regenerative braking system	As Standard			Transmission	Fixed ratio		
BATTERY							
Battery type (Air-cooled)	LiFePO4			Battery pack weight (±10)	187 kg		
Rated capacity (Ah)	300 Ah			Battery capacity***	23 kWh		
Nominal voltage (V)	76.8 V			Battery pack energy density	≈129 Wh/kg		
CARGO PLATFORM							
Cargo type	Pickup			Bucket height	325 mm		
Bucket material	Alloy <sup>Optional</sup>			Bucket thickness	40 mm		
Payload	500 kg			Headboard height	1030 mm		
Loading area	2.2 m <sup>2</sup>			Bucket overall height	1100 mm		
Bucket Length	1700 mm			Weight of the bucket	70 kg		
Bucket Width	1375 mm						
TIRES & SUSPENSIONS							
Front suspension	McPherson			Brakes Front/Rear	Disc / Drum		
Rear suspension	Leaf Spring			Tire specifications	155R13C (LT)		
Parking Brake	Hand Brake (Foot Brake on RHD)			Wheels	Steel		
SAFETY FEATURES				LIGHTING SYSTEM			
ADAS Anti-lock Braking System ABS	Door Ajar Alarm			Front combination light LED	Daytime running light LED		
Electric Power Steering EPS	Reversing Warning Alarm			Combination Tail light LED	Interior lighting LED		
Driver Seat Belt Alarm	Acoustic Vehicle Alerting Systems						
Rear View Camers	3-Point Safety Belt (retractable)						
ACCESSORIES & OTHERS							
Intermittent windshield wipers	Key FOB / Keyless Entry			OBD connection	Radio, MP3, MP4		
Imitation leather seat cover	Push-Start button			9" LCD Infotainment display	Portable EU Type2 charger (220V)		
4-Way adjustable Seats (manual)	Power windows			Loudspeakers x 2	Foldable warning triangle & safety vest		
Heating	Door storage box			Bluetooth connectivity			
Central door locking system	Sun visor (flip) x 2			USB port x 1			
OPTIONS				PAINT OPTIONS			
Air condition	OBC 7 kW			White (standard) <input type="checkbox"/>	Light Green <input type="checkbox"/>		
Towing Hook				Yellow <input type="checkbox"/>	Light Blue <input type="checkbox"/>		
Wall Charger 7.4 kW				Black <input type="checkbox"/>	Customs Color (On Request)		
Spare tire				Light Grey <input type="checkbox"/>			
CARGO PLATFORM OPTIONS							
Pick-up: Alloy or Steel Tray							
Tipper: Alloy or Steel Tray							
Box (FRP Honeycomb Panel)							
Box Half (FRP Honeycomb Panel)							
Cold Chain (Max. Temp. -18°C)							
Other options available on request							
							

\* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.

\*\* Payload excludes the driver (75 kg) but includes cargo options. The total permissible cargo weight must not be exceeded.

\*\*\* Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.

\*\*\*\* Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included in the calculation.

Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.

The electric tipper is equipped with a hand-operated controller located on the driver's side.

! Don't drive while distracted. Don't use handheld devices while driving !


CONTACT US








Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com

Sophie +86 183 6122 7440 | sophieyu@jonwayev.com

For more information [www.jonwayev.com](http://www.jonwayev.com)





VEHICLE TYPE: PICKUP		CLASSIFICATION: L7e-CU		BATTERY PACK: 11.52 kWh		DRIVER: LHD (RHD available)	
MAIN SPECIFICATIONS							
Dimensions (L × W × H) unladen		3700 × 1440 (1735 Mirror) × 1800 mm		Top speed		75 km/h	
Body structure		Load-bearing structure		Gradeability		25% (14°)	
No. of Doors/Seats		2 / 2 (Driver and Passenger)		Minimum turning radius		5500 mm	
Wheelbase		2495 mm		Driving range (WVTA)*		130 km	
Track Width (Front/Rear)		1145 / 1195 mm		Real-world range		100+ km	
Ground Clearance (Curb Weight)		160 mm		Energy consumption*		≈110.8 Wh/km	
Ramp angles (Front/Rear)		48° / 30°		Energy efficiency*		≈9.0 km/kWh	
Gross Vehicle Weight		1450 kg		Battery warranty		4 years or 200,000 km <small>whichever comes first</small>	
Actual vehicle mass		770 kg		Vehicle warranty		3 years or 50,000 km <small>whichever comes first</small>	
CHARGING							
Charging speed		AC slow charging		Charger type		EU Type 2	
On-board charger (OBC)		2.2 kW		Charging time (20-80%)****		≈4 hours	
Charging distance in 1 hour (est.)****		≈16 km		Charging time (0-100%)****		≈7 hours	
ELECTRIC MOTOR							
Motor type		PMSM (Air cooled)		Peak power		20 kW (27 hp)	
Drive System		Rear-wheel drive		Max. torque		112 N.m	
Regenerative braking system		As Standard		Transmission		Fixed ratio	
BATTERY							
Battery type (Air-cooled)		LiFePO4		Battery pack weight (±10)		99 kg	
Rated capacity (Ah)		150 Ah		Battery capacity***		11.5 kWh	
Nominal voltage (V)		76.8 V		Battery pack energy density		≈116 Wh/kg	
CARGO PLATFORM							
Cargo type		Pickup		Bucket height		325 mm	
Bucket material		Alloy <small>Optional</small>		Bucket thickness		40 mm	
Payload		580 kg		Headboard height		1030 mm	
Loading area		2.2 m <sup>2</sup>		Bucket overall height		1100 mm	
Bucket Length		1700 mm		Weight of the bucket		70 kg	
Bucket Width		1375 mm					
TIRES & SUSPENSIONS							
Front suspension		McPherson		Brakes Front/Rear		Disc / Drum	
Rear suspension		Leaf Spring		Tire specifications		155R13C (LT)	
Parking Brake		Hand Brake (Foot Brake on RHD)		Wheels		Steel	
SAFETY FEATURES				LIGHTING SYSTEM			
ADAS Anti-lock Braking System ABS		Door Ajar Alarm		Front combination light LED		Daytime running light LED	
Electric Power Steering EPS		Reversing Warning Alarm		Combination Tail light LED		Interior lighting LED	
Driver Seat Belt Alarm		Acoustic Vehicle Alerting Systems					
Rear View Camers		3-Point Safety Belt (retractable)					
ACCESSORIES & OTHERS							
Intermittent windshield wipers		Key FOB / Keyless Entry		OBD connection		Radio, MP3, MP4	
Imitation leather seat cover		Push-Start button		9" LCD Infotainment display		Portable EU Type2 charger (220V)	
4-Way adjustable Seats (manual)		Power windows		Loudspeakers x 2		Foldable warning triangle & safety vest	
Heating		Door storage box		Bluetooth connectivity			
Central door locking system		Sun visor (flip) x 2		USB port x 1			
OPTIONS				PAINT OPTIONS			
Air condition		Alloy Wheel		White (standard) 		Light Green 	
Towing Hook		OBC 3.3 kW		Yellow 		Light Blue 	
Wall Charger 7.4 kW		OBC 7 kW		Black 		Customs Color (On Request)	
Spare tire				Light Grey 			
CARGO PLATFORM OPTIONS							
Pick-up: Alloy or Steel Tray							
Tipper: Alloy or Steel Tray							
Box (FRP Honeycomb Panel)							
Box Half (FRP Honeycomb Panel)							
Cold Chain (Max. Temp. -18°C)							
Other options available on request							

\* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.  
\*\* Payload excludes the driver (75 kg) but includes cargo options. The total permissible cargo weight must not be exceeded.  
\*\*\* Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.  
\*\*\*\* Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included in the calculation.  
Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.  
The electric tipper is equipped with a hand-operated controller located on the driver's side.  
! Don't drive while distracted. Don't use handheld devices while driving !

CONTACT US  
Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com  
Sophie +86 183 6122 7440 | sophieyu@jonwayev.com  
For more information [www.jonwayev.com](http://www.jonwayev.com)

