



VEHICLE TYPE: COLD CHAIN	HOMOLOGATION: L7e-CU	BATTERY PACK: 23.04 kWh	DRIVER: LHD (RHD available)
--------------------------	----------------------	-------------------------	-----------------------------

MAIN SPECIFICATIONS			
Dimensions (L x W x H) unladen	3700 x 1440 (1735 Mirror) x 2100 mm	Top speed	75 km/h
Body structure	Load-bearing structure	Gradeability	25% (14°)
No. of Doors/Seats	2 / 2 (Driver and Passenger)	Minimum turning radius	5500 mm
Wheelbase	2495 mm	Driving range (WVTA)*	240 km
Track Width (Front/Rear)	1145 / 1195 mm	Real-world range	190+ km
Ground Clearance (Curb Weight)	160 mm	Energy consumption*	≈125.6 Wh/km
Ramp angles (Front/Rear)	48° / 30°	Energy efficiency*	≈8.0 km/kWh
Gross Vehicle Weight	1450 kg	Battery warranty	4 years or 200,000 km <small>whichever comes first</small>
Actual vehicle mass	930 kg	Vehicle warranty	3 years or 50,000 km <small>whichever comes first</small>

CHARGING			
Charging speed	AC slow charging	Charger type	EU Type 2
On-board charger (OBC)	3.3 kW	Charging time (20-80%)*	≈5 hours
Charging distance in 1 hour (est.)*	≈21 km	Charging time (0-100%)*	≈9 hours

ELECTRIC MOTOR			
Motor type	PMSM (Air cooled)	Peak power	20 kW (27 hp)
Drive System	Rear-wheel drive	Max. torque	112 N.m
Regenerative braking system	As Standard	Transmission	Fixed ratio

BATTERY			
Battery type (Air-cooled)	LiFePO4	Battery pack weight (±10)	187 kg
Rated capacity (Ah)	300 Ah	Battery capacity***	23 kWh
Nominal voltage (V)	76.8 V	Battery pack energy density	≈129 Wh/kg

CARGO PLATFORM			
Cargo type	Refrigerated Box	Box external (L x W x H)	1710 (2260) x 1450 x 1360 mm
Cargo volume	2.8 m³	Box internal (L x W x H)	1625 x 1365 x 1275 mm
Cargo payload**	380 kg	Rear door frame (W x H)	1370 x 1280 mm
Operating temperature	-18°C ~+10°C	Rear door left (W x H)	630 x 1150 mm
Rated power of compressor	700 W (72V)	Rear door right (W x H)	630 x 1150 mm
Air Volume (Single Fan)	690 m³/h	Compressor unit (L x W x H)	1080 x 550 x 240 mm
Refrigerant	R404A	Panel thickness	85 mm

TIRES & SUSPENSIONS			
Front suspension	McPherson	Brakes Front/Rear	Disc / Drum
Rear suspension	Leaf Spring	Tire specifications	155R13C (LT)
Parking Brake	Hand Brake (Foot Brake on RHD)	Wheels	Alloy

SAFETY FEATURES		LIGHTING SYSTEM	
ADAS Anti-lock Braking System ABS	Door Ajar Alarm	Front combination light LED	Daytime running light LED
Electric Power Steering EPS	Reversing Warning Alarm	Combination Tail light LED	Interior lighting LED
Driver Seat Belt Alarm	Acoustic Vehicle Alerting Systems		
Rear View Camers	3-Point Safety Belt (retractable)		

ACCESSORIES & OTHERS			
Intermittent windshield wipers	Key FOB / Keyless Entry	OBD connection	Radio, MP3, MP4
Imitation leather seat cover	Push-Start button	9" LCD Infotainment display	Portable EU Type2 charger (220V)
4-Way adjustable Seats (manual)	Power windows	Loudspeakers x 2	Foldable warning triangle & safety vest
Heating	Door storage box	Bluetooth connectivity	
Central door locking system	Sun visor (flip) x 2	USB port x 1	

OPTIONS		PAINT OPTIONS	
Air condition	OBC 7 kW	White (standard) <input type="checkbox"/>	Light Green <input type="checkbox"/>
Wall Charger 7.4 kW	Spare tire	Yellow <input type="checkbox"/>	Light Blue <input type="checkbox"/>
		Black <input type="checkbox"/>	Customs Color (On Request)
		Light Grey <input type="checkbox"/>	

CARGO PLATFORM OPTIONS

Pick-up: Alloy or Steel Tray
 Tipper: Alloy or Steel Tray
 Box (FRP Honeycomb Panel)
 Box Half (FRP Honeycomb Panel)
 Cold Chain (Max. Temp. -18°C)
 Other options available on request



* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.
 ** Payload excludes the driver (75 kg) but includes cargo options. The total permissible cargo weight must not be exceeded.
 *** Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.
 **** Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included in the calculation.
 Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.
 The electric tipper is equipped with a hand-operated controller located on the driver's side.
 ! Don't drive while distracted. Don't use handheld devices while driving!

CONTACT US
 Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com
 Sophie +86 183 6122 7440 | sophieyu@jonwayev.com

For more information www.jonwayev.com

