

CARGO TYPE: FLATBED		WHEELBASE: SWB		BATTERY PACK: 17.66 kWh		DRIVER SEAT: LHD	
General Information				Driving Range ¹			
Classification		L7e-CU		Driving Range (WMTC)		210 km	
Body Structure		Load-bearing		Real-world Driving Range		168+ km	
Dimensions (L × W × H)		3110 x 1230 x 1640 mm		Energy Consumption		≈ 105 Wh/km	
Width with mirror opened		1460 mm		Energy Efficiency		≈ 9.5 km/Wh	
Wheelbase		2140 mm					
Seats / Doors		2 / 2 (available as one-seater)		Tires & Suspensions			
Ramp Angles (Front/Rear)		90° / 22°		Brake (Front / Rear)		Disc / Drum	
Track Width (Front/Rear)		960 / 1060 mm		Wheels		Steel	
Overhang (Front/Rear)		257 / 682 mm		Tire Size (Front / Rear)		145/70R12 (250 kPa)	
Gradeability		15% (8.53°)		Front Suspension		McPherson	
Min. Turning Radius		5000 mm		Rear Suspension		Leaf Spring	
Min. Ground Clearance		140 mm					
GVW		930 kg		Lighting			
Curb Weight		607 kg (600 kg if one seater)		Front Combination Light		Halogen	
				Daytime Running Light		Halogen	
				Turn Signal Lights		Halogen	
Electric Motor				Combination Tail light		LED	
Motor Type / Drive Mode		PMSM / RWD		Rear fog & Reversing light		LED	
Transmission		Fixed ratio		Interior Cabin Light		LED	
Top Speed		70 km/h					
Max Power (Contd. Rated)		15 kW (7.5 kW)		Standard Accessories			
Max Torque (Contd. Rated)		85 N.m (42.5 N.m)		CBS Combined Braking System		Power Windows	
Battery Pack ³				Intermittent Windshield Wiper		Analogue Instrument Cluster	
Battery Type		LiFePO4 (Air-cooled)		Imitation Leather Seat Covers		Heating	
Battery Pack Capacity		17.66 kWh		2-way Manual Seats		Rearview Mirrors ^(manual)	
Battery Pack Nominal Voltage		76.8V		1 × USB Port		7" LCD Infotainment Display	
Battery Pack Rated Capacity		230Ah		Reversing Warning Alarm		Bluetooth connectivity	
Battery Pack Weight		147 kg		2 × Cup Holders		OBD Connection	
				Central Door Lock		Rear-view Camera	
Cargo Platform ²				Key FOB / Keyless Entry		Key-in Ignition	
Box Volume		2 m³		3-point Safety Belt ^{*(retractable)}		EU Type2 Charging Plug	
Cargo Outside (L × W × H)		1510 × 1194 × 1277 mm		4 × Loudspeaker		Portable Charger (220V)	
Cargo Inside (L × W × H)		1397 × 1158 × 1207 mm		Adjustable Air Vents		Warning Triangle & Safety Vest	
Cargo Payload		323 kg (330 kg if one seater)		Drive Mode Dialer (R N D)			
Load Height		680 mm					
Charging ⁴				Warranty			
Charging Mode		AC charging		Battery Pack Warranty		4 years or 200k km ^(whichever comes first)	
On-board Charger (OBC)		3.3 kW		Vehicle Warranty		3 years or 40k km ^(whichever comes first)	
Charging Time (20-80%)		≈ 4.0 h		Options			
Charging Time (0-100%)		≈ 6.7 h		6.6 kW On-board Charger (OBC)		Air Condition	
Charging Distance in 1 hour (est.)		≈ 47 km		Alloy Wheel		Roof Rack Platform	
				Rooftop Solar Panel			