





VEHICLE TYPE: TIPPER		CLASSIFICATION: L7e-CU		BATTERY PACK: 23.04 kWh		DRIVER: LHD (RHD available)	
MAIN SPECIFICATIONS							
Dimensions (L × W × H) unladen	3700 × 1440 (1735 Mirror) × 1800 mm	Top speed	75 km/h				
Body structure	Load-bearing structure	Gradeability	25% (14°)				
No. of Doors/Seats	2 / 2 (Driver and Passenger)	Minimum turning radius	5500 mm				
Wheelbase	2495 mm	Driving range (WVTA)*	260 km				
Track Width (Front/Rear)	1145 / 1195 mm	Real-world range	200+ km				
Ground Clearance (Curb Weight)	160 mm	Energy consumption*	≈115.9 Wh/km				
Ramp angles (Front/Rear)	48° / 30°	Energy efficiency*	≈8.6 km/kWh				
Gross Vehicle Weight	1450 kg	Battery warranty	4 years or 200,000 km whichever comes first				
Actual vehicle mass	850 kg	Vehicle warranty	3 years or 50,000 km whichever comes first				
CHARGING							
Charging speed	AC slow charging	Charger type	EU Type 2				
On-board charger (OBC)	3.3 kW	Charging time (20-80%)*	≈5 hours				
Charging distance in 1 hour (est.)*	≈23 km	Charging time (0-100%)*	≈9 hours				
ELECTRIC MOTOR							
Motor type	PMSM (Air cooled)	Peak power	20 kW (27 hp)				
Drive System	Rear-wheel drive	Max. torque	112 N.m				
Regenerative braking system	As Standard	Transmission	Fixed ratio				
BATTERY							
Battery type (Air-cooled)	LiFePO4	Battery pack weight (±10)	187 kg				
Rated capacity (Ah)	300 Ah	Battery capacity***	23 kWh				
Nominal voltage (V)	76.8 V	Battery pack energy density	≈129 Wh/kg				
CARGO PLATFORM							
Cargo type	Tipper	Bucket thickness	40 mm				
Bucket material	Alloy Optional	Headboard height	1030 mm				
Payload	500 kg	Bucket overall height	1100 mm				
Loading area	2.2 m²	Weight of the bucket	70 kg				
Bucket Length	1700 mm	Maximum height load bed raised	2630 mm				
Bucket Width	1375 mm	Maximum tipping angle	45°				
Bucket height	325 mm	Load bed lifting time (empty)	15 sec				
TIRES & SUSPENSIONS							
Front suspension	McPherson	Brakes Front/Rear	Disc / Drum				
Rear suspension	Leaf Spring	Tire specifications	155R13C (LT)				
Parking Brake	Hand Brake (Foot Brake on RHD)	Wheels	Steel				
SAFETY FEATURES				LIGHTING SYSTEM			
ADAS Anti-lock Braking System ABS	Door Ajar Alarm	Front combination light LED	Daytime running light LED				
Electric Power Steering EPS	Reversing Warning Alarm	Combination Tail light LED	Interior lighting LED				
Driver Seat Belt Alarm	Acoustic Vehicle Alerting Systems						
Rear View Camers	3-Point Safety Belt (retractable)						
ACCESSORIES & OTHERS							
Intermittent windshield wipers	Key FOB / Keyless Entry	OBD connection	Radio, MP3, MP4				
Imitation leather seat cover	Push-Start button	9" LCD Infotainment display	Portable EU Type2 charger (220V)				
4-Way adjustable Seats (manual)	Power windows	Loudspeakers x 2	Foldable warning triangle & safety vest				
Heating	Door storage box	Bluetooth connectivity					
Central door locking system	Sun visor (flip) x 2	USB port x 1					
OPTIONS							
Air condition	OBC 7 kW	□ White (standard)	■ Light Green				
Towing Hook	Magnet-mounted wired control switch	■ Yellow	■ Light Blue				
Wall Charger 7.4 kW		■ Black	■ Customs Color (On Request)				
RHD version		■ Light Grey					
CARGO PLATFORM OPTIONS							



* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.
 ** Payload excludes the driver but includes cargo options. The total permissible cargo weight must not be exceeded.
 *** Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.
 **** Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included.
 Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.
 The electric tipper is equipped with a hand-operated controller located on the driver's side.
 ! Don't drive while distracted. Don't use handheld devices while driving!

CONTACT US
 Alex +86 139 6869 9888 | alexwang@jonwayev.com
 Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com
 Sophie +86 183 6122 7440 | sophieyu@jonwayev.com
 Ella +86 198 9583 6240 | ellawang@jonwayev.com
 For general inquiry contact us at contact@jonwayev.com





VEHICLE TYPE: TIPPER		CLASSIFICATION: L7e-CU		BATTERY PACK: 11.52 kWh		DRIVER: LHD (RHD available)	
MAIN SPECIFICATIONS							
Dimensions (L × W × H) unladen	3700 × 1440 (1735 Mirror) × 1800 mm			Top speed	75 km/h		
Body structure	Load-bearing structure			Gradeability	20% (11.3°)		
No. of Doors/Seats	2 / 2 (Driver and Passenger)			Minimum turning radius	5500 mm		
Wheelbase	2495 mm			Driving range (WVTA)*	130 km		
Track Width (Front/Rear)	1145 / 1195 mm			Real-world range	100+ km		
Ground Clearance (Curb Weight)	160 mm			Energy consumption*	≈110.8 Wh/km		
Ramp angles (Front/Rear)	48° / 30°			Energy efficiency*	≈9.0 km/kWh		
Gross Vehicle Weight	1450 kg			Battery warranty	4 years or 200,000 km whichever comes first		
Actual vehicle mass	770 kg			Vehicle warranty	3 years or 50,000 km whichever comes first		
CHARGING							
Charging speed	AC slow charging			Charger type	EU Type 2		
On-board charger (OBC)	2.2 kW			Charging time (20-80%)****	≈4 hours		
Charging distance in 1 hour (est.)****	≈16 km			Charging time (0-100%)****	≈7 hours		
ELECTRIC MOTOR							
Motor type	PMSM (Air cooled)			Peak power	20 kW (27 hp)		
Drive System	Rear-wheel drive			Max. torque	112 N.m		
Regenerative braking system	As Standard			Transmission	Fixed ratio		
BATTERY							
Battery type (Air-cooled)	LiFePO4			Battery pack weight (±10)	99 kg		
Rated capacity (Ah)	150 Ah			Battery capacity***	11.5 kWh		
Nominal voltage (V)	76.8 V			Battery pack energy density	≈116 Wh/kg		
CARGO PLATFORM							
Cargo type	Tipper			Bucket thickness	40 mm		
Bucket material	Alloy Optional			Headboard height	1030 mm		
Payload	580 kg			Bucket overall height	1100 mm		
Loading area	2.2 m ²			Weight of the bucket	70 kg		
Bucket Length	1700 mm			Maximum height load bed raised	2630 mm		
Bucket Width	1375 mm			Maximum tipping angle	45°		
Bucket height	325 mm			Load bed lifting time (empty)	15 sec		
TIRES & SUSPENSIONS							
Front suspension	McPherson			Brakes Front/Rear	Disc / Drum		
Rear suspension	Leaf Spring			Tire specifications	155R13C (LT)		
Parking Brake	Hand Brake (Foot Brake on RHD)			Wheels	Steel		
SAFETY FEATURES				LIGHTING SYSTEM			
ADAS Anti-lock Braking System ABS	Door Ajar Alarm			Front combination light LED	Daytime running light LED		
Electric Power Steering EPS	Reversing Warning Alarm			Combination Tail light LED	Interior lighting LED		
Driver Seat Belt Alarm	Acoustic Vehicle Alerting Systems						
Rear View Camers	3-Point Safety Belt (retractable)						
ACCESSORIES & OTHERS							
Intermittent windshield wipers	Key FOB / Keyless Entry			OBD connection	Radio, MP3, MP4		
Imitation leather seat cover	Push-Start button			9" LCD Infotainment display	Portable EU Type2 charger (220V)		
4-Way adjustable Seats (manual)	Power windows			Loudspeakers x 2	Foldable warning triangle & safety vest		
Heating	Door storage box			Bluetooth connectivity			
Central door locking system	Sun visor (flip) x 2			USB port x 1			
OPTIONS				PAINT OPTIONS			
Air condition	Alloy Wheel			☐ White (standard)	☒ Light Green		
Towing Hook	OBC 3.3 kW			☒ Yellow	☒ Light Blue		
Wall Charger 7.4 kW	OBC 7 kW			☒ Black	☒ Customs Color (On Request)		
RHD version	Magnet-mounted wired control switch			☐ Light Grey			
CARGO PLATFORM OPTIONS							
Pick-up: Alloy or Steel Tray Tipper: Alloy or Steel Tray Box (FRP Honeycomb Panel) Box Half (FRP Honeycomb Panel) Cold Chain (Max. Temp. -18°C) Other options available on request							

* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.
** Payload excludes the driver but includes cargo options. The total permissible cargo weight must not be exceeded.
*** Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.
**** Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included.
Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.
The electric tipper is equipped with a hand-operated controller located on the driver's side.
! Don't drive while distracted. Don't use handheld devices while driving!

CONTACT US
Alex +86 139 6869 9888 | alexwang@jonwayev.com
Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com
Sophie +86 183 6122 7440 | sophieyu@jonwayev.com
Ella +86 198 9583 6240 | ellawang@jonwayev.com
For general inquiry contact us at contact@jonwayev.com

