








VEHICLE TYPE: COLD CHAIN		HOMOLOGATION: L7e-CU		BATTERY PACK: 23.04 kWh		DRIVER: LHD <small>(RHD available)</small>	
MAIN SPECIFICATIONS							
Dimensions (L × W × H) unladen		3700 × 1440 (1735 Mirror) × 2100 mm		Top speed		75 km/h	
Body structure		Load-bearing structure		Gradeability		25% (14°)	
No. of Doors/Seats		2 / 2 (Driver and Passenger)		Minimum turning radius		5500 mm	
Wheelbase		2495 mm		Driving range (WVTA)*		240 km	
Track Width (Front/Rear)		1145 / 1195 mm		Real-world range		190+ km	
Ground Clearance (Curb Weight)		160 mm		Energy consumption*		≈125.6 Wh/km	
Ramp angles (Front/Rear)		48° / 30°		Energy efficiency*		≈8.0 km/kWh	
Gross Vehicle Weight		1450 kg		Battery warranty		4 years or 200,000 km <small>whichever comes first</small>	
Actual vehicle mass		930 kg		Vehicle warranty		3 years or 50,000 km <small>whichever comes first</small>	
CHARGING							
Charging speed		AC slow charging		Charger type		EU Type 2	
On-board charger (OBC)		3.3 kW		Charging time (20-80%)****		≈5 hours	
Charging distance in 1 hour (est.)****		≈21 km		Charging time (0-100%)****		≈9 hours	
ELECTRIC MOTOR							
Motor type		PMSM (Air cooled)		Peak power		20 kW (27 hp)	
Drive System		Rear-wheel drive		Max. torque		112 N.m	
Regenerative braking system		As Standard		Transmission		Fixed ratio	
BATTERY							
Battery type (Air-cooled)		LiFePO4		Battery pack weight (±10)		187 kg	
Rated capacity (Ah)		300 Ah		Battery capacity***		23 kWh	
Nominal voltage (V)		76.8 V		Battery pack energy density		≈129 Wh/kg	
CARGO PLATFORM							
Cargo type		Refrigerated Box		Box external (L × W × H)		1710 (2260) × 1450 × 1360 mm	
Cargo volume		2.8 m³		Box internal (L × W × H)		1625 × 1365 × 1275 mm	
Cargo payload**		380 kg		Rear door frame (W × H)		1370 × 1280 mm	
Operating temperature		-18°C ~+10°C		Rear door left (W × H)		630 × 1150 mm	
Rated power of compressor		700 W (72V)		Rear door right (W × H)		630 × 1150 mm	
Air Volume (Single Fan)		690 m³/h		Compressor unit (L × W × H)		1080 × 550 × 240 mm	
Refrigerant		R404A		Panel thickness		85 mm	
TIRES & SUSPENSIONS							
Front suspension		McPherson		Brakes Front/Rear		Disc / Drum	
Rear suspension		Leaf Spring		Tire specifications		155R13C (LT)	
Parking Brake		Hand Brake (Foot Brake on RHD)		Wheels		Alloy	
SAFETY FEATURES				LIGHTING SYSTEM			
ADAS Anti-lock Braking System ABS		Door Ajar Alarm		Front combination light LED		Daytime running light LED	
Electric Power Steering EPS		Reversing Warning Alarm		Combination Tail light LED		Interior lighting LED	
Driver Seat Belt Alarm		Acoustic Vehicle Alerting Systems					
Rear View Camers		3-Point Safety Belt (retractable)					
ACCESSORIES & OTHERS							
Intermittent windshield wipers		Key FOB / Keyless Entry		OBD connection		Radio, MP3, MP4	
Imitation leather seat cover		Push-Start button		9" LCD Infotainment display		Portable EU Type2 charger (220V)	
4-Way adjustable Seats (manual)		Power windows		Loudspeakers x 2		Foldable warning triangle & safety vest	
Heating		Door storage box		Bluetooth connectivity			
Central door locking system		Sun visor (flip) x 2		USB port x 1			
OPTIONS				PAINT OPTIONS			
Air condition		OBC 7 kW		□ White (standard)		■ Light Green	
Towing Hook		Spare tire		■ Yellow		■ Light Blue	
Wall Charger 7.4 kW				■ Black		■ Customs Color (On Request)	
RHD version				■ Light Grey			

CARGO PLATFORM OPTIONS

Pick-up: Alloy or Steel Tray
Tipper: Alloy or Steel Tray
Box (FRP Honeycomb Panel)
Box Half (FRP Honeycomb Panel)
Cold Chain (Max. Temp. -18°C)
Other options available on request



* The actual driving range may greatly vary based on driving behavior, charging habits, speed, payload, terrain, accessories and weather conditions.
** Payload excludes the driver but includes cargo options. The total permissible cargo weight must not be exceeded.
*** Battery pack capacity may naturally degrade over time and with use, which will affect vehicle overall performance.
**** Charging times are approximate and require Type 2 compatible charging stations. Charging losses of 20% have been included.
Technical specifications and data are true and accurate as of the publication date which may differ according to the country of sale and are subject to change without prior notice. Images provided are for illustrative purposes only and may not reflect the actual vehicle or its features. Figures provided are intended for comparability purposes only and should be compared with vehicles tested under the same technical procedures and within a similar weight class. Please check with your dealer for any local specifications.
The electric tipper is equipped with a hand-operated controller located on the driver's side.
! Don't drive while distracted. Don't use handheld devices while driving!

CONTACT US

Alex +86 139 6869 9888 | alexwang@jonwayev.com
Shelton +86 188 6292 8261 | sheltonwu@jonwayev.com
Sophie +86 183 6122 7440 | sophieyu@jonwayev.com
Ella +86 198 9583 6240 | ellawang@jonwayev.com
For general inquiry contact us at contact@jonwayev.com

