



JONWAY EV's T21 — a reliable battery electric mini truck designed specifically for SMEs running a last-mile delivery business. Its compact design allows for effortless driving and maneuvering in narrow streets and busy urban environments.

**DISCLAIMER:**

The battery pack capacity may/will degrade over time and usage. The actual driving range will vary depending on driving behaviors, charging intervals, driving speed, cargo load weight and weather conditions. The figures shown are for comparability purposes; only compare with other vehicles tested to the same technical procedures and similar vehicle weight class. The charging times are estimates. Charging stations must be Type 2 compatible. The permissible total cargo weight must not exceed. Technical specifications and data are valid at the time of publishing. The product images shown are for illustrative purposes only. Specifications are subject to change without prior notice.

**JONWAY**

# T2 GENERAL SPECIFICATIONS (L7e-CU)

**JONWAY**

|                          | LS                       | HS                       |
|--------------------------|--------------------------|--------------------------|
| Dimensions (L × W × H)   | 3175 x 1240 x 1950 mm    | 3175 x 1240 x 1950 mm    |
| Wheelbase                | 2090 mm                  | 2090 mm                  |
| Ramp angles (Front/Rear) | 90° / 22°                | 90° / 22°                |
| Min. turning radius      | 5000 mm                  | 5000 mm                  |
| Min. ground clearance    | 135 mm                   | 135 mm                   |
| GVW (Gross)              | 1200 kg                  | 1200 kg                  |
| Curb weight (Net)        | 616 kg                   | 695 kg                   |
| Cargo volume             | 1.84 m <sup>3</sup>      | 1.84 m <sup>3</sup>      |
| Cargo Inside (L × W × H) | 1420 × 1110 × 1170 mm    | 1420 × 1110 × 1170 mm    |
| Peak power               | 7.5 kW                   | 15 kW                    |
| Peak torque              | 55 N.m                   | 85 N.m                   |
| Top speed                | 45 km/h                  | 70 km/h                  |
| Gradeability             | 20% (11.54°)             | 20% (11.54°)             |
| Drive mode               | Rear-wheel drive         | Rear-wheel drive         |
| 1-Speed transmission     | Fixed ratio              | Fixed ratio              |
| Driving range            | 80 km                    | 130 km                   |
| Real-life driving range  | 60+ km                   | 100+ km                  |
| Battery pack capacity    | 7.68 kWh                 | 11.52 kWh                |
| Battery type             | LiFeP04                  | LiFeP04                  |
| On-board charger (OBC)   | 2.2 kW (6.6 kW optional) | 2.2 kW (6.6 kW optional) |
| Charging time (20-80%)   | ≈ 2.6 h / 0.9 h          | ≈ 3.9 h / 1.3 h          |
| Charging time (0-100%)   | ≈ 4.4 h / 1.5 h          | ≈ 6.5 h / 2.2 h          |

**DISCLAIMER:**

The battery pack capacity may/will degrade over time and usage. The actual driving range will vary depending on driving behaviors, charging intervals, driving speed, cargo load weight and weather conditions.

The figures shown are for comparability purposes; only compare with other vehicles tested to the same technical procedures and similar vehicle weight class. The charging times are estimates. Charging stations must be Type 2 compatible. The permissible total cargo weight must not exceed. Technical specifications and data are valid at the time of publishing. The product images shown are for illustrative purposes only. Specifications are subject to change without prior notice.