

A920Pro

ICONIC Smart Mobile



Food & Beverage



Fashion & Retail



Transportation



SMARTPOS



Powered by
Android 10/14



PCI 6 SRED
PCI 7 SRED



5.5" or 6.56"
HD+ Display



Top-Side Scanner
Front & Rear Cameras



Advanced
Connectivity



MAXSTORE

A920Pro

Android Mobile

SPECIFICATIONS	A920Pro 6.56" Display	A920Pro 5.5" Display
 Operating System	PayDroid Powered by Android 14	PayDroid Powered by Android 10
 Processor	Dual-core Cortex A75 + Six-Core Cortex A55, 1.6GHz	ARM Cortex A53 Quad-Core, 1.4GHz + Secure Processor
 Memory	Default: 2GB DDR RAM + 32GB eMMC Flash Optional: 4GB DDR RAM + 32GB eMMC Flash Optional: 4GB DDR RAM + 64GB eMMC Flash Extended microSD Card Slot Up to 1TB	Default: 2GB DDR RAM + 16GB eMMC Flash Extended microSD Card Slot Up to 128GB
 Card Readers	Chip & PIN Contactless (NFC TAG) Magnetic Stripe	Chip & PIN Contactless (NFC Tag) Magnetic Stripe
 Cameras	5MP FF Front Camera + 8MP AF Rear Camera + Top-Side 2MP Barcode Scanner	5MP FF Front Camera + 8MP AF Rear Camera + Top-Side 0.3MP Barcode Scanner Optional: Top-Side 2MP Barcode Scanner
 Displays	6.56" IPS HD+ 720 x 1612 Pixels Optional Customer Facing Display: 1.99" 170 x 320 Pixels	5.5" IPS HD+ 720 x 1440 Pixels
 Comms Configurations	4G + WiFi 2.4GHz/5GHz + Bluetooth 5.0	4G + WiFi 2.4GHz + Bluetooth 5.0 Optional: 4G + WiFi 5GHz + Bluetooth 5.0
 Battery	5150mAh 3.7V, 19.055Wh	●
 Printer	80mm/sec Paper Roll Outer Diameter: 40mm	●
 SIM / SAM	1 Micro SIM + 2 SAM 1 Micro SIM + 1 Mini SIM + 1 SAM Optional: eSIM + 1 Micro SIM + 2 SAM	1 Micro SIM + 2 SAM 1 Micro SIM + 1 SIM + 1 SAM
 Positioning	GPS A-GPS GLONASS BEIDOU	GPS GLONASS BEIDOU
 Keys / Buttons	4 Keys: Power ON/OFF Volume+ Volume- Quick Scan key	●
 Audio	1 Buzzer 1 Speaker 1 Microphone 1 Vibrator	1 Buzzer 1 Speaker 1 Microphone
 Ports	1 Type-C OTG Magnetic Charging Port 6 PIN POGO PIN	1 Type-C OTG 6 PIN POGO PIN
 Adapter	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
 Physical	185.05 x 78 x 54.75mm, 400g (including battery)	178.3 x 78 x 54.2mm, 390g (including battery)
 Environmental	0°C ~ 45°C (32°F ~ 113°F) Operating Temperature, Non-Charging -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature, Non-Charging -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
 Accessories	L920Pro-BC: Charging Base 1 Power Port (Type-C) L920Pro-BM: Charging Base 1 Ethernet(RJ45) 1 RS232 (RJ45) 2 USB(Host) 1 Power Port (Type-C) L920Pro-BE: Charging + Wireless WiFi 5GHz + Bluetooth 5.0 1 RS232 (RJ45) 1 Ethernet (RJ45) 1 Power Port (Type-C) 1 Type-C (Device) 1 USB (Host)	● Same BC & BE bases (but no BM version)
 Certifications	PCI PTS 7.x SRED EMV L1 & L2 EMV contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs ATEX BQB	PCI PTS 6.x SRED EMV L1 & L2 EMV contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs ATEX FCC IC PTCRB WPC BIS Anatel ABECS

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX and the PAX logo are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. The Bluetooth 5.0 word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Limited is under license. Other trademarks and trade names are those of their respective owners. © 2025 PAX Technology Limited. All rights reserved.