

# FRAGMENT

## S A F E T Y

### SALONGA S3 HRO SRC

Reference : SALONGAS3

HIGH CUT SAFETY SHOES S3 HRO SRC – OUTSOLE 100% NITRILE



#### USER BENEFITS

- ✳ **Ultra robust** : Front leather bumper
- ✳ **Hydrolysis resistant** shoe : 0% PU (upper and sole)
- ✳ **Heat resistant** outsole (300°C for 60 seconds)
- ✳ Side **reflective stripes**

#### PRODUCT SPECIFICATIONS

**Upper** : Water resistant full-grain leather + high resistant nylon + front bumper **Color** : Black / Red

**Protection parts** : Stainless steel

**Sizes** : 36 to 48

**Lining** : Breathable mesh with extra padding

**Weight** : 720 g for size 42

**Insole** : Removable premolded - EVA

**Packing** : 10x pairs /box

**Outsole** : Welded 100% Nitrile - Hydrolyse resistant

**Extra** : Side reflective stripe and red leather

#### PROTECTIONS

- 🛡 Safety toe cap (200 J)
- ⚡ A : Antistatic
- 🔥 E : Energy absorbing heel
- 🛢 FO : Oil resistant outsole
- 🔪 P : Puncture resistant sole (1 100 Newtons)
- 🚫 WRU : Water resistant upper
- 👤 SRC : Slip resistance
- 🔥 HRO : Heat resistant outsole (300°C for 60 seconds)

#### SECTORS OF USE

INDUSTRIES



OIL & GAS



MINING



CONSTRUCTION



METALLURGY / FOUNDRY



CHEMISTRY



FORESTRY / PRUNNING



#### CERTIFICATIONS

REGULATION (UE) 2016/425

EN ISO 20344:2011 Personal protective equipment – Test methods for footwear

EN ISO 20345:2011 Personal protective equipment – Safety footwear

S3 HRO : Additional special requirements

SRC : Slip resistance