

# Q25

## Linux PINpad



Supermarkets



Fashion & Retail



Food & Beverage



CLASSIC



Powered by  
Prolin



PCI 6  
SRED



2.8"  
Display



0.3MP  
Front



Pole Stand  
Option

## SPECIFICATIONS

|                                                                                     |                             |                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>Operating System</b>     | Prolin                                                                                                                                                                                                                |
|    | <b>Processor</b>            | Cortex A7                                                                                                                                                                                                             |
|    | <b>Memory</b>               | 256MB FLASH + 256MB DDR RAM                                                                                                                                                                                           |
|    | <b>Card Readers</b>         | Chip & PIN   NFC Contactless   Magnetic Stripe                                                                                                                                                                        |
|    | <b>Cameras</b>              | Optional 0.3MP Front-Facing                                                                                                                                                                                           |
|    | <b>Display</b>              | 2.8" TFT QVGA 320 * 240 Pixels<br>Optional Touch Screen                                                                                                                                                               |
|    | <b>Comms Configurations</b> | RS232   Fast Ethernet   USB 2.0   WiFi (2.4G / 5G ) (optional)                                                                                                                                                        |
|    | <b>Battery</b>              | No                                                                                                                                                                                                                    |
|    | <b>Printer</b>              | No                                                                                                                                                                                                                    |
|    | <b>SIM / SAM</b>            | 3 PSAM                                                                                                                                                                                                                |
|   | <b>Positioning</b>          | No                                                                                                                                                                                                                    |
|  | <b>Keys / Buttons</b>       | 18 Keys: Menu   Up   Down   Func   0~9   Alpha   Enter   Clear   Cancel   Back-Lighting                                                                                                                               |
|  | <b>Audio</b>                | 1 Speaker                                                                                                                                                                                                             |
|  | <b>Ports</b>                | Multi-Functional Port   1 Type-C USB 2.0, OTG   1 Kensington                                                                                                                                                          |
|  | <b>Physical</b>             | 159 * 80 * 43 mm, 260g                                                                                                                                                                                                |
|  | <b>Environmental</b>        | 0°C ~ 50°C (32°F ~ 122°F) Operating Temperature<br>-20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature<br>5% ~ 93% Relative Humidity, Non-Condensing                                                                      |
|  | <b>Accessories</b>          | Privacy Shields   Multiple Cabling Options                                                                                                                                                                            |
|  | <b>Certifications</b>       | PCI PTS 6.x, SRED   EMV L1 & L2   EMV Contactless L1   MasterCard Contactless<br>Visa payWave   American ExpressPay   Discover D-PAS   Interac Flash<br>J/Speedy   qUICS   MasterCard TQM   UL   CE   FCC   IC   RoHS |

