

VERIFICATION OF COMPLIANCE

No.: LVD SHES171201192401PVC
Applicant: MAYSUN SOLAR FZCO
Warehouse No. FZS2AB01, Jebel Ali, Dubai, UAE
Manufacturer: Same as applicant
Product Name: Photovoltaic (PV) Modules
Product Description: Photovoltaic (PV) Modules
Trade Mark:



Rating: Max. Power: 380 W, Max. system voltage:1500V/1000V
Protection against Electric Shock: Application class: Class A
Degree of Protection: N/A
Additional Information: N/A

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: EN 61730-1:2007+A1:2012+A2:2013+A11:2014
EN 61730-2:2007+A1:2012

as shown in the

Test Report Number(s): SHES171201192401/02/03

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant harmonized standards under the Low Voltage Directive 2014/35/EU. The CE marking as shown below can be affixed, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The affixing of the CE marking presumes in addition that the conditions in annexes III and IV of the Directive are fulfilled.



A handwritten signature in blue ink that reads 'Erin Lin'.

Erin Lin
Laboratory Technical Manager
SGS-CSTC

2018-01-05

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)

No.:

LVD SHES171201192401PVC

Model No.:	With 6" mono c-Si cell: MSxxxM-72 (xxx=310 to 380, in increments of 5, 72 cells) MSxxxM-60 (xxx=250 to 315, in increments of 5, 60 cells) MSxxxM-54 (xxx=230 to 285, in increments of 5, 54 cells) MSxxxM-48 (xxx=205 to 255, in increments of 5, 48 cells) MSxxxM-36 (xxx=150 to 190, in increments of 5, 36 cells) With 6" poly c-Si cell: MSxxxP-72 (xxx=280 to 340, in increments of 5, 72 cells) MSxxxP-60 (xxx=235 to 280, in increments of 5, 60 cells) MSxxxP-54 (xxx=210 to 255, in increments of 5, 54 cells) MSxxxP-48 (xxx=180 to 230, in increments of 5, 48 cells) MSxxxP-36 (xxx=140 to 165, in increments of 5, 36 cells)
------------	--



Erin Lin

Laboratory Technical Manager
SGS-CSTC

2018-01-05

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)