Litchi



Stylish Design, Unique Experience

Litchi's sleek look comes from its suspended design. Made of aluminum alloy, it's anodized to give you a unique experience.

Outstanding Setup, Excellent Performance

Features a 15.6" IPS high-definition main screen and 15.6"/10.1" associated screen to meet diverse business needs. Equipped with rich interfaces like Cash Drawer, Gigabit Ethernet Port, USB, Serial Port, etc., and compatible with various commercial peripherals.

Convenient and Secured

Utilizing IoT device access security and face recognition technology, Litchi ensures safer and faster operations.

☐ Cutting-Edge System, Innovative Feature

With the adoption of Android 12 OS and integration of LinkUp, Litchi achieves seamless ecological integration and collaboration, doubling business efficiency.











Litchi Specifications

Model Name: L1600 / L1601 / L1602



Operating System

Android 12 Supporting Uniphiz

Displays



Processor

Quad-Core



Memory

LPDDR4X 4GB + eMMC 64GB
Optional:
LPDDR4X 2GB + eMMC 16GB
External:
MicroSD Card slot (Up to 128G



Cameras

Optional: Main Screen Camera: 5MP Auto Focus Optional: Secondary Screen Camera: 5MP Auto Focus



Button

Power Butto



Audio

Speaker: 3W Microphone



Comms Configurations

Main Screen: 15.6" 1920 × 1080 px IPS FHD Touch Screen Secondary Screen:

WiFi 2.4GHz / 5GHz



SAM

Optional: 1 * Mini SAM



Power Indicator

White LED



Ports

1 * USB Type-A 3.0 | 3 * USB Type-A | 1 * USB Type-C | 1 * LAN (1000M) 1 * DK (RJ11, 24V / 12V) | 1 * RS232(RJ45) | DC IN | Audio Jack



Environmental

Operating Temperature: $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ ($32^{\circ}\text{F} \sim 122^{\circ}\text{F}$) Storage Temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ ($-4^{\circ}\text{F} \sim 158^{\circ}\text{F}$) Relative Humidity: $10\% \sim 93\%$, non-condensing



Power

Input: 100-240V AC, 1.0A Output: 24V DC, 1.5A



Physical

364.6 × 220.0 × 322.4mm







