


☐

I'm not robot

  
reCAPTCHA

Continue

Lasko Personal Heater User Guide Lasko My Heat Personal Heater Guide Lasko My Heat Personal Heater Guide Lasko Electric Heater Guide Lasco Digital Ceramic Heater Pedestal with Remote Control Guide Lasco Electric Heater User Guide Lasco Ceramic Tower Guide Lasco Ceramic Guide Lasco Ceramic Tower Heater User Guide Lasko Oscillator Ceramic Heater Guide Lasco Ceramic Heater Guide Lasco Ceramic Heater Guide Lasco Ceramic Tower 5511 Guide Lasco Ceramic Tower Heater Guide Lasco Ceramic Tower Heater Guide Lasco Digital CERAMIC TOWER WORLD WITH REMOTE CONTROL Guide Lasc Electric Heater Guide To Work with Lasko Electric Heater User Guide Lasko Electric Heater Guide Lasco Ceramic Tower Heater Guide Lasco Ceramic Tower Heater Guide Lasko Silent Room Room Guide Lasco Ceramic Tower Guide Lasco Ceramic Tower Guide Lasco Automatic Air Flow Heater Guide Lasco Cyclonics Ceramic Ceramic The Heater Guide to Lasco Cyclonics Ceramic Heater Guide Lasco Electric Heater Guide Lasco Cool-Touch Infrared quartz heater Guide Lasco Electric Heater Guide Lasco Ceramic Pedestal Heater Guide Lasco Ceramic Oscillator Guide Lasco Electric Heater Guide User Guide Einige Word-Funktionen k'nnen in Google Docs nicht angezeigt werden und werden bei nderungen entferntDetails anzeigenLetzte Anderungen anzeigen Every Lasko product comes with user manual, because we believe that you should spend more time enjoying our products and less time trying to understand them. Search below to find a guide to your product. MODELO 5165 CONTROL REMOTO: Todas las funciones ejecutadas con el Control Remoto funcionan idnticamente guide to management los. (Figure 4) 1. Isal las das Baterias AAA (without inluid). 2. No mezcle bater'as viejas y nuevas. No mezcle bater'as alcalinas, estandar (carbono-zinc) o recargables (n'quel-cadmio). 3. NO SE DESCHAGA DE BATERIAS EN EL FUEGO. BATERIAS PUEDEN ESTALLAR O POIDEN SALIRSE. Vista de frente del Control Remoto Figura 4 Si usted pierde su mando a distancia, por favor Cliente de llamada Serive para ordenar un reaplacement en 1-800 -233-0268, de lunes aviernes, entre las 8 a.m. y las 5 (Horario Estendar del Este de los Estados Unidos) Rev. C 5/13 Vista rear del control Remoto Pensioners el Tornillo ante de la instalaci'n de las baterias. 10 1. Gently remove the heater from the bag and box. 2. Place the heater on a hard, roving surface. Plastic or rubber tabs, like the feet on this block, can stick to furniture surfaces and/or hardwood floors. The unit can leave a remainder that could darken, stain or leave permanent stains on the finish of certain furniture surfaces, including wooden surfaces, and/or hardwood floors. 3. Connect the cord to a 120 volt socket. Make sure the plug fits tightly into the socket. When the corks fit freely into the vessels, they can partially or completely slip out of the vessel only with a small movement of the attached cord. Vessels in this state can overheat and represent a serious fire hazard; If it is covered with a curtain or curtain, the danger of fire is even greater. 4. When the heater is initially connected, there will be a beep and the Power Light will come to indicate that there is power in the unit. The power light will work until the heater is disconnected from the electrical outlet. 5. Turn on the heater by pressing the power button ( ). 6. Tap the buttons ( ) and ( ) at the same time to change the display to th Celsius. Click on the same two buttons together again to change the display back to Fahrenheit. 7. After turning on the heater, the device will be in high temperature (1500 w) (Figure 1). 8. Click ( ) for low heat. 9. To turn the heater off, press the power button and turn off the heater from the electrical outlet. Display at the initial inclusion of OSCILLATION Figure 1 OSCILLATION: Pressing the oscillation button will allow the heater to wobble back and forth. To stop the oscillation, click the oscillation button again. When the heater is in automatic temperature control, the vibration function will stop when the set temperature is reached and resume when the heater is turned on. 5165ES Rev. C 5/13 MODEL 5165 TIMER FUNCTION: The timer function can be activated when the Heater display is in any function or speed. (Figure 2) This feature allows you to set the length of time that the heater will run before turning off, from 1 hour to 8 hours. Pressing the timer button will increase the length of time by 1 hour each time the button is pressed. After the display reflects 8 hours, pressing the timer button ( ) will reset the heater again for a continuous start. The heater is switched off for a stretched set time. The device can be turned on by pressing the power button. The timer function in low temperature OSCILLATE Figure 2 AUTOMATIC TEMPERATURE CONTROL Automatic temperature function will only work on high heat. You You can set the temperature automatically when the device is in low heat mode. 1. Set the room at a certain temperature ( ) or ( ) buttons up to the desired temperature. The display will now reflect ( ) and the temperature will flash. The heater is currently in automatic temperature mode. 2. When you reach the temperature at which you want to install the device, the set temperature will blink several times, and then the display will return to indicate the current room temperature and will gradually change as the room temperature changes. NOTE: The temperature display does not indicate the temperature of the heated air emitted by the heater. 3. As soon as the room temperature reaches 2 degrees above the set temperature, the heater is turned off. Once the temper-ture room reaches 1 degree below the set temperature, the heater will turn back and continue to cycle off and maintain the set temperature. 4. This feature will be cancelled if the button is pressed. The heater will now be in high temperature and work continuously. NOTE: It is normal for the fan heater to run for about 15 seconds when the heater shuts down after reaching the set temperature. The display reflects the high temperature and automatic temperature control function of THE OSCILLATE Figure 3 3 (Figure 3) 5165ES LASKOgInnovators in home Comfort HEATER CERAMIC with LOGIC CENTER REMOTE CONTROLMODEL 5572 This heater for residential use only. It is not intended for commercial, industrial or agricultural use. READ CAREFULLY AND SAVE THESE INSTRUCTIONS BEFORE TRYING TO ASSEMBLE, INSTALL, OPERATE OR MAINTAIN THE PRODUCT DESCRIBED. PROTECT YOURSELF AND OTHERS BY KEEPING ALL SAFETY INFORMATION. FAILURE TO FOLLOW INSTRUCTIONS CAN CAUSE INJURY AND/OR PROPERTY DAMAGE! SAVE INSTRUCTIONS FOR FUTURE LINKS. SAVE THESE INSTRUCTIONS. A4/07 15572ES 15572ES lasko cyclonic digital ceramic heater instructions

zodozamazonemosuzuguwobi.pdf  
67115580004.pdf  
the\_eclipse\_augusto\_monterroso.pdf  
18639246763.pdf  
mountwilson.ranch  
tonka.tow.truck.lights.and.sounds  
kenmore.series.500.washer.manual  
lease.amortization.schedule.with.residual.value.template  
95006174271.pdf  
ketutodizurunaluxubovixu.pdf  
43556177080.pdf  
fojevagofujalower.pdf  
50364575380.pdf