

# T8 防水植物燈管



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞





IP22

|             |                |       |       |
|-------------|----------------|-------|-------|
| 材質          | 鋁合金+塑料         |       |       |
| 演色性 (CRI)   | >80            |       |       |
| 功率因數        | >0.9           |       |       |
| 色溫 (CCT)    | 3000K          | 4000K | 6500K |
| 功率 (W)      | 9W             | 18W   |       |
| 發光效率        | >100 lm/w      |       |       |
| 光通量/流明 (lm) | 900 lm-1800 lm |       |       |
| 光源壽命        | 30000hr        |       |       |
| 輸入電壓        | 100-240 Vac    |       |       |

## 產品型號

|    |     |                 |
|----|-----|-----------------|
| 2呎 | 9W  | T8G- 2FPL1-009W |
| 4呎 | 18W | T8G- 4FPL1-018W |



# T8 1呎燈管



R45674



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞



IP22

鋁合金+塑料




鋁合金+玻璃



|             |                   |       |       |
|-------------|-------------------|-------|-------|
| 材質          | 鋁合金+塑料/鋁合金+玻璃     |       |       |
| 演色性 (CRI)   | >80               |       |       |
| 功率因數        | >0.9              |       |       |
| 色溫 (CCT)    | 3000K             | 4000K | 6500K |
| 功率 (W)      | 4W                |       |       |
| 發光效率        | 100 lm/w-180 lm/w |       |       |
| 光通量/流明 (lm) | 400lm             |       |       |
| 光源壽命        | 50000hr           |       |       |
| 輸入電壓        | 100-240 Vac       |       |       |

## 產品型號

|    |                      |
|----|----------------------|
| 4W | T8N-1FAL1-004W-60K-H |
|----|----------------------|



# T8 2呎燈管



R45674



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞



IP22

鋁合金+塑料




鋁合金+玻璃



|             |                   |       |       |
|-------------|-------------------|-------|-------|
| 材質          | 鋁合金+塑料/鋁合金+玻璃     |       |       |
| 演色性 (CRI)   | >80               |       |       |
| 功率因數        | >0.9              |       |       |
| 色溫 (CCT)    | 3000K             | 4000K | 6500K |
| 功率 (W)      | 7W                | 9W    | 10W   |
| 發光效率        | 100 lm/w-180 lm/w |       |       |
| 光通量/流明 (lm) | 700 lm-1000 lm    |       |       |
| 光源壽命        | 50000hr           |       |       |
| 輸入電壓        | 100-240 Vac       |       |       |

## 產品型號

|     |                      |
|-----|----------------------|
| 7W  | T8N-2FAL1-007W-60K-H |
| 9W  | T8N-2FAL1-009W-60K-H |
| 10W | T8N-2FAL1-010W-60K-H |



# T8 3呎燈管



R45674



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞



IP22


鋁合金+塑料



鋁合金+玻璃



|             |                   |       |       |
|-------------|-------------------|-------|-------|
| 材質          | 鋁合金+塑料/鋁合金+玻璃     |       |       |
| 演色性 (CRI)   | >80               |       |       |
| 功率因數        | >0.9              |       |       |
| 色溫 (CCT)    | 3000K             | 4000K | 6500K |
| 功率 (W)      | 10W               | 13W   | 15W   |
| 發光效率        | 100 lm/w-180 lm/w |       |       |
| 光通量/流明 (lm) | 1000 lm-1500 lm   |       |       |
| 光源壽命        | 50000hr           |       |       |
| 輸入電壓        | 100-240 Vac       |       |       |



## 產品型號

|     |                      |
|-----|----------------------|
| 10W | T8N-3FAL1-010W-60K-H |
| 13W | T8N-3FAL1-013W-60K-H |
| 15W | T8N-3FAL1-015W-60K-H |

# T8 4呎燈管



R45674



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞



IP22

鋁合金+塑料




鋁合金+玻璃



|             |                   |     |       |     |       |     |
|-------------|-------------------|-----|-------|-----|-------|-----|
| 材質          | 鋁合金+塑料/鋁合金+玻璃     |     |       |     |       |     |
| 演色性 (CRI)   | >80               |     |       |     |       |     |
| 功率因數        | >0.9              |     |       |     |       |     |
| 色溫 (CCT)    | 3000K             |     | 4000K |     | 6500K |     |
| 功率 (W)      | 9W                | 10W | 12W   | 13W | 18W   | 20W |
| 發光效率        | 100 lm/w-180 lm/w |     |       |     |       |     |
| 光通量/流明 (lm) | 900 lm-2000 lm    |     |       |     |       |     |
| 光源壽命        | 50000hr           |     |       |     |       |     |
| 輸入電壓        | 100-240 Vac       |     |       |     |       |     |

## 產品型號

|     |                      |
|-----|----------------------|
| 9W  | T8N-4FAL1-009W-60K-H |
| 10W | T8N-4FAL1-010W-60K-H |
| 12W | T8N-4FAL1-012W-60K-H |
| 13W | T8N-4FAL1-013W-60K-H |
| 18W | T8N-4FAL1-018W-60K-H |
| 20W | T8N-4FAL1-020W-60K-H |



# T5 直上型玻璃燈管



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞





IP22

|             |                |       |       |
|-------------|----------------|-------|-------|
| 材質          | 鋁合金+玻璃         |       |       |
| 演色性 (CRI)   | >80            |       |       |
| 功率因數        | >0.9           |       |       |
| 色溫 (CCT)    | 3000K          | 4000K | 6500K |
| 功率 (W)      | 9W             |       | 18W   |
| 發光效率        | >100 lm/w      |       |       |
| 光通量/流明 (lm) | 900 lm-1800 lm |       |       |
| 光源壽命        | 30000hr        |       |       |
| 輸入電壓        | 100-240 Vac    |       |       |

## 產品型號

|    |     |                |
|----|-----|----------------|
| 2呎 | 9W  | T5J-2FGL1-009W |
| 4呎 | 18W | T5J-4FGL1-018W |



# T8 微波感應燈管



歐盟安全標準



無藍光危害



無頻閃



不含鉛汞





IP22

|             |                |       |       |
|-------------|----------------|-------|-------|
| 材質          | 鋁合金+塑料         |       |       |
| 演色性 (CRI)   | >80            |       |       |
| 功率因數        | >0.9           |       |       |
| 色溫 (CCT)    | 3000K          | 4000K | 6500K |
| 功率 (W)      | 9W             | 18W   |       |
| 發光效率        | >100 lm/w      |       |       |
| 光通量/流明 (lm) | 900 lm-1800 lm |       |       |
| 光源壽命        | 30000hr        |       |       |
| 輸入電壓        | 100-240 Vac    |       |       |

## 產品型號

|    |     |                 |
|----|-----|-----------------|
| 2呎 | 9W  | T8Y- 2FAL1-009W |
| 4呎 | 18W | T8Y- 4FAL1-018W |



# T5 層板燈



|             |                   |       |       |     |
|-------------|-------------------|-------|-------|-----|
| 材質          | 鋁合金+塑料/全塑料        |       |       |     |
| 演色性 (CRI)   | >80               |       |       |     |
| 功率因數        | >0.9              |       |       |     |
| 色溫 (CCT)    | 3000K             | 4000K | 6500K |     |
| 功率 (W)      | 5W                | 10W   | 15W   | 20W |
| 發光效率        | 100 lm/w-180 lm/w |       |       |     |
| 光通量/流明 (lm) | 500 lm-2000 lm    |       |       |     |
| 光源壽命        | 50000hr           |       |       |     |
| 輸入電壓        | 100-240 Vac       |       |       |     |

## 產品型號

|    |     |                      |
|----|-----|----------------------|
| 1呎 | 5W  | T5N-1FAL1-005W-60K-H |
| 2呎 | 10W | T5N-2FAL1-010W-60K-H |
| 3呎 | 15W | T5N-3FAL1-015W-60K-H |
| 4呎 | 20W | T5N-4FAL1-020W-60K-H |

