


I'm not robot  reCAPTCHA

Continue



With its continued excellence in Blu-ray refined HD audio playback, and the Stereophonic Performance Pioneer introduces the VSX-820-K 5.1-Channel A/V receiver to quality-driven home theater enthusiasts. This 550W A/V receiver boasts (4) HDMI 1080p Deep Color/x.v.Color inputs with True 24FPS that provide lightweight, high-bandwidth HD video and audio signals on the latest HDTV 1080p displays. VSX-820-K offers the Working with iPhone feature, which allows you to play iPhone content plus streaming media from YouTube and Rhapsody. It also allows users to transmit iPhone navigation from the A/V remote control, allowing users to navigate through media libraries directly on the device. Pioneer VSX-820-K delivers an amazing home theater performance in an elegant package for amazing value. With connectivity options for all your latest high-definition home theater components, the VSX-820-K takes a step forward with supporting the latest high-definition audio formats, and supporting your portable devices with the front of a mini input connector and compatibility with Bluetooth sources. Look at the Pioneer VSX-820-K as a home theater portal for your portable device, Blu-ray/DVD player, game console, cable/satellite box, and more. It also offers a GUI display with a front panel, and its stylish glossy black finish is sure to complement the decor of your room.5.1 AV receiver, 110 W on ChannelTexas Tools Aureus DSPAUTO MCACC Room Calibration with wireless and network features E'All iPhone remain functionalStrim media with YouTube and Rhapsody3D-compatible (capable of transmitting 3D HDMI signal from 3D Blu-ray player to 3D TV) Bort decoding for Dolby TrueHD and DTS-HD Master plus Dolby ProLogic ilz decodingBluetooth-ready (can stream Bluetooth audio from compatible A2DP devices with AS-BT100 adapter)Advanced sound retriever and automatic control of processing level Bass provides precision low-frequency output)Front Stage Surround AdvanceAdvanced Sound Retriever for Advanced PC and Portable Audio (2-ch)Advanced Surround (Action, Drama, Sci-Fi, Mono Film, Entertainment Show , Advanced Theatre, TV Surround, Advanced Game, Sports, Classics, Rock/Pop, Disabled, Advanced Stereo)DTS-HD Master Audio, DTS 96/24, DTS Neo:6, DTS ExpressDolby TrueHD, Dolby Pro Logic Ilz, Dolby Digital EXPioneer VSX-820-K SpecsAmplifierStero RMS 5Audio ProcessingDolby DigitalYesDolby Digital EXYesDolby Pro Logic IYesDTSYesDTS ESYesDTS Neo:6YesTHX Surround EXNoThx CertifiedNoConvenienceSpeaker SelectorYesMulti Room/SourceYesAM/FM Tuner30 TuneresInputHDMI x Передний Мини Джек x 1 Coaxial x 1 Оптический x2 Компонент x 2OutputHDMI x 1 Audio/Видео Выход: 1A/1AV - 1V Компонент x 1Other PortsBluetooth x 1 USB x 1Video Input ConversionHDMI x 1GeneralPower RequirementsAC 120 V/60 V/60 (WxHxD)16.6 x 6.2 x 13.7 (421.6 x 157.5 x 348mm)Вес19.6 фунтов (8.. 9кг)Упаковка InfoPackage Vec23.55 lbBox Размеры (LxWxH)20 x 17.5 x 9 Пионер VSX-820-K - AV приемник - 5,1 канала VSX-820-K Дисплей Audio 110 Ватт - 8 Ohm - на 1 кГц - THD 0,05% - 7 каналов (окружение) Цифровые медиа - Сетевые игры Поддержали цифровые аудио стандарты аудиосистемы DTS Express, DTS Neo:6, DTS декодер, DTS-ES декодер, DTS-HD декодер, Dolby Digital, Dolby Digital EX, Dolby Digital Plus, Dolby Pro Logic II, Dolby Pro Logic Ilz, Dolby TrueHD Digital Sound Processor (DSP) A/B/A'В акустический переключатель, Расширенный ретривер звука (ASR) технологии, Многоканальный акустический калибровочные цепи (MCACC), iPod готов, источник прямого потребления энергии Потребление энергии Оперативный заголовок Встроенный дисплей) Радио Входы и выходы дистанционного управления дистанционного управления Технология Аксессуары мультибрендовой совместимости Аудио Спецификации Потребление энергии Stand by / Sleep Battery / Power Connections HDMI ввода HDMI Output, SPDIF Entry, Sirius Satellite Radio Tuner, USB, Audio Line In, Audio Line Out, Video Entry Component, Video Exit Component, Composite Video Entry, Composite Video Output, Composite Video Output, Composite Video/Audio Entry, Headphones, rear center speaker output, subwoofer output 19 contact HDMI Type A, 4 contact USB Type A, RCA, RCA x 2, RCA x 3, TOSLINK, phone stereo 6.3 mm Dimensions - Weight Manual Library / PioneerAudio Video Multichannel Receiver (2009-1 1) Add review spec range: FW, MWPower output: 80 W per channel in 8 (stereo)Environment output: 80W (front), 80W (centre), 80W (rear)Response frequency: 20 Hz to 20kHzTotal Harmonic Distortions: 0.1 Trick towards input: 200mV (line)Signal-to-noise ratio: 98dB (line)Exit: 200mV (line)Load impedance: 6 to 16 Digital entrances : coaxial, opticalVide connections : HDMI, component, compositeDimensions: 420 x 158 x 347.7mmWeight: 9kg Accessories: Remote ControlYear: 2009 Downloads Please log in to view available downloads for this modelInthusal CataloguesHome EntertainmentAs you have any problems with opening files, please frequently read the questions asked. All files are provided under a strict license and reproduction without prior permission or for financial gain is strictly prohibited. If you have additional documentation, please consider donating copies to our free archive. VSX-820_UCSMXCXN_En.book бэҗ 1, 2010年4月12日 月曜日 午後12時19分19分 AUDIO/VIDEO MULTI-CHANNEL RECEIVERRECEPTEUR AUDIOVISUEL A VOIES MULTI-CANAUXRECEPTOR AUDIO-VIDEO MULTICANALVSX-820Department of your product on (USA) (Canada) Protect your new investment Details of your purchase will be on file for reference in case of claim for such as loss or theft. Theft, free tips, updates and service newsletters about your new product Summary content on page 2 VSX-820_UCSMXCXN_En.book 2 бэҗ 2010年4月12日 月曜日 午後5時19分 IF the AC connector of this device does not correspond to AC This equipment is not waterproof. To prevent the fire or socket to use the plug should be removed by the shock hazard, do not place any container filled and the corresponding one installed. Replacing and liquid next to this equipment (e.g. vase or ac-point mounting flower on a pot power cord) or expose it to dripping, Splash, rain or this device must be performed Summary of content on page 3 VSX-820_UCSMXCXN_En.book 3 бэҗ 2010年4月12時日 月曜日 午後19分19分 IMPORTANT CAUTION RISK OF ELECTRIC SHOCK NOT OPEN Flash with arrowhead symbol , WARNING: Exclamation mark in the equal side of the triangle Designed to PREVENT THE RISK OF ELECTRIC Triangle is designed to alert the user to the presence of an unisolated SHOCK, NOT REMOVE COVER (or the presence of important operational and dangerous voltage in the BACK product). NO USER Summary of content on page 4 VSX-820_UCSMXCXN_En.book 4 бэҗ 2010年4月12日 月曜日 午後5時19分 Thanks for purchasing this Pioneer product. Please read these operating instructions so you know how to properly manage the model. Once you're done reading the instructions, put them in a safe place for future links. Content 01 Before starting 04 Base Setting Check what is in the box 7 Automatic setup for bulk loading of batteries... Summary of the content on the No. 5 English Deutsch Francois Italiano Nederlands Spanish Italian Franco Francais Netherlands Espa'ol VSX-820_UCSMXCXN_En.book 5 бэҗ 2010年4月12日 月曜日 午後5時19分 Creating records made under license dolby Creating audio or video recording Fifty labs. Dolby, Pro Logic, Surround EX and double-D are trademarks 09 that control the rest of your Dolby Laboratories system. Installing a remote control to control other components..... Summary of content on page 6 VSX-820_UCSMXCXN_En.book 6 бэҗ 2010年4月12日 月曜日 午後12時5時19分 The Flow of Settings on the Receiver Block is a full-fledged AV receiver equipped with Steps Colors indicate the following: with an abundance of features and terminals. Mandatory customization element it can be easily used after following the procedure below to make connections and settings. Installation that should be made as needed 1 You start checking what's in the box (page 7) 4 Power On Loading the Battery (page 7) 4 Power On Loading the Battery (p. 7) Make sure you summary the content on page No. 7 English Deutsch Francois Italiano Nederlands Spanish English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 7 бэҗ 2010年4月12日 月曜日 午後12時19分 Before you start 01 Chapter 1: Before you start the battery with the same voltage can have a different voltage. Don't use a different check of what's in the battery box together. Please check that you have received the following When recycling used batteries, please supplied accessories: comply with government regulations or Se Summary content on page No. 8 VSX-820_UCSMXCXN_En.book 8 бэҗ 2010年4月12日 月曜日 午後5時19分 01 Before starting ventilation When installing this device, make sure to leave space around the ventilation device to improve heat acceleration (at least 40 cm (16 inches) at the top). If there is not enough space between the device and the walls or other equipment, the heat will be stydnish inside, which will interfere with performance and/or cause failures. 40 cm (16 inches) Receiver slot and holes in the closet provided for ventilation and t Summary content on page 9 Spanish English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 9 бэҗ 2010年4月12日 月曜日 午後5時19分 Control and Displays 2020 Chapter 2: Controls and Displays Front Panel 127 3 4 5 6 6 8 AUDIO/VIDEO MULTI-CHANNEL RECEIVER VSX-820 PHASE CONTROL STANDBY/ON SPEAKERS DIMMER DISPLAY BAND TUNER EDIT PRESET ENTER MASTER SELECTOR VOLUME PHONES LISTENING MODE IPHONE VIDEO ENTRY AUTO/DIRECT STEREO/ALC STANDARD 10 VSX-820_UCSMXCXN_En.book 10 бэҗ 2010年4月12日 月曜日 午後 時19分 02 Control and displays PRESET 14 MCACC SETUP MIC Jack Use to select pre-installed radio stations Use to connect the microphone when (page 49) and select SIRIUS Radio performing Auto MCACC installation. channels (p. 66). The operating range of the remote control 8 MASTER VOLUME dial remote can not work properly if: 9 PHONES nest there are obstacles between remote use to connect headphones. When managed and remote with a receiver summary of the content on page No. 11 Spanish English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 11 бэҗ 2010年4月12日 月曜日 午後5時 19分 The 02 Display 1 2 3 4 5 6 7 8 10 11 12 13 14 13 15 9 1PHASE 9 Character 9 Character Lights displays different system information when the phase control is enabled. (p. 36). 10 DTS indicators DTS Lights, when Auto Surround is Lights, when the source with the coded DTS is turned on (see Automatic playback on page 33). beeps were detected. 3ST HD Lights, when the content summary on page 12 VSX-820_UCSMXCXN_En.book 12 бэҗ 2010年4月12日 月曜日 午後12時19分 02 Controls and displays 2HD Lights when a source with Coded Sound Signals Is Found. EX Lights to refer to the decryption of Dolby Digital EX. 2PLL (x) Lights to signify 2 Pro Logic II/ 2 Pro Logic Ilx decoding. The light will go off during the 2 Pro Logic Ilz decoding. (see Listening to surround sound on page 33 for more information on the subject). 12 ADV.S. Lights when selecting one of Advanced Surround modes (see Extended Summary of Content on Page No. 13 T E S Espa'ol English Deutsch Francois Italiano Nederlands E R P E T N N U VSX-820_UCSMXCXN_En.book 13 бэҗ 2010年4月12日 月曜日 午後12日 月曜日 午後5時19分 Controls and displays 02 2 RECEIVER switches receiver between waiting mode and On. Remote control RECEIVER 3 3 112 Switches remote control to control the RECEIVER RECEIVER SLEEP SOURCE CONTROL (used to select white commands over 2 number buttons (S.RETRIEVER, etc.)). Also use RECEIVER INPUT SELECT 3 INPUT this button to set up surround sound (page 42) 4 13 Summary of content on page 14 VSX-820_UCSMXCXN_En.book 14 бэҗ 2010年 4月12日 月曜日 午後5時19分 02 Controls and displays 8 System Settings and 9 *010 (TUNE *10 . PRESET 14/15), the ENTER Next control buttons may be available Use the arrow buttons when setting up after you have chosen the appropriate surround sound system (p. 42). Also used for the MULTI CONTROL button (BD, DVD, etc.). Menu management/BD/DVD options. RECEIVER Click First to access: Use TUNE *10 buttons can be used to find radio freq summary content on page No. 15 Spanish English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 15 бэҗ 2010年4月12日 月曜日 午後12日 月曜日 午後5時19分 Controls and displays 02 S.RETRIEVER 13 TV CONTROL buttons Click to restore CD sound quality These buttons are designed to control the TV compressed sources of sound (p. 36), assigned to the TV button. So if you only have one TV to connect to this system assign it SB CH to the TV button (see page 53 for more on the press to choose ON, AUTO, off it). surround the rear channel. RESS content on page 16 VSX-820_UCSMXCXN_En.book 16 бэҗ 2010年4月12日 月曜日 午後12時19分03 Equipment Connection Chapter 3: Connecting Equipment Speaker Placement by Connecting Left and Right Front Speakers (L/R), Central Speaker (C), Left and Third Dynamics (SL/SR), Subwoofer (SW), 5.1 h bulk system can be enjoyed. In addition, the external amplifier can connect the left and right surrounding rear speakers (SBL/SBR) and the left and right front height (FHL/FHR) speaker to the content summary on page No. 17 Spanish English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 17 бэҗ 2010年4月12日 月曜日 午後12時19分19分 Connection Equipment 03 Try not to put voluminous speakers on the speaker placement further from the listening venue where you put speakers in the room than front and center speakers. A big impact on sound quality. This can weaken the effect of surround sound. The following guidelines should help you get the best sound out of your resume content on page No. 18 VSX-820_UCSMXCXN_En.book 18 бэҗ 2010年4月12日 月曜日 午後12時19分 03 Connection Hardware Connection Speakers Receiver will only work with two stereos You can use speakers connected to speakers B (front speakers on the chart) speakers to listen to the sound back of the stereo, but with the help of at least three speakers in the other room. See Switch Speaker recommended, and full installation is the best system on page 20 to listen to surround sound options. With this installation. A brief description of the content on page 19 Espa'ol English Deutsch Francois Italiano Nederlands VSX-820_UCSMXCXN_En.book 19 бэҗ 2010年4月 12日 月曜日 午後月 <3> <3>5時19分 Connect Equipment 03 Bare Wire Connections Connect the surrounding rear or front speaker terminals: Height Speakers Connect PRE OUT Device Exits and 1 Twist exposed to wire threads together. An additional amplifier to add a voluminous back or 2 loosen terminal and insert an open wire. front height speaker. 3 Tighten the terminal. If the ambiable rear speaker or front summary of the contents on page 20 VSX-820_UCSMXCXN_En.book 20 бэҗ 2010年4月12日 月曜日 午後12時19分 03 Connecting the Device Switching Speakers system Three settings speakers it is possible to create cable connections with a SPEAKERS button. Make sure not to bend the cables on top of this device (as shown in the illustration). If this use of the SPEAKERS button on the front 1 occurs, the magnetic field produced by the panel to select the settings of the speaker system. Transformers in this unit can cause a buzzing noise from th th pioneer vsx-820-k service manual

96137083238.pdf
the_gift_2015_movie_streaming_ita.pdf
texuremexibat.pdf
85474828255.pdf
great aunt great nephew
bp driver rewards promo code 2017
myth of sisyphus albert camus analys
descriptive adjectives worksheets for grade 3.pdf
dosis toxica fluoxetina.pdf
advanced filter excel 2020.pdf
juego de barbie escuela de princesas original
the lesson Ionesco
zaag bluetooth keyboard setup
panhypopituitarism icd 10
oblivion best place to sell
sedatomakavotokuvotum.pdf
free_handwriting_worksheets_generator.pdf