

S210

Simple PINPAD



Individual Merchant



Hospitality



Food & Beverage



CLASSIC



Powered by
RunthOS



PCI PTS
6.x SRED



320 x 240
Color Screen



















Secure
Platform



Optional Front
0.3MP Camera

SPECIFICATIONS

	Operating System	RunthOS
	Processor	32-Bit Secure Processor, 192MHz
	Memory	CPU Built-In: 1MB SRAM + 4MB Flash, External: 8MB Flash
	Display	2.4", 320 x 240 Color Screen
	Barcode	Front 0.3MP Camera for Barcode (opt)
	Key	16 keys: 0~9, Clear, Enter, Cancel, F1, F2, F3
	Card Readers	ICCR (opt) Contactless
	SAM	2 x Micro SAM (opt)
	Communication	USB Type-C Serial
	Peripheral Ports	1 x USB Type-C 1 x 6 PIN Serial
	Multimedia	Audio Speaker, up to 85DB
	Physical	L x W x H (mm) : 146 x 76.5 x 39.5mm
	Power Supply	5V1A DC input, 5~12V Input on Serial (opt)
	Safety-Certification	CE UKCA RoHS
	Certifications	AMEX DPAS JCB PAYPASS PAYWAVE qUICSS EMV L1 EMV CL L1
	Environmental	5% ~ 96% Relative Humidity, Non-condensing -10 ~ 50°C Operating Temperature -20°C ~ 70°C Storage Temperature

