



## **Landini 7000-9000 IS-AR**



The 7000-9000 Series equal-wheel tractors are available in two versions: IS with front wheel steering and AR with articulated steering. Both versions come standard with reversible driving position and are available in either ROPS or cab configuration.



# Landini 7000-9000 IS-AR

7000-9000 Series, powerful and reversible for maximum flexibility

## DIMENSIONS AND WEIGHTS

	7075 IS-AR	7085 IS-AR	90105 IS-AR	90115 IS-AR
Wheelbase mm	1495	1495	1495	1495
Min/Max Length mm	3737	3737	3737	3737
Total Weight Kg	2285 (IS) - 2205 (AR)	2285 (IS) - 2205 (AR)	2285 (IS) - 2205 (AR)	2285 (IS) - 2205 (AR)



## POWER

70 76 95 102

## ENGINE

2,9 / 4

## TRANSMISSION

Synchro Shuttle

The 7000-9000 tractors sport a fresh new look with a restyled hood and an updated fuel tank which now boasts a capacity of 58 litres. The driver's station has also been redesigned with an all-new digital instrumentation cluster.

# Landini®



## Landini FEATURES

### ENGINE

The two models in the range, the 90105 and 90115, are powered by new Deutz TCD L4 engines meeting the Stage 3B / Tier4i emission regulations. Equipped with four valves per cylinder, turbocharger and aftercooler, these new 2.9L, 4-cylinder engines deliver 95 and 102 hp.

### TRANSMISSION

The 7000-9000 Series offers standard a 16/16 transmission with synchro shuttle and creeper. max. speed 40 km/h.

### DRIVING POSITION

Both versions come standard with reversible driving position and are available in either ROPS or cab configuration. The driver's station has also been redesigned with an all-new digital instrumentation cluster.