

B8900

Extension Base for A8900



SPECIFICATIONS

Model Name		B8900-BC	B8900-BM	B8900-BE
Pro	duct Type	Charging Base	Multifunctional Base	Wireless Base
Pro	cessor	N/A	N/A	Xtensa® 32 bit LX7
□ Me	mory	N/A	N/A	512K SRAM + 4MB Flash
☐ RS2	232	N/A	1 Serial Port (RJ45)	1 Serial Port (RJ45)
C LAI	N	N/A	1 Ethernet Port (RJ45, 10/100Mbps)	1 Ethernet Port (RJ45, 10/100Mbps)
- USI	В	1 Type-C Port (charge only)	1 Type-C Port (charge only) 1 Type-C Port (HOST) 1 Type-A Port (HOST)	1 Type-C Port (charge only) 1 Type-C Port (device) 1 Type-A Port (HOST)
	-Fi	N/A	N/A	Wi-Fi® 2.4GHz IEEE 802.11b/g/n
₿ Blu	etooth	N/A	N/A	Bluetooth® 4.2
¬∰ Pov	wer Supply	5V/2A (Type-C)	5V/2A (Type-C)	5V/2A (Type-C)
G Env	vironment	Operating Temperature: 0°C ~ 50°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 5% ~ 96% (non-condensing)	Operating Temperature: 0°C ~ 50°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 5% ~ 96% (non-condensing)	Operating Temperature: 0°C ~ 50°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 5% ~ 96% (non-condensing)
D Phy	ysical	171 x 82 x 25 mm	171 x 82 x 25 mm	171 x 82 x 25 mm





