













# B910S\_RTX

## Extension Base for A910S & A930RTX

### SPECIFICATIONS

Model Name	B910S_RTX-BC	B910S_RTX-BE
 <b>Product Type</b>	A910S & A930RTX Charging Base	A910S & A930RTX Wireless Communication Base
 <b>Processor</b>	N/A	ARM Cortex®-A7
 <b>Memory</b>	N/A	128MB NAND Flash + 256MB DDR SDRAM
 <b>RS232</b>	N/A	1 Serial Port (RJ45, Default)
 <b>LAN</b>	N/A	1 Ethernet Port (RJ45, 100M)
 <b>USB</b>	1 Type-C port(charge only )	1 Type-C Port (charge only) 1 Type-C Port (device) 1 Type-A Port (HOST)
 <b>Wi-Fi</b>	N/A	Wi-Fi® 2.4GHz
 <b>Indicator</b>	N/A	5 Communication indicators
 <b>Bluetooth</b>	N/A	<b>Bluetooth®4.2</b>
 <b>Power Supply</b>	5V/2A (Type-C)	5V/2A (Type-C)
 <b>Environment</b>	Operating Temperature: 0°C ~ 45°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 5% ~ 95% (non-condensing)	Operating Temperature: 0°C ~ 45°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 5% ~ 95% (non-condensing)
 <b>Physical</b>	162 x 83 x 40mm	162 x 83 x 40mm

