



## **SPECIFICATIONS**

00	Operating System	Monitor
₿	Processor	32-Bit ARM CPU
	Memory	8MB FLASH + 1MB SRAM
	Card Readers	Chip & PIN   Contactless   Magnetic Stripe (Optional)
Ū	Display	1.77'' TFT 128 x 160 Pixels   Electronic Signature Capture (Optional)
((†))	Comms Configurations	Bluetooth 4.2
Ī	Battery	750mAh   3.7V
Ę	Keys / Buttons	13 Keys: 0~9   Enter   Clear   Cancel Optional: Back-lighting
ふシ	Audio	1 Buzzer
	Ports	1 Type-C   4 PIN POGO PIN (Optional)
[0]	Physical	99.3 x 61 x 12.7mm, 100g
Ğ	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature, Non-Charging -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
$\overline{\heartsuit}$	Certifications	PCI PTS 5.x SRED   EMV L1 & CL L1   Mastercard Contactless   Visa PayWave   American Expresspay   Discover D-PAS   UPI qUICS   TQM   J/Speedy JCB   CE   RoHs   BIS   WPC   Ru-pay   Anatel   ABECS



This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX and the PAX logo are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Limited is under license. Other trademarks and trade names are those of their respective owners. © 2022 PAX Technology Limited. All rights reserved.

