## **IR510 Nano Series**

## Handheld Thermal Imager



Night Hunting Search & Rescue Law Enforcement Night Patrol Outdoor Sports Personal Security

It's time to upgrade your IR510 series. Connected to mobile APP via Wi-Fi, the new IR510 series can be remote controlled to display synchronously, take photos and videos. Compared with the last version, it provides superior image, longer detection range and advanced algorithm, helping to pick up the targets.



- Wi-Fi for remote control,to display synchronously, take photos
   and videos
- o Imaging better, detect further, highlight the target easier
- o Easy operation with only three buttons Silent and lightproof design to prevent exposure
- o Built-in battery life up to 5h, external power supply available
- o Illuminator or laser pointer or neither
- o IP66 protection and 1m drop test passed to suit the wild

Model	IR510 N1	IR510 N1 WIFI	IR510 N2	IR510 N2 WIFI
tector				
Detector Type	400×300 @17μm, 8μm∼14μm, NETD≤50mk			
ns				
Focus	19mm		25mm	
Focusing	Focus-free		Manual	
FOV	19.0	°×14.5°	14.6	°×11.1°
play		700 540 . Calar	ful 0 2// COC	
Screen	720×540, Colorful 0.2"LCOS			
Eyepiece Magnification	Monocular, diopter adjustable±4  0.9—3.6X  1.2—4.8X			
ige	0.9-	3.6A	1.2	<del></del>
Frame		50H	7	
Digital Zoom	×2, ×4			
Color Palette	highlight, Black hot, white hot, red hot 1, red hot 2, red hot 3			
etions		gg.n, 2.00. not, mino not, i		
hotspot tracking	<b>√</b>	<b>√</b>	V	<b>√</b>
Wi-Fi	×	V	×	√
Other	Freeze,Indicate Box, Illuminator or laser pointer or neither			
/er				
Battery	Internal Li-ion battery,3.7V,3200mAh			
Working Time	≥5h			
Adapter	Standard USB power adapter, max 10W			
rface				
USB	Charging			
Video Output		MCX Connecto	r,PAL/NTSC	
vironment Characteristics				
Working Temperature	-10°C~50°C			
Storage Temperature	-30°C~60°C			
Encapsulation	IP66 1m drop N/A			
Drop	1m	n drop		N/A
ysical Parameter Weight	2	F0 a		275.0
Size	350g 160mm×67mm×62mm		375g 168mm×67mm×62mm	
ckage	10011111120	7111111×02111111	100111111×0	7/11111×02/11111
Standard accessories	Power adapter, USB cable, Video cable, Lens cap, Wrist strap, Shoulder strap, Soft drawstring bag, User manual			
Optional accessories	N/A 40mm lens(FOV:9.3°×7.0°)		FOV:9.3°×7.0°)	
ection Range Recognition Range	IR510 N1/N1 WIFI		IR510 N2/N2 WIFI	
1.8m×0.5m	500		700	
	1300			
2.3m×2.3m	500	1300	700	1700