IR517 Series

Multi-functional Handheld Thermal Imager



Night Hunting Search & Rescue Law Enforcement Night Patrol Outdoor Sports Personal Security

IR517 handheld thermal monocular is the latest multi-functional portable thermal imager. The lenses of IR517 series are interchangeable for different detection missions. The built-in Wi-Fi module can connect the IR517 to a mobile device with an APPÿand make various applications possible. This highly compact thermal imaging device is small and light weight so that you can easily stuff in your package.



- 19mm/35mm/65mm/80mm lenses for different detection missions as well as different budget.
- Built-in Wi-Fi module enables connection between IR517 and mobile devices for image & video transfer, program upgrading etc.
- o through the LCOS viewfinder display.
- Built-in large capacity SD card, user can record real-time video or take photos whenever they want.
- IR517 can record on-site voice annotation and GPS information together with the thermal images.

Model	IR517G	IR517G I	Pro	
etector	113170	113176		
Resolution	400×300@25μm			
Spectral		8 ~ 14um		
ens				
Focus	35mm standard lens (19mm,65mm,80mm external lens)			
Focusing		Fixed focus , manual focus		
FOV	19mm:19.7°×15° / 35	19mm:19.7°×15° / 35mm:11.0°×8.3° / 65mm:6.0°×4.5° / 80mm:4.9°×3.6°		
isplay				
Mini display	Color	r mini display, 1280×960 resolution		
View Finder	Monocula	Monocular display, adjustable diopter (-5~+5)		
nage				
Frame Rte		PAL/25Hz, NTSC/30Hz		
Digital Zoom		2X、4X		
Palette		Black hot, white hot, red hot		
Image Storage	Photo format JPG, Video MP4			
unctions				
Photo	√ ,	√		
Video	√	√		
Hotspot tracking	\checkmark	√ =		
Wi-Fi/APP	No	Wi-Fi share photo and video, also Android		
GPS	N/A	YES	^)	
ower				
Battery		Li-on		
Adapter		5VDC		
Working Time	With IR mode, Co	With IR mode, Continuous working hours after a single charge ≥3h		
nterface				
USB	Char	Charge , output data from storage mode		
Analog Video	Vio	Video streaming with MCX interface		
Storage		Built-in 16G/32G(optional)		
Microphone	No	Yes		
<u> </u>				
nvironment Characteristics				
nvironment Characteristics Working Temperature		-10°C ~ 40°C		
nvironment Characteristics Working Temperature Storage Temperature		-30°C ~ 70°C		
nvironment Characteristics Working Temperature Storage Temperature Humidity		-30°C ~ 70°C 10% ~ 95%		
nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation		-30°C ~ 70°C 10% ~ 95% IP66		
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test		-30°C ~ 70°C 10% ~ 95%		
Note that the control of the control		-30°C ~ 70°C 10% ~ 95% IP66 1m drop		
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight		-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g		
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight Size		-30°C ~ 70°C 10% ~ 95% IP66 1m drop	n	
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight	35mmle	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr		
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight Size	35mmler Power adapter, U	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr		
Notice the content of	35mmler Power adapter,U Soft d	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr USB cable,Lens cap,Wrist strap,Should drawstring bag,User manual,Warranty	der strap,	
Nvironment Characteristics Working Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight Size ackage	35mmler Power adapter,U Soft d	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr	der strap,	
Norking Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight Size ackage Standard Optional	Power adapter,U Soft d Extender	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr USB cable,Lens cap,Wrist strap,Should drawstring bag,User manual,Warranty and lens(19mm、35mm、65mm、80mm	der strap,	
Notice the control of	35mmler Power adapter, USoft d Extender	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr USB cable,Lens cap,Wrist strap,Should drawstring bag,User manual,Warranty ed lens(19mm、35mm、65mm、80mm	der strap, n) 80mm	
Notice the control of	Power adapter,U Soft d Extender	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr USB cable,Lens cap,Wrist strap,Should drawstring bag,User manual,Warranty and lens(19mm、35mm、65mm、80mm	der strap,	
Norking Temperature Storage Temperature Humidity Encapsulation Drop Test hysical Characteristics Weight Size ackage Standard Optional Recognition Range	Power adapter, U Soft d Extender 19mm 35mm	-30°C ~ 70°C 10% ~ 95% IP66 1m drop 35mm lens(Standard) : 787g en(Standard) : 220.2mm×80mm×71mr USB cable,Lens cap,Wrist strap,Should drawstring bag,User manual,Warranty ed lens(19mm、35mm、65mm、80mm 65mm	der strap, 1) 80mm	