



JETWAVE®

HIGH PRESSURE CLEANERS

Distributed by:

CADET™ 200-15 3000 psi • 15 l/pm



Electric Driven



Three Phase



Cold Water



Continuous Usage

FIELDS OF APPLICATION

- Primary Industry
- Factory Washdown
- Cleaning Contractors
- Construction and Mining
- Schools and Universities
- Government and Councils
- Aviation Ground Support
- Transportation and Logistics

The Jetwave® Cadet™ 200-15 is the perfect electric pressure washer for heavy duty frequent usage and applications. Engineered and assembled with quality Italian and global components.



SHOWN WITH OPTIONAL BYPASS TANK

HERO INNOVATIONS



Protection

Formed galvanised steel cover to safeguard components and for work site safety.



Durable

Foam filled 14" puncture proof tyres.

STANDOUT FEATURES



Quality Assured IP66 electrical control box for increased protection against dust and water ingress.



Professional Italian triplex delivers performance and longer life.



Low speed professional pump for increased reliability and longer maintenance intervals.



Maintenance free low speed, electric motor, air cooled and protected with soft coupling and thermal cut-out.



Brass washable inlet water filter.



Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass and over pressurisation.



Quality pressure gauge.



Zero brass line pressure loader valve for user safety and flexibility.



Integrated accessory storage for gun and lance.



Professional line accessories.



Jetwave Group
 72-74 Richmond Road
 Keswick | Adelaide
 South Australia | 5035 | AU
 +61 8 8371 3599
 sales@jetwave.com.au
 jetwave.com.au

Robust - Galvanised steel to withstand tough environmental conditions.

Performance - Dependable Italian industrial triplex pump.

Ergonomics - Trolley frame designed for durability.

Portability - Heavy duty double bearing wheels.



SHOWN WITH OPTIONAL BYPASS TANK

STANDARD EQUIPMENT



Spray Gun - J5000™ heavy duty insulated back part lance and quick coupling.

Lance / Nozzle - Stainless steel dual lance with variable pressure control complete with hardened nozzles.

Hose - 10m of 3/8" double wire braided hose with quick coupling.

OPTIONAL ACCESSORIES

| | | |
|---|-----|----------------------|
| 1. Complete Turbo Head with Lance | p/n | JWA160.045 |
| 2. Additional High Pressure Hose (per metre) | p/n | 52001 |
| 3. High Pressure Swivel | p/n | Included |
| 4. LS12 Foaming Lance with Tank | p/n | JWA221-LS12 |
| 5. JW Pro Foam System | p/n | PROFOAM.045 |
| 6. High Pressure Hose Reel (Capacity 30m or 60m) | p/n | 1060CMPL 1067CMPL |
| 7. Stainless Steel High pressure Hose Reel (Capacity 60m) | p/n | 1067CMPLSS |
| 8. Hammerhead FSC 21" - ABS Plastic | p/n | JWA-FSC21.045 |
| 9. Hammerhead FSC 21" - Stainless Steel | p/n | JWA-FSC22.045 |
| 10. Sandblasting Kit | p/n | JWA164.045 |
| 11. Sludge Kit | p/n | 80005.045 |
| 12. Vulcan V1 Hot Box | p/n | 10199 |

OPTIONAL MACHINE UPGRADES

| | | |
|---|-----|------------|
| 1. Engine Hour Meter 24V * | p/n | RQ48024VAC |
| 2. Emergency Stop* | p/n | JWA218 |
| 3. Stainless Steel Bypass Tank | p/n | 90008-12S |
| 4. Timer Shutdown and Low Voltage Upgrade | p/n | Add: 24TS |
| 5. Forklift Pockets | p/n | 90051FP |
| 6. Low Level Water Cut Out | p/n | JWA217 |

| | | |
|--------------|-----|--------------|
| Product Code | p/n | CW200-15ELCP |
|--------------|-----|--------------|

TECHNICAL DATA

| | | |
|----------------------|-----------|------------|
| Working Pressure | psi / bar | 3000 / 200 |
| Flow Rate | l/pm | 15 |
| Max Water Inlet Temp | °c / °f | 60 / 140 |

INTENDED APPLICATION

| | | |
|--|--------------|-----------------------|
| Usage Frequency | hours / type | 6+ Daily / Continuous |
| Category of Dirt / Debris (AS/NZS 4233.1:2013) | type | Medium |
| | class | A (3000 BAR/LITRES) |

ELECTRICAL FEATURES

| | | |
|----------------|----------------------|----------------------|
| Motor | type | Induction |
| Power Supply | Ph / V / Hz / Amp | 3 / 415 / 50 / 20 |
| Absorbed Power | kW / HP / Pole (rpm) | 5.5 / 7.5 / 4 (1400) |
| Cable Length | metres | 8 |
| Control | type | Bypass System™ (BPS) |

HYDRAULIC FEATURES

| | | |
|-----------------------|------|--|
| Pump / Head / Pistons | type | JW Italian Plunger Triplex / Brass (nickel plated) / Ceramic |
| Motor Pump Coupling | type | Direct Elastic |
| Pump Speed | rpm | 1450 |
| Unloader Valve | type | Independant Zero |
| Orifice / Nozzle | size | 045 |

OTHER FEATURES

| | | |
|---------------------------|-------|-------------------------------|
| Adjustable Pressure | y / n | Y |
| Frame Structure | type | Hot dipped galvanised 4 wheel |
| Onboard Accessory Storage | y / n | Y |
| Detergent Injector | y / n | Y - Downstream low pressure |

DIMENSIONS & WEIGHT

| | | |
|-------------------|--------------|---------------------------|
| Approx Weight | kg | 135 unit / 145 boxed |
| Unit Dimensions | mm | 1100(L) x 770(W) x 720(H) |
| Boxed Dimensions | mm | 1200(L) x 800(W) x 650(H) |
| Number per Pallet | type; pieces | Euro: 1 |

WARRANTY(S)

| | | | |
|----------------|-------|---|--|
| Motor Warranty | years | 1 | |
| Pump Warranty | years | 2 | |

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.