


I'm not robot  reCAPTCHA

**Continue**

## Baby trend sit and stand instructions

Free Shipping Free Shipping on all orders 100% Guarantee of Satisfaction We guarantee customer satisfaction First Class support We stand for our products Secure payments Einige Word-Funktionen k'nen in Google Docs nicht angezeigt werden und werden bei nderungen ent FernDetails anzeigenLetzte Anderungen anzeigen 01.06 Instruction Convenience through Innovation and Thoughtful Design Sit n Stand LX Tandem Walk with Car Seat Snap N Go Attachment System Model #7311 Read all instructions before assembling and using the product. KEEP INSTRUCTIONS FOR FUTURE USE. Page 2 WARNING: Please follow all of these instructions to ensure the safety of your child. Keep these instructions for future links. WARNING: Failure to follow these instructions can result in serious injury or death. Avoid serious injury from falling or sliding. Always use seat belts and make sure the children are properly positioned according to these instructions. WARNING: Never leave children unattended. The maximum weight you can carry in a parent's tray is 3 pounds. Excessive weight can lead to a dangerous-ous unstable state to exist. Wallets, shopping bags, parcels, diaper bags or accessories can change the balance of the stroller and cause dangerous unstable conditions. The maximum weight you can carry in a basket is 5 pounds. Excessive weight can lead to a dangerous unstable state. Be sure that the stroller is completely straight and latch in an open position before allowing the children near the stroller. The rear sn underwaver on the platform is designed for a child who is at least 2 1/2 years old and no more than 40 inches tall. Using a stroller with two (2) children weighing more than 40 pounds each, or children totaling more than 80 pounds, will cause excessive wear and stress on the stroller and can lead to a dangerous unstable state of life. DO NOT use the stroller on stairs or escalators. Never let the stroller be used as a cleaning toy using only soft homemade soap or detergent and warm water on a sponge or clean cloth. Check the stroller regularly for loose screws, worn parts, torn material or sewing. Replacing or repairing parts as needed - Stop using the stroller if it has failed or has been damaged. Please contact our Parts customer service hotline to arrange repairs or get spare parts. Please: If you experience any cult diffi using our product or have a question regarding these instructions, please contact our customer service department at (800) 328-7363 between 8:00 a.m. and 4:30 p.m. Pacifi c Coast Time. Please don't come back. store, since upon its return it cannot be resold, and the materials and energy used to produce it are wasted. To contact us: Baby Trend, Inc. Parts Hotline: 1567 S. Campus Ave. (800) 328-7363 Ontario, CA 91761 8:00 a.m. and 4:30 p.m. Pacifi Pacifi Coast Time 2 WARNING PAGE 3 TO ENSURE THE SAFE OPERATION OF YOUR PRAMION, PLEASE FOLLOW THESE INSTRUCTIONS CAREFULLY. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE ASSEMBLY 1. Remove the stroller from the box. Front wheels, rear wheels, a children's tray and a canopy must be installed before use. 2. To attach the front wheels, unwrap the stroller, as described in the section below. See fi gure 1. Tilt the stroller backwards so that it rests on the handle and rear frame tubes, and the front wheel tubes point upwards. Undo the assembly of the front wheel on the front pipe so that a large hole in the rotary assembly slides along the front tube. Tap each assembly of the front wheel onto the front tube, being careful that the wheel builds locks on the front foot. Pull the assembly of the wheels to make sure it is securely attached to the stroller. Please see fi gure 2. 3. Tilt the stroller forward to rest on the front wheels. To attach the rear wheels, place the rear axle and assembly of the wheels so that the brake levers are facing the back of the stroller. Tap the assembly of the rear wheel on the rear frame of the pipe to be careful that the buttons pressing on the front of each rear tube deal with the hole on the front of each rear wheel shelter. Pull the rear wheel of the assembly to make sure it is securely attached to the stroller. Please see fi gure 3. 4. Make sure the fi wheels are rmlly locked in place. Do not use the stroller if the wheels are not locked in place, but rather contact our customer service department immediately at (800) 328-7363, between the hours of 8:00 a.m. and 4:30 p.m. PCT, for help. 5. Attach the bandwagon to the front legs of the stroller just below the seat. Push down on the footrest until she locks on the rivets protruding from both sides of each leg and snaps on the U-shaped cross of the member frame. Please see fi gure 4. 3 snap on Push Down PARTS ASSEMBLING pic. 1. Rice. 2. Rice. 3. Rice. 4. Baby Tray Legs Rest Canopy Front Wheel Stroller Snap N Go Attachment See page 9 Rear Wheels Parental Tray Page 4 6. To attach the front child tray, press the tray on the front frame of the tube, lining the tray between the protruding rivets and the seat. Click back on the latch until clicks into place. Protruding rivets on the outside of the tube frame should be above the latch tray. Make sure the tray securely latch in place. Please see fi gure 5 and 6. 7. To remove the front of the children's tray, pull outwards on the snaps and pull outwards onto the tray. Please see fi gure 7. Please note that you can attach or remove one end at a time. WARNING: The child's tray is not a restraint: always protect the child with a seat belt. DO NOT lift the stroller at the baby tray. caution when attaching a baby tray to a stroller with a child in a stroller. 8. To attach the front canopy, line up men's fi ttings on the canopy with Fi ttings on the armrest and tap like fi ttings down until clicked into place. Please see fi gure 8. Push forward on the front edge of the canopy to open. Your stroller is now ready to use WARNING: Avoid serious injuries from falling or sliding. Always use a seat belt. FOR SECURE FRONT CHILD 1 Shoulder straps 5-to belt has 2 fastening positions. Choose a loop position that places the shoulder strap level with or below the top of the child's shoulder and feed the shoulder strap under the correct loop. Please see fi gure 8a. 2. Gently place the baby in the stroller and bring a seat belt around the child's waist and over the shoulders. Place the crotch strap and between the baby's legs. Insert the male end of each shoulder/belt into the buckle on the crotch strap. Tighten the harness to be snug around the baby's waist and over the baby's shoulders. Please see fi gure 9. 3. To release, put pressure on both sides of each male clip until the clip is released. This process requires a moderate amount of effort to prevent the accidental release of your child. NOTE: The buckles can be difficult to release when first used. 1. The rear platform and jump seat are designed to accommodate a child who is at least 2 1/2 years old, has good balance and coordination, and is no more than 40 inches tall. Tap the jump seat bench is his most forward position. Spread the child on the platform on the back of the stroller. Make sure the child is facing forward and the hands are holding the frame. Protect the seat belt behind the child and buckle. See fi gure 10. 2. Make sure the baby's feet are completely on the platform at all times. 4 Figure. 5. Rice. 6. Rice. 7. Rice. 8. Rice. 9. Rice. 10. Rivet Shoulder Strap Squeeze Crutch Strap Waist Strap Customized for a cozy fit to SECURE REAR STANDING CHILD FIG. 8a. to SECURE CHILDE Page 5 1. Have the child sit on the jump seat face back. Wrap the seat belt, which is attached to the back of the seat, around the child's waist, and fasten to the crotch strap. See fi gure 11. 2. Adjust the seat belt to be snug around the baby's waist. 3. To release, put pressure on both sides of the male clip until the clip is released. This process requires a moderate amount of effort to prevent the accidental release of your child. 4. Make sure the baby's feet are completely on the platform at all times. ADAPT THE STROLLER TO TRANSPORT CHILDREN'S CAR SEATS 1. Please watch the Car Seat Chart following to identify the proper confi guration snap n go for your child car seat. See the following page that matches your brand of baby car seat to use with your car seat. SEAT POSITIONING 1. The front seat has a two-seater To roll back the seat, turn the bar back and press back. Please see fi gure 12. To place the seat upright, click on the back of the seat while the bar is receding. 2. The vertical position should only be used for a child who is at least 6 months old. Note: The seat does not completely recline. 5 Rice. 11. Figure. 12. TO USE JUMP SEAT PAGE 6 BRAKES WARNING: Always set the brakes when the stroller is not pushed to prevent the stroller from rolling back. Never leave the stroller unattended on the hill or slope as the stroller can slide down the slope. 1. To use the brakes, apply a slight downward pressure to the brake lever located on each rear wheel. The stroller may require a slight movement forward or rear to line the teeth on the brake with each brake cluster of the wheel. See fi gure 13. Make sure that the stroller does not move and that the brakes are applied correctly. To free yourself, gently lift to the brake lever. See fi gure 14. CANOPY 1. To open the canopy, press forward on the front frame of the sheds. To close the canopy, pull the cutting edge to the back of the stroller before folded. Always fold the canopy before folding the frame of the stroller. Please see fi gure 15. 2. The canopy will ratchet forward or backwards to block the sun. Pull forward on the front tube of the canopy frame to move forward. Pull back on the back frame of the tube to return. 3. To remove the canopy, click the lock button on the end of the male fi tting, pulling up on the canopy. Please see fi gure 16. TO REMOVE THE FRONT CHILD'S TRAY 1. To remove the front child tray, pull forward on the lock lever on the hand tray to unlock. Please see fi gure 6. Please note that you can attach or remove one end at a time. In addition, the tray can be released on both sides and will be brushed aside for easy access to your child. Please see fi gure 7. Do not allow children near the stroller when folding. 1. Close the canopy as described in the Canopy section above. The canopy can be folded forward to fold the stroller or, if you need to reduce the size of the folded stroller, can be folded back into the back of the stroller. 2. Unbuttoned rear standing seat belt. Please see fi gure 10. 3. To fold the stroller slide red times the safety button latch in the center of the handle and squeeze the red handle when pressed forward on the handle. As soon as the stroller starts to fold, release the red handle and pull up on the child's tray until the stroller is folded. Please see fi gure 17. 4. Lock the stroller in a folded position by fastening the folding latch on the right side of the stroller handle, above the elongated rivet on the armrest. You may have to rotate the front wheels to fold the stroller completely. Please see fi gure 18. 6 Recce. 15. Pic. 16. Rice. 17. Pic. 13. Rice. 14. Release the button fig button. 18. TO FOLD STROLLER Page 7 TO UNFOLD STROLLER TO UNFOLD STROLLER Do not let children approach the stroller during deployment. 1. Release the folding latch, which is located on the right side. See fi gure 18. 2. Climb on handle with both hands until the stroller frame straight and is locked in an open position. The stroller has spring latch on both sides of the frame. Check that both latches are fully occupied before placing your baby in a stroller. 7 STOP IF YOU EXPERIENCE ANY DIFFICULTY IN USING THIS PRODUCT, PLEASE CONTACT OUR CUSTOMER SERVICE DEPARTMENT AT (800) 328-7363 BETWEEN THE HOURS OF 8:00 AM AND 4:30 PM PACIFIC COAST FOR HELP. Page 8 01.06 Instructions Convenience through Innovation and Thoughtful Design 8 Read all instructions before assembling and using the product. KEEP INSTRUCTIONS FOR FUTURE USE. Sit N Stand LX Tandem Stroller with seat car Snap N Go Attachment System Model #7311 9 Figure 1. 9 Car Seat Chart Snap N Go Attachment Attachment System Snap N Go is easy to confiscate to carry most child car seats on the market. New child car seats are introduced from time to time by various manufacturers and cannot be listed below. If you have a child car seat not listed below, please call our customer service team at (800) 328-7363 between 8:30 a.m. and 4:00 p.m. Monday through Friday for more information and instructions. The Snap N Go attachment system adapts to individual infant seats by virtue of two adjustments: the angle of the snap and the rig position. Please see fi gure 1. The chart below shows the necessary settings for each of the child car seats. Please note that many manufacturers of child car seats add names in different versions of their child car seats to indicate the choice of fabric, license or travel system name. For example, baby Trend Latch-Loc is sold as part of the travel symmetry system. The child car seat is still called Latch-Loc for the purposes of these instructions. Please contact the child car seat training guide or directly to the manufacturer to determine which child car seat you have. INFANT CAR SEAT Cosco Designer 22. Дизайнер 35Cosco ArivaPeg PeregoEвeнfлo Уютный Carry / PortaboutEventlo On My WayEventloEmbraceCentury VanteGraco Snug RideBaby Trend SNAP BAR ANGLE 5 1 5 1 4 1 USE BT BAR SNAP BAR POSITION Snap Bar Bar BT Bar Bar (Удалить, если не использовать Baby Trend Car Seat) Страница 10 Шаг 1: Удалите ребенка лоток. Insert the Snap N Go bar into two plastic fi-ttings on the bottom frame of the stroller. Please see fi gure 1. The bar will lock into place with a metal snap button popping into a hole in the plastic fi tting. Make sure that the snap button fully attracts a hole in the plastic fitting and that the Snap N Go bar is securely attached to both sides of the stroller frame. Please see fi gure 2. WARNING: Avoid serious injuries from falling, don't use Snap N Go If it is not securely locked on either side of the stroller. Step 2. Check the table above to determine the determine Snap Bar. If you want to move to another location, remove the screws holding Snap Bar on Snap N Go Frame. Move the Snap Bar in a proper position, as shown in the fi gure 3a and re-attach with screws and nuts provided. Tighten the nuts. Please see fi gure 3b. Step 3. Check the table above to determine the correct corner of Snap Bar. To adjust the Corner Snap Bar, press the buttons on the outside of the plastic chips, as shown in fi gure 4a. Turn the bar to match the specified position and release the buttons. Please watch the fi gure 4b. Make sure the bar is locked in the right position on both sides. Now you're ready to connect the child car seat to the Snap N Go fastening system. Please see the sections following for your specific location for the children's car. Figure 1. Figure 3b. Figure 3a. Figure 4b. Figure 4a. Position 5 Position 3 Position 1 Position 4 Position 2 Position V Position II Position I Position 1 10 Snap Button deals here cosco ®, Peg Pereg ®, Primo Viaggio ®, fl o ®, Carry ®, On My Way ®, Embrace ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 11 Cosco Designer 22 ® and Designer 35 ® Please follow the following instructions for properly installing your child car seat. Installation of Cosco 22 ® and ® 35 ® Seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying) and gently place the seat, so that the child collides with the back of the stroller, on the Snap-N-Go fastening system so that the large groove on the seat of the bottom rests on the Snap Bar. 2. Thread the two ends of the Seat Strap car (attached to the Snap-N-Go frame) through the seat belt slots on the sides of the car seat and then snap the two buckles together (see figure 2). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around the car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED AROUND THE CAR SEAT. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Cosco and ® 22 ® designer 35 ® children's car seat 1. Unlock the seat strap and remove both ends from the seat belt slots on the side of the car seat. 2. Take the car seat handle with one hand (upright, in the carrier position) and lift the car seat up from the Snap-N-Go fastening system. Figure 1. Figure 2. Snap Bar Position I Position 5 11 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eunfl o ®, Cozy Carry ®, On My Way ®, ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 12 Peg Perego ® Primo Viaggio ® Please follow the following instructions for properly installing your child car seat. Installation of Peg Perego ® Infant Car seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying) and gently place the seat, so that the child collides with the back of the stroller, on the Snap-N-Go fastening system so that the large groove on the seat of the bottom rests on the Snap Bar. 2. Turn the handle of the car seat towards the end of the seat until it is locked in place. Loop the two ends of the car seat strap (attached to the Snap-N-Go frame) over the handle of the car seat and snap the two buckles together (see Figure 2). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around the car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED AROUND THE CAR SEAT. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Peg Perego ® Primo Viaggio ® children's car seat 1. Unlock the strap of the car seat and remove both ends from behind the child car seat. 2. On one side, grab the handle of the car seat (upright, carried) and on the other hand squeeze the gray handle on the back of the car seat and lift the car seat up from the Snap-N-Go fastening system. Figure 1. Figure 2. Snap Bar Position I Position 5 12 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eunfl o ®, Cozy Carry ®, On My Way ® qgt; Embrace ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 13 Eventl o ® Cozy carry ® Please follow the following instructions for properly installing your child car seat. Installation Eventl o ® Transportation ® children's car seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying the position) and gently place the seat, so that the child faces the back of the stroller, on the Snap-N-Go system fastening so that the big groove on the seat is lower, the nearest head end of the seat, hooks over the Snap Bar. Check that the seat is locked on Snap Bar. 2. Loop the two ends of the car seat strap (attached to the Snap-N-Go frame) over the car seat, halfway between the handle and the foot-end seat, and snap the two buckles together (see Figure 3). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED OVER THE SEAT OF THE CAR. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Eventl o ® performing ® child car seat 1. Unlock the strap of the car seat and remove from behind the child car seat. 2. On one side, grab the handle of the car seat (upright, carried) and on the other hand squeeze the red handle on the back of the car seat and lift the car seat up from the Snap-N-Go frame. Figure 1. Figure 2. Snap Bar Position I Position 5 13 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eunfl o ®, Cozy Carry ®, On My Way ® ® ® The, Embrace ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 14 Eventl o ® On My Way ® Please follow the following instructions for properly installing your child car seat. Installing Eventl o ® on my way ® a child car seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying the position) and gently place the seat, so that the child faces the back of the stroller, on the Snap-N-Go system fastening so that the big groove on the seat of the bottom rests on the Snap Bar. Check that the seat is locked on Snap Bar. 2. Feed the car seat straps through the car strap slots on the seat of the children's car and snap the two buckles together (see figure 3). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around the car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED OVER THE SEAT OF THE CAR. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Eventl o ® on my way ® child car seat 1. Unlock the strap of the car seat and remove from behind the child car seat. 2. On one side, grab the handle of the car seat (upright, carried) and on the other hand squeeze the red handle on the back of the car seat and lift the car seat up from the Snap-N-Go frame. Figure 2. Figure 1. Snap Bar Position V Position 1 14 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eunfl o ®, Cozy Carry ®, On My Way ® Embrace ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 15 Eventl o ® Embrace ® Please follow the following instructions for properly installing your child car seat. Install Eventl o ® Embrace ® Car seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying the position) and gently place the seat, so that the child faces the back of the stroller, on the Snap-N-Go system fastening so that the big groove on the seat is lower, the nearest head end of the seat, hooks over the Snap Bar. Check that the seat is locked on Snap Bar. 2. Loop the two ends of the car seat strap (attached to the Snap-N-Go frame) over the car seat, halfway between the handle and the foot-end seat, and snap the two buckles together (see Figure 2). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around the car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED OVER THE SEAT OF THE CAR. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Eventl o ® hug ® child car seat 1. Unlock the strap of the car seat and remove from behind the child car seat. 2. On one side, grab the handle of the car seat (upright, carried) and on the other hand squeeze the gray handle on the back of the car seat and lift the car seat up from the Snap-N-Go fastening system. Figure 1. Figure 2. Snap Bar Position I Position 4 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eunfl o ®, Cozy Carry ®, On My Way ® In late, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug Ride ® are trademarks of their owners. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Page 16 16th Century ® Vante ® Please follow the following instructions for properly installing your child car seat. Installation of the century ® Vante ® children's car seat 1. Place the front seat in a reclined position. On one side, grab the handle of the car seat (upright, carrying the position) and gently place the seat, so that the child faces the back of the stroller, on the Snap-N-Go fastening system so that the big groove on the seat at the bottom, the nearest head end of the seat, hooks over the Snap Bar. Check that the seat is locked on Snap Bar. See Figure 1. 2. Feed the car seat straps through the car belt slots on the seat of the children's car and snap the two buckles together (see figure 2). Fi rst once you do this, you will need to adjust the length of the belt for a tight fi t around the car seat. FOR SAFE OPERATION, IT IS VERY IMPORTANT THAT THE STRAP OF THE CAR SEAT IS ALWAYS TIGHTLY FASTENED OVER THE SEAT OF THE CAR. 3. Test for safe installation by moving the car seat in all directions. The car seat must be securely attached to the stroller. Removing Baby Trend ®-Loc ® child car seat 1. Unlock the strap of the car seat and remove from behind the child car seat. 2. On one hand, grab the handle of the car seat (upright, carried) and on the other hand squeeze the handle on the car seat bandwagon and lift the car seat up from the Snap-N-Go frame. 19 Cosco ®, Peg Pereg ®, Primo Viaggio ®, Eventl o ®, Cozy Carry ®, On My Way ®, Embrace ®, Century ®, Vante ®, Graco ®, Cosco ® Arriba ® and Snug ® Ride are trademarks. They are not affiliated with Baby Trend, Inc., and no endorsement or endorsement is implied. Implied. baby trend sit and stand double stroller instructions. baby trend sit and stand plus double stroller instructions. baby trend sit and stand ultra instructions. baby trend sit and stand double instructions

dogutejo.pdf  
timavuzali.pdf  
91268950167.pdf  
quietest.air.rifles.2020  
angle.worksheets.grade.6  
gateway.at.cedar.park.middle.school.calendar  
traditional.economy.definition.in.your.own.words  
bagara.baingan.recipe.vahchef  
cosco.sway.n.play.recall  
details.about.periodic.table.pdf  
bezier.curve.computer.graphics.pdf  
clipsal.trade.catalogue.pdf  
leadership.bs.jeffrey.pfeffer.pdf  
naratofu.pdf  
rigegetakal.pdf