


☐

I'm not robot

  
reCAPTCHA

Continue

Baby trend expedition elx manual

Free Shipping Free Shipping on All Requests 100% Satisfaction Guarantee We Guarantee Customer Satisfaction First Line Support We are behind our Products Safe Payments Announcement ► Roll to page 2 of 6 ads Thank you for your participation! \* Your assessment is very important to improve the work of artificial intelligence, which forms the content of this project PROBLEM SHOT WHEEL ADJUSTMENT: It should be noted that all three-wheeled vehicles can be easily influenced to deviate from a straight line. In most cases, strollers may have a tendency to pull right/left due to many factors. Including uneven tire pressure, improper wheel installation, road conditions and manufacturing tolerances. If you find the baby trend cart to track or pull significantly left or right while using flat terrain, follow the sequence of instructions on page 3/page 5 to realign your Front Wheel. IF YOU HAVE ANY DIFFICULTY IN USING THIS PRODUCT, PLEASE CONTACT OUR CUSTOMER SERVICE DEPARTMENT AT 1-800-328-7363 BETWEEN 8:00 AM AND 4:30 PM STANDARD TIME FOR ASSISTANCE. PLEASE HAVE YOUR MODEL NUMBER AND MANUFACTURING DATE AVAILABLE WHEN YOU CALL. THIS INFORMATION CAN BE FOUND ON A SMALL STICKER INSIDE THE CART FRAME. Convenience through innovation and considerate design Contact us by mail: Baby Trend, Inc. 1607 S. Campus Ave., Ontario, CA 91761 FLAT TIRE: The race cart features bicycle tires to allow for prolonged wear and ease of pushing. Just like a bicycle tyre, the race cart can suffer from flat tires. If you have a flat tire, you can use a standard bicycle tire repair kit to repair the tire or you can take the tire to a bike shop for repair. If you try numerous flat tires, you may want to buy thorn-proof inner tubes for the race cart. These can be purchased at bicycle shops or in many national stores. The correct size to buy is shown on the side wall of the tire. Contact us by phone: 1-800-328-7363 (8:00am ~ 16:30 PST) or online Read all instructions BEFORE assembly and use of the product. KEEP INSTRUCTIONS FOR FUTURE USE. ELX Shipping Instruction Manual Convenience through innovation and thoughtful design www.babytrend.com Racing Cart 04.08 ASSEMBLY MONTAJE ASSEMBLEE Fig. 15a Fig. 15a Short Clip Hook Corto Fig. 16 Staple courte 17 Copyright © 2011, Baby Trend Inc., All Rights Reserved. All them reserved derechos. Tous droits réservés. • Position the child seat so that it is facing the back of the stroller and the I nod between a diaanteira tray and no place. (Fig. 15b) • To place the Baby Trend Car Seat, place the backrest in the highest position. (Fig. 15a) Make sure the front child tray is firmly attached to the armrest armrests O Carrito. Place la Sillita para el Automàvil en direccion a la parte trasera del carrito, so el amazon de la sillita is incorporated a la bandeja delantera y se prone bien. (Fig. 15b) - To join the Baby Trend car seat, lift the back of the seat to the highest position. (Fig. 15a) Make sure that the child tray is securely attached to the stroller's armrests. Place the car seat facing the back of the cart and the seat shell is properly mounted and securely locked the tray. (Fig. 15b) 16) - When the child seat is firmly locked in place, tie the only short clip over the child seat car seat through the seat belt slot in the child seat. (Fig. 16) VERY IMPORTANT THAT THE SHORT CLIP IS ALWAYS WELL ATTACHED AROUND THE CHILDREN'S CAR. Verifique que la sillita para el automàvil esté firmemente trabada en la bandeja para nios, luego fije la sillita infantil para el altomàvil con el gancho corto en la ranura y gua ubicada en la sillita infantil para el automàvil. (Fig. 16) MUY IMPORTANT TIE BIEN EL GANCHO CORTO ALREDEDOR DE LA SILLITA INFANTIL PARA EL AUTOM-VIL. With the car seat installed, connect the only short clip over the baby's car seat through the seat belt slot on the baby seat. (Fig. 16) IT IS VERY IMPORTANT THAT THE SHORT CLIP IS ALWAYS TIGHT AROUND THE BABY CAR. 17) - To remove the child seat, tighten the release strap located at the end of the seat foot and carefully lift up the seat. (Fig. 17) - To remove la Sillita para el Autom-vila, apriete la manija de liberacion ubicada en el extremo inferior del asiento y levante cuidadosamente la silla. (Fig. 17) - To remove the seats from the children's car, press the handle at the end of the seat and lift the top of the seat. (Fig. 17) MULTI-POSITION HANDLE MANIJA AJUSTABLE PLESE 18) - To adjust the handle, press the red buttons to move the handle up or down to a comfort position for the user (Fig. 18) - To adjust lal manija, seize them from the rojos a la misma buttons to adjust a c-mode level. (Fig. 18) - To adjust the handle, press the two red buttons to move the handle to a comfortable position for the user. (Fig. 18) It is Before you put your children in the cart, follow the instructions below. Before putting a su hijo en el carrito, siga las instrucciones que figuran ms abajo. Before placing your children in the cart, follow the instructions below. meiéndolo WARNING: ES a recommended age/weight for your baby in a whole stroller. WARNING: Being pushed so that the cart does not roll. NEVER leave stroller alone on a hill or slope like stroller slide down the hill. WARNING: Pediatrician the age or weight recommended to start carrying your baby in an all-terrain stroller. SAFETY SEGURIDAD LA SÉCURITÉ Always check with your pediatrician forever until the brakes when the cart is not Siempre check con su Copyright © 2011, Baby Trend Inc., All Rights Reserved. All rights reserved. Tous droits réservés. Fig. 17 Fig. 18 18 18